MIL-P-14137B (PA)
28 February 1974
SUPERSEDING
MIL-P-14137A (MU)
12 December 1963 and
MIL-P-60012 (MU)
12 December 1963
(see 6.5)

MILITARY SPECIFICATION

PRIMER, STAB M106
PARTS FOR,
LOADING, ASSEMBLING AND PACKING

*This specification is approved for use by all Departments and Agencies in the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for, loading, assembling and packing for one type of primer designated as Primer, Stab, M106.

*2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-A-2550 - Ammunition, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-650 - Explosives: Sampling, Inspection and Testing
MIL-STD-1168- Lot Numbering of Ammunition

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

MIL-STD-1235- Single and Multilevel Continuous Sampling and Procedures and Tables For Inspection by Attributes

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGING DRAWINGS

8796462 - Primer, Stab M106 Assembly
9258182 - Box, Set-Up, Packing, Ammunition, Inner for Small Explosive Components
9258183 - Box, Set-Up, Packing, Ammunition Outer for Small Explosive Components
9258184 - Box, Packing, Ammunition for Small Explosive Components

INSPECTION EQUIPMENT DRAWINGS

8816014 - Ball, Adapter
8816367 - Holder, Firing Pin
8816368 - Lead Disc
8827828 - Plastic Sleeve
9200012 - Firing Pin
9200602 - Bushing
9200985 - Set-Up Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Primers. - The primers shall comply with all requirements specified on drawing (dwg.) 8796462, and with all requirements specified in applicable specifications.

3.3 Moisture content

3.3.1 Lead azide. - The moisture content of the lead azide used in loading the primers shall not exceed 0.50 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

3.3.2 Primer mixture. - The moisture content of the primer mixture used in loading the primers shall not exceed 0.30 percent.

3.4 Functioning

3.4.1 Output. - The primer shall function on the first attempt when an energy of 4.90 inch ounces, maximum (max.) is applied, and shall cause perforation of a .1345 inch thick lead disc, to a diameter of not less than 1/8 inch.

3.4.2 Waterproofness. - The primer shall comply with the requirements of 3.4.1 after being submerged in water at a minimum depth of 2 inches for not less than 48 hours, at a temperature of 75 degrees Fahrenheit (F) plus or minus 5 degrees.

3.5 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.6 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

*4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the suppler may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of product. - At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications, referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

*4.2 First article inspection

4.2.1 Submission. - Prior to the start of regular production, the contractor shall submit a first article sample (see 6.1.c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of three hundred forty (340) loaded primers and 50 complete sets of parts and subassemblies (i.e., 50 each of every component and every subassembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

with the sample, including certificates of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed. - Components and subassemblies will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection. - If any component or subassembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any component or subassembly in the sample to comply with any of the stated requirements.

4.2.4 Loaded Primers. - A sample of three hundred forty (340) loaded primers shall be submitted in accordance with 4.2.1 and tested as specified in 4.3.3.3.

*4.3 Inspection Provisions

4.3.1 Lot Formation. - The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with the applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications, and same specification revisions, and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government shall not be deemed to alter the homogeneity of

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded primer assemblies shall contain:

a. Parts of one lot interfix number from one supplier.
b. Primer mixture consisting of batches, blended by the same process, each ingredient being from not more than 2 lots from one manufacturer.
c. Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant.

*4.3.2 Examination. - The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and the AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Disc, primer (see dwg. 8797326 covering a detail of dwg. 8796462).

Categories	Defects	Method of Inspection	Code NO. (see 6.2)
Critical: None defined			

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Diameter	Gage	01001
102.	Thickness	Gage	01002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	01003

4.3.2.2 Disc, primer closing (see dwg. 8797325 covering a detail of dwg. 8796462).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Diameter	Gage	02001
102.	Thickness	Gage	02002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	02003

4.3.2.3 Cup, primer (see dwg. 8797327 covering a detail of dwg. 8796462).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.00 percent		
101.	Diameter of hole,min.	Gage	03001
102.	Concentricity of flash hole with outside diameter	Gage	03002
103.	Thickness through bottom	Gage	03003
104.	Length	Gage	03004
105.	Outside diameter	Gage	03005
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	03006

4.3.2.4 Primer assembly (see dwg. 8796462).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Cup split or cracked	Visual	04001
Major:	AQL 0.65 percent		
101.	Outside diameter, max.	Gage	04002
102.	Length, max.	Gage	04003
103.	Identification color missing or incorrect	Visual	04004
Minor:	AQL 2.50 percent		
201.	Outside diameter, min.	Gage	04005
202.	Length, min.	Gage	04006
203.	Seal incomplete	Visual	04007
204.	Disc wrinkled	Visual	04008
205.	Crimp less than 360 degrees ...	Visual	04009
206.	Evidence of poor workmanship (see 3.5)	Visual	04010

4.3.2.5 Box, set-up, inner, after loading and prior to closing slide cover (see dwg. 9258182).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Filler and cushion assembly missing	Visual	05001
2.	Filler and cushion assembly improperly assembled	Visual	05002
3.	Stiffener missing	Visual	05003
4.	Slide cover assembled reversed ..	Visual	05004
Major:	AQL 0.40 percent		
101.	Release paper missing	Visual	05005
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	05006
202.	Evidence of poor workmanship (see 3.5)	Visual	05007

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

4.3.2.6 Box, set-up, outer; with inner set-up boxes assembled and prior to assembling top and sealing strip (see dwg. 9258183).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Red surfaces on inner set-up boxes do not alternate on same side of outer set-up box	Visual	06001
2.	Stiffener not facing one direction	Visual	06002
Major:	None defined		
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	06003
202.	Evidence of poor workmanship (see 3.5)	Visual	06004

4.3.2.7 Box, packing, ammunition prior to assembling cover and strapping (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Bags containing set-up boxes damaged	Visual	07001
102.	Cushioning material incomplete or missing from around outer set-up boxes	Visual	07002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	07003

4.3.2.8 Box, packing, ammunition (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

Critical: None defined

Major:	AQL 0.65 percent		
101.	Strapping missing, broken, loose or improperly fastened ...	Visual/ Manual	08001
102.	Box damaged	Visual	08002
103.	Marking missing, incomplete or illegible	Visual	08003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	08004

4.3.3 Testing

4.3.3.1 Moisture content of lead azide (see 3.3.1) - Major defect - Code No. 04011. - The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample shall be selected and tested as specified in 4.4.1. If the moisture content is in excess of the percentage specified and loading has not yet begun, the lot of lead azide shall be rejected. If loading has begun, action on the unloaded lead azide shall be as specified above and all primers loaded with the questionable lead azide shall be rejected.

4.3.3.2 Moisture content of primer mixture (see 3.3.2) - Major defect - Code No. 04012. - The moisture content of the primer mixture shall be determined for each lot at the time of loading. A sample shall be selected and tested as specified in 4.4.2. If the moisture content is in excess of the percentage specified and loading has not yet begun, the lot of primer mix shall be rejected. If loading has begun, action on the unloaded primer mix shall be as specified above and all primers loaded with the questionable primer mix shall be rejected.

4.3.3.3 Functioning

4.3.3.3.1 Output (see 3.4.1) - Major defect - Code No. 04013. - A sample of 315 primers shall be selected at random from each lot. If 3 or more primers fail to comply with the requirements specified, the lot shall be rejected. If one or two defects are found, a second sample of 315 shall be selected at random and tested. If, in the combined first and second sample, a total of 4 or more defects are found, the lot shall be rejected. The test shall be performed as specified in 4.4.4.1 using test equipment as specified in 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

4.3.3.3.2 Waterproofness (see 3.4.2) - Major defect - Code No. 04014. - A sample of 25 primers shall be selected at random from each lot. If one or more detonators fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.4.2, using test equipment specified in 4.3.4 and 4.4.4.1.

4.3.3.4 Composition of primer mixture (see dwg. 8796462) - Major Defect - Code No. 04015. - A sample of approximately 0.5 grams shall be selected from each batch or blend of batches of primer mixture and tested as specified in 4.4.3. The batch or blend of batches shall be rejected if one or more of the requirements are not met.

4.3.3.5 Heat seal test of sealed bag (see dwg. 9258183) - Major Defect - Code No. 08004. - Sampling, acceptance criteria, and test procedures for this test shall be as specified in MIL-P-116.

*4.3.4 Inspection Equipment. - Inspection equipment required to perform the inspections prescribed in this specification is identified in the examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval.

4.4 Test Methods and Procedures

4.4.1 Moisture content of lead azide. - The moisture content of the lead azide shall be determined in accordance with MIL-STD-650, Method 101.5 except, use a two gram sample and cover the dish with a sheet of polytetrafluoroethylene.

4.4.2 Moisture content of the primer mixture. - The moisture content of the primer mixture shall be determined as specified in 4.4.1 except that the drying temperature shall be 60 plus or minus 5 degrees C. and only 0.40 to 0.70 grams of ignition mixture shall be dried.

4.4.3 Composition of primer mixture. - The sample shall be dried to constant weight and then tested in the following sequence:

4.4.3.1 Percentage of Barium Nitrate. - Three milliliters of lead azide saturated in distilled water shall be added at a temperature of 5 degrees plus or minus 3 degrees C., agitated for 1 minute, and if necessary, any lumps shall be broken up with a rubber policeman

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

attached to a glass rod. Suction shall be applied. This procedure shall be repeated five times, making a total of six, 3 mol. extractions. The sample in the filtering crucible shall be rinsed three times with alcohol, dried in an oven maintained at 60 degrees plus or minus 5 degrees C. for 30 minutes, cooled in a desiccator and weighed. The loss in weight shall be calculated as the percentage of barium nitrate in the sample on a dry basis as follows:

$$\text{Percent of Barium Nitrate} = \frac{A - B}{W} \quad (100)$$

where:

W = Weight of dry sample
A = Weight of crucible and dry sample.
B = Weight of crucible and sample after extractions with lead azide saturated water.

4.4.3.2 Percentage of basic lead styphnate. - The residue obtained in the determination of barium nitrate shall be extracted with six ml. portions of saturated ammonium acetate solution at about 25 degrees C. (Hot saturated ammonium acetate shall not be used as it dissolves antimony sulfide to some extent) agitating each portion for about 30 seconds and allowing each portion to remain in contact with the residue for approximately 2 minutes. The residue shall be washed with water until the filtrate coming through the crucible appears colorless. The wet residue obtained in the determination of basic lead styphnate shall be washed three times with alcohol, dried in an oven maintained at 60 degrees, plus or minus 5 degrees C. for 30 minutes, cooled in a desiccator and weighed. The loss in weight shall be considered as the percentage of basic lead styphnate.

4.4.3.3 Percentage of tetracene. - The dried residue in the crucible shall be transferred to a 125 ml. beaker with a stream of water 25 ml. of water shall be added, and the contents of the beaker boiled on a hot plate for 5 minutes. The contents of the beaker shall be poured into the same crucible, and the residue in the crucible washed three times with boiling water, and finally with alcohol. The crucible and contents shall be dried in an oven maintained at 60 degrees C. for 30 minutes, cooled in a desiccator and weighted. The loss in weight shall be calculated as the percentage of tetracene in the sample on a dry basis as follows:

$$\text{Percent of Tetracene} - \frac{(C - D)\ 100}{W\ (1.01M)}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

where:

C = Weight of crucible and residue after extraction with saturated ammonium acetate solution.
D = Weight of crucible and residue after treating with hot water.
W = Weight of the sample.
M = Moisture content of sample, percent.

4.4.3.4 Percentage of antimony sulfide. - The weight of the residue shall be calculated from the determination of tetracene to percentage antimony sulfide in the sample on a dry basis as follows:

$$\text{Percent of antimony sulfide} = \frac{(D - E)\ 100}{W(1-.01M)}$$

where:

D = Weight of crucible and sample after treating with hot water.
E = Weight of crucible.
W = Weight of sample.
M = Moisture content of sample, percent.

4.4.3.5 Percentage of lead azide. - The lead azide content in the sample shall be determined by subtracting from 100 the combined percentages of barium nitrate, basic lead styphnate, tetracene and antimony sulfide.

*4.4.4.1 Functioning

4.4.4.1 Output. - The primer shall be assembled to the applicable test equipment and a steel ball weighing a maximum of 1.96 ounces shall be dropped from a maximum height of 2.5 inches on the firing pin of the test set-up. A primer that fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective. Method of Inspection shall be in accordance with dwg. 8816014, 8816367, 8816368, 8827828, 9200012, 9200602 and 9200985.

4.4.4.2 Waterproofness. - The primer shall be immersed under water as specified for the time specified. Within one hour after removal from the water the primer shall be subjected to the output test specified in 4.4.4.1. Any primer which fails to fire shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

*5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C. - Packaging shall be as specified on dwgs. 9258182 and 9258183.

5.2 Packing

5.2.1 Level C. - Packing shall be as specified on dwg. 9258184.

5.3 Marking. - Marking of all packaging and packing shall comply with dwgs. 9258182, 9258183 and 9258184.

*6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. The contractor must include in his submission of designs a listing of any and all Government SIE

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

designs which will be utilized. Partial submission of inspection designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Check test for possible deterioration. - The following test is designed to prevent major ammunition items being loaded with primers that may have deteriorated. This test shall be performed on detonators from each lot which has been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are loaded does not require a check test, the contracting officer shall insert into the contract a check test performance provision. The contracting officer will arrange for the contractor to be reimbursed for expenses incurred in the performance of the deterioration check test.

6.4.1 Functioning. - A sample of 315 primers shall be selected at rondom from each lot. If 4 or more primers fail to comply with the requirement specified, the lot shall be rejected. If more than one defect is found, a second sample of 315 shall be selected at random and tested. If in the combined first and second sample a total of 5 or more defects are found, the lot shall be rejected. The test shall be performed as specified in 4.4.4.1 using test equipment as specified in 4.3.4.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.6 Supersession data. - This specification includes the requirements of MIL-P-60012 (MU) dated 12 December 1963.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1390-A-020

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. *Fold on lines on reverse side, staple in corner, and send to* preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an *envelope addressed to preparing activity.*

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.