MIL-P-14145C
3 June 1977
SUPERSEDING
MIL-P-14145B
9 September 1971

MILITARY SPECIFICATION

PRINT WASHER, PHOTOGRAPHIC:

ROTARY PAN TYPE, (EK-4)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a water-powered rotary, tub-type, photographic-print washer, Joint Photographic Type Designation EK-4.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

FSC 6740

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

L-P-383	- Plastic Material, Polyester Resin, Glass Fiber Base, Low Pressure Laminated.
QQ-S-781	- Strapping, Steel, and Seals.
WW-C-624	- Coupling Assembly, Hose (Garden, Water, and Water Suction).
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-P-40	- Packaging and Packing of Hand Tools.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-P-4672	- Paper, Photographic, Black and White, Sensitized.
MIL-F-26615	- Fixing Bath, Conventional Photographic, Acid Hardening.

STANDARDS

FEDERAL

FED. TEST METHOD STD. No. 101	- Preservation, Packaging, and Packing Materials: Test Procedures.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.
MS35842	- Clamp, Hose: Low Pressure Type "F".

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167	- Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.
A 380	- Cleaning and Descaling Stainless Steel Parts, Equipment, and Systems.
A 569	- Steel, Carbon (0.15 Maximum, Percent), Hot-Rolled Sheet and Strip, Commercial Quality.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The print washer shall consist of a perforated circular basket designed to revolve around a vertical axis within an outer stationary circular pan, and a water jet spraying arrangement. The basket shall revolve, powered solely by the force of the jet spray. The washer shall be supported on a knockdown-type stand.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

3.2 First article (first-produced washer). The contractor shall furnish one or more washers as specified (see 6.2) for examination and testing within the time frame specified (see 6.2) to prove that his production methods and choice of design detail will produce washers that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.8).

3.3.1 Stainless steel. Stainless steel shall conform to ASTM A 167, Type 316.

3.3.2 Carbon steel. Carbon steel shall conform to ASTM A 569.

3.3.3 Plastic material. Glass-reinforced plastic laminate shall conform to L-P-383, Type I.

3.4 Pan. The outer pan shall be of stainless steel as specified in 3.3.1, or when specified (see 6.2), shall be of glass-reinforced plastic laminate as specified in 3.3.3. The pan shall be not less than 47.0 inches in diameter and not less than 5.5 inches deep. Provision shall be made for draining. A vertical basket support bearing shall be provided. The pan shall not leak and shall be stationary when resting directly on the stand.

3.5 Basket. The inner basket shall be of stainless steel as specified in 3.3.1 and shall be not less than 45.5 inches in diameter and not less than 3.0 inches deep. The basket shall be supported on a ball-bearing-type mount or on a ball- and sleeve-bearing-type mount, and shall be mated to the vertical basket support bearing in the outer pan. The basket shall rotate freely under the action of the spray jets when fully loaded with prints (see 3.12) with the pan level, and with the pan tilted from the level position by raising any quadrant of the pan 0.5 inch. The basket shall have openings in the bottom, or sides, or both, to allow chemical-laden wash water to drain into the pan. These openings shall have an outward taper to prevent scratching or damaging the prints.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

3.6 Jet spraying apparatus. When operating, the water jet spray shall keep the prints from bunching, provide the necessary agitation of the prints, and provide the rotational force for the inner basket. The jet spray apparatus shall be fabricated of stainless steel as specified in 3.3.1 or tinned brass.

3.7 Water inlet. The water inlet shall be fabricated of stainless steel as specified in 3.3.1 or tinned brass, and shall be provided with a 3/4-inch internal thread garden-hose-type coupling. When specified (see 6.2), a shut-off globe valve shall be provided.

3.8 Drainage system. The drainage system shall be fabricated of stainless steel as specified in 3.3.1 or tinned brass, and shall maintain a balanced rate of flow between the water inlet and outlet. Provision shall be made for complete draining of the washer without removal from the stand. The drainage system shall terminate in a single 3/4-inch external thread garden-hose-type coupling. When specified (see 6.2), the drainage system shall terminate with a 3/4-inch hose nipple.

3.9 Stand. The metal stand shall be fabricated of carbon steel as specified in 3.3.2. The stand shall be rigid when assembled and shall support the fully loaded washer. A leveling screw and pad shall be incorporated into each foot. The stand shall be bolted or fitted together in such a manner so as to be readily disassembled with common handtools for the purpose of shipment or storage.

3.10 Couplings. Hose couplings shall conform to WW-C-624, Type A, Size 3/4-inch, style optional.

3.11 Hose. Two sections of 3/4-inch synthetic rubber or flexible plastic garden-type hose, each section not less than 8 feet in length, shall be furnished with each washer. The inlet hose shall withstand not less than 50 pounds per square inch (psi) internal water pressure without leakage or damage, and shall be equipped with a 3/4-inch internal thread garden-hose-type coupling on one end, and a 3/4-inch external thread garden-hose-type coupling on the other end. Unless otherwise specified (see 6.2), the drain hose shall have one end terminated in a 3/4-inch internal thread garden-hose-type coupling. When specified (see 6.2), a hose clamp conforming to MS35842 may be substituted for the coupling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

3.12 Capacity. The washer shall be capable of washing not less than 60 double-weight 9.0 inch by 18.0 inch semi-matte photographic prints on nonwaterproof stock in 40 minutes.

3.13 Dimensions. The washer shall be not more than 50.0 inches in overall diameter. The stand shall be 35.5 inches, plus or minus 1.0 inch, on each side. The overall height of the washer and stand shall be not less than 36.0 inches nor more than 45.0 inches.

3.14 Lubrication. All surfaces requiring lubrication shall be provided with a means for lubricating. The washer shall operate as specified herein when lubricated with military lubricants (see 6.7).

3.15 Identification marking. The washer shall be identified in accordance with MIL-STD-130. The marking shall be applied to the washer on plates conforming to MIL-P-514, Type I, Style 3, Composition C of Type I, Grade A, Class 1 material. Plates shall be attached by screws, bolts, or rivets in a location where the plate will be both visible and legible.

3.16 Stainless steel parts. All fabricated stainless steel parts shall be cleaned and descaled in accordance with ASTM A 380.

3.17 Treatment and painting. The portions of the washer normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, Type A, color as specified (see 6.2).

3.18 Workmanship. All external components and assemblies of the washer shall be clean and free from cracks, tears, burrs, and sharp edges. Contact and bearing surfaces shall be true to allow for ease of fit and movement.

3.18.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. All bends shall be made with controlled means to insure uniformity of size and shape. Precautions shall be taken to avoid overheating. Heated steel shall be allowed to cool slowly.

3.18.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, mill scale that can be removed by chipping and wire brushing, and other foreign matter. All weldments

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

shall be free of impurities detrimental to either the appearance or strength of the weldment. Unless otherwise specified (see 6.2), the welding process used in fabricating the washer shall be at the option of the contractor.

3.18.3 Bolted connections. Boltholes shall be accurately formed and shall have the burrs removed. Washers or lockwashers shall be provided where necessary. Matching thread areas securing bolts conforming to SAE J429 or capscrews shall be of sufficient strength to withstand the tensile strength of the bolt. All fasteners shall be correctly torqued and shall have full thread engagement. Bolts shall protrude not more than two full threads.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First-produced washer inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First-produced washer inspection.

4.3.1 Examination. The washer shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

4.3.2 Tests. The washer shall be tested as specified in 4.5.2. Failure to pass any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, Inspection Level III.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. AQL shall be 2.5 percent defective.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The washer shall be examined as specified herein for the following major defects:

101. Dimensions not as specified.
102. Material not as specified.
103. Components missing or not as specified.
104. Basket does not revolve as specified.
105. Lubrication provisions not as specified.
106. Stainless steel parts not cleaned and descaled as specified.
107. Identification marking not as specified.
108. Treatment and painting not as specified.
109. Workmanship not as specified.

4.5.2 Tests.

4.5.2.1 Wash test conditions.

4.5.2.1.1 Solution. Prepare a stock test solution by dissolving 0.3 gram of potassium permanganate and 0.6 gram of sodium hydroxide in 180 cc of distilled water; add sufficient distilled water to make 250 cc of stock solution. Add 1 cc of the stock solution to 250 cc of distilled water to prepare the dilute test solution.

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:54Z
Check the source to verify that this is the current version before use.

4.5.2.1.2 Wash water. Prior to the wash test, test the wash water as follows to insure that it contains no dissolved substance which will cause erroneous test results: Place 1/2 ounce of the dilute test solution in a clean container and add 3/4 ounce of wash water. No change in the color of the test sample after 1-1/2 minutes indicates the wash water is free of substances which would cause erroneous test results. If a change of color occurs, another source of wash water must be used which results in no change of color.

4.5.2.2 Wash test procedure. Soak not less than sixty 9.0 inch by 18.0 inch nonwaterproof photographic prints conforming to MIL-P-4672, type optional, Subtype D in a standard hypo fixing bath conforming to MIL-F-26615 for not less than 5 minutes. (Some of the prints may be fogged; an image is not required on all prints.) Place the hypo-wet prints in the washer and wash for 40 minutes. The water supply pressure to the washer shall not exceed 20 psig. Hoses and stand shall be used in this test. Remove three or four prints from the washer, one from the bottom, one from the top, and one from the middle of the mass of prints, or one from each quadrant. Allow the water to drain from the prints until they begin to drip. Then allow the water to drip from the prints into 1/2 ounce of the dilute test solution for 30 seconds. No change in color of the test solution after 1-1/2 minutes indicates the prints are sufficiently washed. A change in color of the test solution to a yellow-orange in approximately 1/2 minute or to colorless in 1 minute indicates an excess of residual hypo is present in the wash water. Either of these changes in color of the test solution shall constitute failure of this test.

4.5.2.3 Rigidity. While the washer is operating, raise one edge of the outer pan or one leg of the stand 0.5 inch. Any leaking, or failure of the basket to turn by pressure of the jet spray only, shall constitute failure of this test.

4.5.2.4 Leakage. Fill the pan with water to its maximum holding level and allow to stand for 1 hour. Cap the hose and subject to 50 psi water pressure. Any evidence of leakage shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

4.6 Inspection of packaging.

4.6.1 Preproduction pack inspection.

4.6.1.1 Examination. The preproduction pack shall be examined for defects listed in 4.6.2.3. Presence of one or more defects shall be cause for rejection.

4.6.1.2 Test. The preproduction pack shall be drop tested in accordance with Method 5007 of FED. TEST METHOD STD. No. 101, Procedures B and E. Rupture of the pack or any physical damage to the washer components shall constitute failure of the pack and shall be cause for rejection.

4.6.2 Quality conformance inspection of pack.

4.6.2.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.2.3 Examination. Samples selected in accordance with 4.6.2.2 shall be examined for the following major defects. AQL shall be 2.5 percent defective.

110.	Materials, methods, or containers not as specified. Each incorrect material, method, or container shall be considered one defect.
111.	Unprotected metal surfaces not coated with preservative for Level A.
112.	Hose not coiled and secured as specified for Level A.
113.	Repair parts not preserved as specified.
114.	Maintenance tools not preserved as specified.
115.	Consolidation not as specified for Level A.
116.	Cushioning, blocking, and bracing not as specified for Level A.
117.	Marking illegible, incomplete, incorrect, or missing.
118.	Strapping not as specified for Level A or Level B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

5: PACKAGING

5.1 Preproduction pack. When specified (see 6.2), the contractor shall furnish a preproduction pack for examination and testing within the time frame specified (see 6.2) to prove prior to starting production packaging that the applied preservation, packing, and marking comply with the packaging requirements of this specification. Examination and tests shall be those specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.4). The preproduction pack may be prepared utilizing either the preproduction model or a production washer. When the preproduction model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction model and production washers.

5.2 Preservation. Preservation shall be Level A or Commercial, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Unprotected metal surfaces. Unprotected metal surfaces of the washer and unassembled stand requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative, except that no preservative shall be applied to the bearing. The preservative shall conform to the applicable specification listed in MIL-P-116 and shall be applied in accordance with MIL-P-116.

5.2.1.2 Hose. The hose shall be coiled and the coil secured with cotton tape or twine. The hose shall be placed in the washer.

5.2.1.3 Technical publications. The technical publications shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3.

5.2.1.4 Repair parts. The preservation application criteria and applicable submethods of preservation in MIL-P-116 shall be used to preserve the repair parts.

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:54Z
Check the source to verify that this is the currentversion before use.

5.2.1.5 Maintenance tools. Maintenance tools shall be preserved in accordance with PPP-P-40.

5.2.1.6 Consolidation. The repair parts, technical publications, and maintenance tools for each washer shall be consolidated in a close-fitting box conforming to PPP-B-636, W5c, style optional.

5.2.2 Commercial. Each complete print washer shall be preserved to afford protection against deterioration and damage during shipment from the contractor to the initial destination.

5.3 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.3.1 Level A. Each washer, with stand, repair parts, and maintenance tools, shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B. Cushioning, blocking, and bracing shall be in accordance with MIL-STD-1186. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.3.2 Level B. Each complete washer, with stand, repair parts, and maintenance tools, shall be packed as specified in 5.3.1 for Level A except that the box shall be Domestic Type and strapping shall be Finish A or Finish B.

5.3.3 Commercial. The preserved print washer shall be packed in exterior shipping containers to meet common carrier acceptance, and provide safe delivery to destination at lowest rates in compliance with carrier rules applicable to the mode of shipment.

5.4 Marking.

5.4.1 Military. Marking shall be in accordance with MIL-STD-129.

5.4.2 Commercial. Marking shall be by any means which provides legibility and shall include the national stock number (NSN) or part number, nomenclature, quantity and unit of issue, contract purchase order, delivery order number, and address.

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:54Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Intended use. The washer is used to wash chemicals from large quantities of photographic prints.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of first-produced washer and number of washers required (see 3.2).
(c) When outer pan shall be of glass-reinforced plastic laminate (see 3.4).
(d) When a shut-off globe valve is required (see 3.7).
(e) When a nipple shall be substituted for the drain hose coupling (see 3.8).
(f) When a hose clamp shall be substituted for the drain hose coupling (see 3.11).
(g) Color required (see 3.17).
(h) When welding process shall be specified (see 3.18.2).
(i) Time frame required for submission of preproduction pack (see 5.1).
(j) Degree of preservation and degree of packing required (see 5.2 and 5.3).
(k) When Finish A strapping is required (see 5.3.1).

6.3 First-produced washer. Any changes or deviations of production washers from the approved first-produced washers during production will be subject to the approval of the contracting officer. Approval of the first-produced washer will not relieve the contractor of his obligation to furnish washers conforming to this specification.

6.4 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the washers in accordance with this specification.

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:54Z
Check the source to verify that this is the currentversion before use.

6.5 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's maintenance and operational manual to be furnished with each washer.

6.6 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions regarding shipment of washers.

6.7 Lubricants. The contracting officer should furnish a list of military lubricants applicable to the washer covered by this specification as contained in the Federal Supply Catalog, Department of Defense Section, Identification List C9100-IL, for FSC Group 91.

6.8 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification.

Custodians:
Army - ME
Air Force - 99

Review activities:
Army - EL
DLA - GS

Preparing activity:
Army - ME

Project 6740-0198

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-P-14145C Print Washer, Photographic: Rotary Pan Type, (EK-4)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:54Z
Check the source to verify that this is the current version before use.