MIL-P-14207 (Ord)
9 December 1955
SUPERSEDING
WTVPD 1490
7 March 1955

MILITARY SPECIFICATION
PACKAGING OF PARTS, SPARE PARTS, TOOLS AND EQUIPMENT FOR GAGE KITS, PULLOVER

1. SCOPE

1.1 This specification covers the packaging and packing of parts, spare parts, tools and equipment for Gage Kits, Pullover for each level of protection.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications of the issue in effect on the date of invitation for bids, form a part of this specification.

SPECIFICATIONS

Federal:

NN-B-591 - Boxes, Fiberboard, Wood-Cleated (for Domestic Shipment)
NN-B-621 - Boxes, Wood, Nailed and Lock-Corner
NN-B-631 - Boxes; Wood, Wirebound (for Domestic Shipment)
PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-676 - Boxes, Set-Up, Paperboard
PPP-T-0076 - Tape, Paper, Water Resistant Pressure-Sensitive

Military:

JAN-P-100 - Packaging and Packing for Overseas Shipment General Specification
JAN-P-106 - Boxes; Wood, Nailed (Overseas Type)
MIL-B-107 - Boxes; Wood, Wirebound (Military Type)
JAN-P-108 - Boxes; Fiberboard, Corrugated and Solid (Military Type)
MIL-P-116 - Preservation, Methods of
JAN-P-120 - Packaging and Packing for Overseas Shipment Cartons, Folding, Paperboard
MIL-B-121 - Barrier-Material, Greaseproofed, Flexible (Waterproofed)
MIL-B-130 - Barrier-Material, Paper, Noncorrosive
JAN-P-138 - Packaging and Packing for Overseas Shipment Boxes, Wood, Fiberboard-Lined
MIL-L-644 - Lubricating-Oil, Preservative, Special
MIL-P-3420 - Packaging Materials, Volatile Corrosion Inhibitor Treated

FED. SUP. CLASS
5220

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

MIL-P-8574 - Preservation and Packaging Procedures Utilizing Volatile Corrosion Inhibitor Treated Materials
MIL-L-10547 - Liners, Case, Waterproof
MIL-C-12147 - Containers: Shipping, Fiber Tube, Spirally Wound Single Body Type
MIL-C-12804 - Containers: Shipping, Fiber Tube, Spirally Wound, Telescopic Type

STANDARDS
Military:
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

DRAWINGS
Ordnance Corps:
(See Table IV)

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Consolidated Freight Classification Ratings, Rules and Regulations.

(Application for copies should be addressed to the Consolidated Freight Classification Committee, 202 Union Station, Chicago 6, Illinois.)

National Motor Freight Classification No. A-2 and No. 12.

(Application for copies should be addressed to the American Trucking Association, 1424 Sixteenth Street, N.W., Washinton 6, D.C.)

Postal Laws and Regulations

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington 25, D. C.)

3. REQUIREMENTS

3.1 Materials and methods.- The materials, methods, and procedures used in the packaging of items shall be in accordance with this specification. Materials and methods not specified shall be suited to the intended use and subject to the approval of the procuring agency having technical responsibility for the packaged item. Unless otherwise specified, the contractor shall provide the Government inspector certification of adherence to the requirements of material specifications. Throughout the packaging processing, all materials and methods shall be maintained at the quality level requirements of the pertinent material and method documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

3.2 Cleaning.- Parts shall be cleaned just prior to preservation. Where this is impractical, parts shall be cleaned at the most suitable point, and shall be protected from contamination or corrosion in the interval between cleaning and preservation. Special preservative oil conforming to Specification MIL-L-644 shall be applied to such parts. Tests in conformance with Specification MIL-P-116 shall be made intermittently for cleanliness of parts.

3.2.1 Protective finishes.- Additional cleaning is not necessary for parts which go directly from protective finish treatment (phosphate or black oxide coatings, finished with oil; anodized finish; electroplated finish; painted finish) to final preservative without intervening handling such as inspection or assembly.

3.2.2 Cleaning processes.- All items shall be cleaned as specified in Table IV of this specification and in accordance with Specification MIL-P-116. In addition, all items to be preserved with VCI shall be completely neutralized by a petroleum rinse before further processing.

3.3 Drying.- Immediately after cleaning, all items shall be dried in accordance with Specification MIL-P-116.

3.3.1 Drying by wiping.- This procedure of drying shall be used only when other methods are not practicable.

3.4 Preservation.- Immediately after cleaning and drying, all items shall be preserved as required in this specification. The method of preservative application shall be in accordance with Specification MIL-P-116. All items coated with oil shall be thoroughly drained before further processing.

3.4.1 Limitations.- Items which cannot be preserved by immersion shall be preserved by brushing. Preservatives shall not be applied to electrical assemblies or to nonmetallic parts of assemblies such as wood, rubber, leather, fiber, fabric, plastic or glass.

3.4.2 Level A - Military package.- All items shall be preserved as specified in Table IV of this specification and in accordance with Table I of Specification MIL-P-116. VCI shall be applied as specified in 3.5.1.1.1.

3.4.3 Level B - Limited military package.- As specified in 3.4.2.

3.4.4 Level C - Minimum military package.- Preservation shall be accomplished by application of special oil conforming to Specification MIL-L-644.

3.5 Packaging.

3.5.1 Level A - Military package.- All items shall be packaged as specified in Table IV of this specification, and in accordance with Specification MIL-P-116.

3.5.1.1 Unit package.- The number of items per unit package shall be as specified in Table IV.

3.5.1.1.1 Packaging methods.- All items preserved with VCI, as specified in Table IV shall either be wrapped in a layer of VCI material, conforming to type I, grade B or C, Specification MIL-P-3420, when a box or fiber can is required, or inserted into VCI-lined bags when bags are required. VCI lining shall be equal in area to the interior area of the bag. VCI-treated surfaces of wraps shall be adjacent to metal surfaces of the items.

3.5.1.1.1.1 RESTRICTIONS.- The application of VCI-treated materials shall be within the technical limitations of Specification MIL-P-8574. Different chemical VCI formulations shall not be used in the same unit package. VCI-treated material shall be of proven compatability with barrier materials used in the package. Asphalt laminated VCI-treated barrier materials shall not be used unless specifically authorized by the procuring agency having responsibility for the packaged item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

3.5.1.1.2 Unit containers.

3.5.1.1.2.1 When a box is specified in the fabrication of a unit package, wrapped parts shall be inserted into boxes conforming to the following requirements:

(a) Weight of box and contents less than 5 pounds:
Paperboard boxes, type I, style 4 of Specification PPP-B-676
Paperboard cartons, style III or IV, type B, class A of Specification JAN-P-120

(b) Weight of box and contents more than 5 pounds:
Fiberboard boxes conforming to Specification JAN-P-108
Closure shall be made with tape conforming to Specification PPP-T-0076.

3.5.1.1.2.2 When a fiber can is specified in the fabrication of a unit package, wrapped parts shall be inserted into spirally wound, fiber tube containers conforming to the following requirements:

(a) Weight of tube and contents less than 10 pounds:
Single body, fiber tubes conforming to Specification MIL-C-12147
Telescopic fiber tubes, grade II, class 1 or 2 of Specification MIL-C-12804

(b) Weight of tube and contents more than 10 pounds:
Telescopic fiber tubes, grade II, class 3 or 4 of Specification MIL-C-12804

3.5.1.1.3 Cushioning.- When items are preserved with VCI, all parts with projections, sharp edges or corners, exposed threads or critical sufaces shall be cushioned with VCI material, conforming to type I, grade B or C, Specification MIL-P-3420, before unit packaging to prevent damage to the part or the package. When more than one item, except for small items such as bolts, nuts, pin, screws and washers, is specified for a unit package, each item shall be wrapped in VCI material. The VCI-treated surface shall be applied adjacent to the metal surface of the item.

3.5.1.1.3.1 When items are preserved without VCI, then creped, grade A greaseproof barrier-material, conforming to type II or III, class 1, or 2, Specification MIL-B-121, shall be used for cushioning and shall be applied in the same manner specified in 3.5.1.1.3.

3.5.1.1.3.2 When items require no preservative, then noncorrosive barrier-material, conforming to type II or III, Specification MIL-B-130, shall be used for cushioning and shall be applied in the same manner specified in 3.5.1.1.3.

3.5.1.2 Intermediate package.- The intermediate package shall consist of an intermediate container, style CSC or RSC, W-Board, Specification JAN-P-108, and a certain number of like items.

3.5.1.2.1 Contents.- The number of like items (in unit packages) per intermediate package is specified in Table IV of this specification under intermediate package quantity. When zero (0) is specified, no intermediate containers shall be used and the unit packages shall be placed directly into a shipping container.

3.5.1.2.2 Cushioning.- Contents which do not completely fill the intermediate container shall be immobilized, cushioned, blocked or braced to prevent damage to the contents or to the container.

3.5.1.2.3 Closure.- Intermediate containers shall be sealed with 2-inch wide, water resistant, pressure-sensitive tape conforming to PPP-T-0076.

Three strips shall be applied to both top and bottom so that all seams are covered their full length. Tape applied over center lengthwise seams shall extend at least 3 inches onto each of the end panels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

3.5.1.2.4 Odd quantities.- If an odd quantity remains insufficient to fill an intermediate container after the intermediate containers have been filled with the unit packages, the odd quantity of unit packages shall be placed in an identical intermediate container and clearly marked to indicate the quantity (number of items) contained therein.

3.5.2 Level B - Limited military package.- As specified in 3.5.1.

3.5.3 Level C - Minimum military package.- Packaging shall be accomplished by wrapping the items, preserved with oil, in grade A greaseproof barrier-material conforming to type I or II, class 1 or 2, Specification MIL-B-121.

3.6 Packing.- Uniformity in exterior container shapes, sizes, quantity of contents and weights is essential. When more than one exterior container for a particular line item is needed, containers of like dimensions containing like quantities shall be utilized.

3.6.1 Level A - Military pack.

3.6.1.1 Shipping containers.- Items shall be packed in shipping containers conforming to one of the following specifications:

PPP-B-601 - Boxes, Wood, Cleated-Plywood (Overseas type)
JAN-P-106 - Boxes; Wood, Nailed
MIL-B-107 - Boxes; Wood, Wirebound (Overseas type)
JAN-P-138 - Boxes, Wood, Fiberboard-Lined

3.6.1.2 Gross weight of shipping container.- Unless the packaging specification or instruction prescribes a definite quantity per container, or the weight of a single item exceeds the weight limitations, the gross weight shall not exceed:

(a) 70 pounds for containers being shipped into combat areas.
(b) 150 pounds for other shipments.

3.6.1.3 Minimum container size.- The minimum size of the exterior shipping container shall be one cubic foot except when the total shipment displaces less than one cubic foot. In all cases the exterior container shall be of a minimum size required for the shipment.

3.6.1.4 Multiple packs.- When the number of like items does not fill the minimum size exterior containers (3.6.1.3), the items may be multiple packed provided all of the following conditions are met:

(a) Unit packages of like items are packaged together in intermediate packages.
(b) The container does not exceed 100 pounds gross weight or 4 cubic feet displacement.
(c) In any one shipment, like items are not packed in more than one multiple pack.
(d) The individual packages are given sufficient mechanical protection.

3.6.1.5 Case-liner.- Shipping containers shall be lined with a bag-type case-liner conforming to Specification MIL-L-10547 and sealed according to the specification, only when the entrance of free water would destroy the cushioning, blocking or bracing, or the integrity of the intermediate package or of the unit package when no intermediate is used.

3.6.1.5.1 Exceptions.- A case-liner shall not be used under the following conditions:

(a) The cushioning is moisture resistant and protected from free water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

(b) The intermediate package, container or wrap (or unit package, container or wrap when no intermediate is required) is water resistant.

(c) Unit packages accomplished by the use of Kraft-backed barrier-material (other than JAN-P-125) are intermediate packaged.

3.6.1.6 Strapping.- Strapping shall be in accordance with the applicable container specification and shall be applied just prior to shipment when practicable. Straps on export shipping containers shall be stapled when specified in the applicable container specifications.

3.6.1.7 Cushioning.- Contents which do not completely fill the shipping container shall be immobilized, cushioned, blocked or braced to prevent damage to the contents or to the container.

3.6.2 Level B - Limited military pack.

3.6.2.1 Shipping containers.- Items shall be packed in shipping containers conforming to one of the following specifications:

NN-B-591 - Boxes, Fiberboard, Wood-Cleated
NN-B-621 - Boxes, Wood, Nailed and Lock-Corner
NN-B-631 - Boxes; Wood, Wirebound (for Domestic Shipment)
PPP-B-601 - Boxes, Wood, Cleated-Plywood

3.6.2.2 Gross weight of shipping container.- The maximum gross weight of each shipping container shall not exceed 150 pounds, except where the weight of a single item exceeds this weight limitation, where a definite quantity of items is specified per container, or as indicated in 3.6.2.3.

3.6.2.3 Multiple packs.- Items shall be packed as specified in 3.6.1.4, except that there is no general weight restriction for multiple packs. When multiple packs weigh more than 200 pounds or when the size is over 8 cubic feet, the container shall be provided with skids to facilitate handling.

3.6.2.4 Minimum container size.- As specified in 3.6.1.3.

3.6.2.5 Strapping.- As specified in 3.6.1.6.

3.6.2.6 Cushioning.- As specified in 3.6.1.7.

3.6.3 Level C - Minimum military pack.- Items for immediate use shall be packed in commercial containers of the type, size and kind commonly used for this purpose, and in a manner which assures both acceptance by common carrier and safe delivery at destination. Containers shall conform to Consolidated Freight Classification Rules, Postal Regulations, or Motor Freight Regulations, whichever is applicable.

3.7 Marking.

3.7.1 Interior packages.- Marking of unit and intermediate packages by contractors shall be in accordance with Standard MIL-STD-129. The method of preservation shall be specified as part of the basic marking.

3.7.1.1 Special marking.- In addition to the basic marking and any special marking required by the contract or order, interior packages utilizing VCI material shall reflect "VCI", the applicable code of the VCI material used and the specification number of the supplementary oil.

3.7.2 Shipping containers.- Marking of oversea and domestic shipping containers by contractors shall be in accordance with Standard MIL-STD-129. The method of preservation shall be specified as part of the basic marking.

3.7.2.1 Special marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

3.7.2.1.1 VCI identification.- In addition to the basic marking and any special marking required by the contract or order, shipping containers utilizing VCI material shall reflect "VCI", the applicable code for VCI material used and the specification number of the supplementary oil.

3.7.2.1.2 Levels of protection.- Shipping containers packed for Level B or Level C protection shall be conspicuously marked "LTD MIL PK" or "MIN MIL PK", as applicable.

3.7.2.1.3 Oversea supply.- Shipping containers designated for oversea supply shall be implemented by the following requirements:

(a) The service symbol shall be stencilled on the surface immediately adjacent to the oversea address. The symbol shall be of a size commensurate with the size of the letters used in the oversea address and be of the same color.

(b) SNL group of the item (SNL-Applicable letter) shall be stencilled on the sides of the container adjacent to the service color corner marking. The size of the stencil shall be commensurate with the size of the letters in the basic marking on the exterior container.

(c) All oversea exterior container markings and labels shall be protected with a coating of transparent waterproof material as specified in Standard MIL-STD-129.

3.8 Pilot pack.- Pilot packs shall be submitted to the Government inspector to determine conformance with this specification.

3.9 Workmanship.- Visual observation shall be made for the following requirements:

(a) Each coating of preservative, wax, paint, or plastic shall be free from shop contaminants or foreign particles.

(b) Indiscriminate use of preservative, wax, paint, plastic, wrapping and cushioning materials shall be avoided.

(c) Wraps shall be neat, conforming, and firmly secured.

(d) Shipping containers shall be free from damage, protruding nails, and debris. Irrelevant markings shall be neatly obliterated.

(e) Marking shall be uniform and readily legible.

(f) Strapping shall be applied perpendicular to the container sides, and shall not cover any markings.

4. QUALITY ASSURANCE PROVISIONS

4.1 General.- The tests shall be accomplished by the contractor or his agent under supervision of the Government inspector. Inspection and test procedures shall be conducted in process.

4.2 Lot sizes.- The lot size submitted for acceptance purposes shall be determined by the procuring activity or Government inspection agency and shall be as large as is practicable, consistent with available facilities.

4.3 Sampling.

4.3.1 For inspection.- Sampling for inspection shall be conducted in accordance with inspection Level I of Standard MIL-STD-105.

4.3.2 For tests.- Sampling for tests shall be conducted in accordance with Table I, with the exception of the rough handling tests. Sampling for the rough handling tests shall be as specified in 4.5.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

TABLE I - Samples

Lot Size Packages	Sample Size
2 to 100	2
101 to 500	5
501 to 1000	7
1001 and over	10

4.4 Inspection.

4.4.1 Classification of defects.- Visual inspection for defects established in Table II shall apply to each item of the applicable sample of interior packages or exterior containers.

TABLE II - Defects

Defects	AQL (%)
Illegible marking	1.0
Incorrect marking	1.0
Incorrect packaging materials	2.5
Non-adherence to prescribed preservatives	2.5
Improper closure of interior packages	2.5
Inadequate blocking	2.5
Improper packing (insufficient clearance between contents and container; container oversize; inadequate or excessive cushioning material; etc.)	2.5
Non-adherence to the requirements of prescribed shipping container specification	2.5
Workmanship	6.5

4.5 Tests.

4.5.1 Rough handling tests.

4.5.1.1 Shipping containers.- The rough handling test of Specification JAN-P-100 for shipping containers shall not be required for lot sizes under 21. For lot sizes exceeding 21, the minimum sample size shall be one. Each sample shipping container shall be subjected to the rough handling test in accordance with Specification JAN-P-100.

4.5.1.2 Interior packages.- One sample from each lot of packed shipping containers shall be subjected to the rough handling test in accordance with Specification MIL-P-116.

4.5.2 Packaging tests.- Each package in the applicable sample of Table I shall be subjected to the pertinent packaging tests of Specification MIL-P-116 as determined by the methods of preservation shown in Table III.

4.5.2.1 Determination of cleanliness test.- Periodically the Government inspector shall subject the applicable surfaces of one or more units to the determination of cleanliness test in accordance with Specification MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

4.6 Acceptance and rejection.

4.6.1 Shipping container.- Shipping container lots shall have passed the rough handling test when the following conditions exist:

(a) Visual observation indicates that interior contents and packaging components of the sample containers show no damage that would affect their utility.

(b) Sample containers have not been damaged, beyond the point where repair and repacking would represent not more than 25 percent of the original cost of the containers.

4.6.2 Final acceptance.- Lots shall be accepted when the applicable samples have met the requirements of Standard MIL-STD-105 for the inspection of defects established in Table II, the tests specified in 4.5, and the shipping container has passed the tests specified in 4.6.1.

4.6.3 Rejection.- Any defective package or pack found during the sampling inspection or tests shall be cause for corrective action by the contractor, whether or not the lot is accepted.

5. PREPARATION FOR DELIVERY

5.1 There are no applicable requirements.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.

(b) Levels of protection required for packaging and packing.

6.2 The procuring activity should furnish a current list of VCI codes for marking purposes.

6.3 Definitions.

6.3.1 Packaging.- For military purposes packaging is considered to include any necessary cleaning, preservation, determination of unit quantities per package, and protective wrapping, cushioning and identification marking, up to but not including the shipping container.

6.3.2 Packing.- For military purposes, packing is considered to include the selection or construction of the shipping container and assembling of items or packages therein, including any necessary blocking, bracing or cushioning, weatherproofing, exterior strapping, and marking of shipping container for identification of contents.

Patent notice: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian

Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

TABLE III - Tests

TEST	METHOD OF PRESERVATION															
	I	IA-1	IA-2	IA-5	IA-8	IB-1	IC-1	IC-2	IC-3	IC-4	IC-5	IIa	IIb	IIc	IId	IIe	III
Determination of Cleanliness (Required when a cleaning process is used)																	
Preservative compound application (Required when a preservative is used)																	
Heat Seal (Applicable to levels A and B)					X							X					
Quick Leak (Applicable to levels A and B)		X	X	X	X							X	X	X	X	X	
*Waterproofness (Applicable to levels A and B)							X	X	X	X	X						
Cyclic Exposure (Applicable to levels A and B)		X	X	X	X	X						X	X	X	X	X	

* When the size, weight, or other characteristics of Method IC packages precludes the use of the water-proofness test, the water spray test shall be used in lieu thereof.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

TABLE IV - Drawings

STOCK NUMBER	DRAWING NO.	NOMENCLATURE	CLEAN. PROCESS	PRESERVATIVE	UNIT QTY.	PACKAGE METHOD	INTERM. PKG.QTY.
	C7243002	Body & Slide Ass'y (37MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243003	Body & Slide Ass'y (40MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243004	Body & Slide Ass'y (57MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243005	Body & Slide Ass'y (75MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243006	Body & Slide Ass'y (76MM & 3")	C-2	P-9 & VCI	1	IA-8	4
	C7243007	Body & Slide Ass'y (90MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243008	Body & Slide Ass'y (105MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243009	Body & Slide Ass'y (120MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243010	Body & Slide Ass'y (155MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243011	Body & Slide Ass'y (8-In)	C-2	P-9 & VCI	1	IA-8	4
	C7243012	Body & Slide Ass'y (240MM)	C-2	P-9 & VCI	1	IA-8	4
	C7243016	Body & Slide Ass'y (280MM)	C-2	P-9 & VCI	1	IA-8	4
	A7247967	Caliper, Vernier, w/case	C-1	P-9	1	IA-8	0
	D7242996	Case, Accessory	C-1	None	1	III	0
	D7242979	Case, Carrying	C-1	None	1	III	0
	D7242993	Container, Pullover Gage Ass'y Small	C-1	P-9 & VCI	1	IC-1	0
	D7242994	Container, Pullover Gage Ass'y Large	C-1	P-9 & VCI	1	IC-2	0
	C7243150	Gage, Pullover (37MM)	C-2	P-9 & VCI	1	IA-8*	0
	C7243151	Gage, Pullover (40MM)	C-2	P-9 & VCI	1	IA-8*	0
	C7243152	Gage, Pullover (57MM)	C-2	P-9 & VCI	1	IA-8*	0
	C7243153	Gage, Pullover (75MM)	C-2	P-9 & VCI	1	IA-8*	0
	A7244651	Gage, Pullover (76MM & 3")	C-2	P-9 & VCI	1	IA-8*	0
	C7243155	Gage, Pullover (90MM)	C-2	P-9 & VCI	1	IA-8*	0
	C7243156	Gage, Pullover (105MM)	C-2	P-9 & VCI	1	IA-8*	0
	C7243158	Gage, Pullover (120MM)	C-2	P-9 & VCI	1	IA-8*	0
	C7243159	Gage, Pullover (155MM)	C-2	P-9 & VCI	1	IA-8*	0
	C7243160	Gage, Pullover (8-In)	C-2	P-9 & VCI	1	IA-8*	0
	C7243161	Gage, Pullover (240MM)	C-2	P-9 & VCI	1	IA-8*	0
	D7247982	Gage, Pullover (280MM)	C-2	P-9 & VCI	1	IA-8*	0
	A7247968	Glass, Magnifying	None	None	1	IA-8	12
J717-7243172	A7243172	Hinge Assembly	C-2	P-9 & VCI	2	IA-8	12
J717-7243202	A7243202	Hinge Assembly	C-2	P-9 & VCI	2	IA-8	12

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.

TABLE IV - Drawings (Cont.)

STOCK NUMBER	DRAWING NO.	NOMENCLATURE	CLEAN. PROCESS	PRESER VATIVE	UNIT QTY.	PACKAGE METHOD	INTERM. PKG.QTY.
J717-7243162	A7243162	Nut, Adjusting	C-2	P-9 & VCI	1	IA-8	6
14-0-2833-994		Oil, in oil can (4 oz)	None	None	1	III	12
	A7243173	Pin, Clevis (.124 Dia)	C-2	P-9 & VCI	2	IA-8	12
	A7243203	Pin, Clevis (.186 Dia)	C-2	P-9 & VCI	2	IA-8	12
J717-7243180	A7243180	Pin, Push	C-2	P-9 & VCI	2	IA-8	8
J717-7243181	A7243181	Pin, Push	C-2	P-9 & VCI	3	IA-8	12
	A7243176	Protector	C-2	P-9 & VCI	2	IA-8	12
	A7243206	Protector	C-2	P-9 & VCI	2	IA-8	12
	B7248582	Rod Assembly	C-1	P-3	2	IA-1	8
	B7248583	Rod Assembly	C-1	P-3	2	IA-1	8
	A7242966	Rule, Steel, 6-inch	C-2	P-9 & VCI	1	IA-8	12
J717-7243164	A7243164	Screw, Adjusting	C-2	P-9 & VCI	1	IA-8	6
J717-7243184	A7243184	Screw, Adjusting	C-2	P-9 & VCI	1	IA-8	6
J717-7243163	A7243163	Spring	C-2	P-9 & VCI	1	IA-8	12
J717-7243183	A7243183	Spring	C-2	P-9 & VCI	1	IA-8	12
	A7243154	Stop	C-2	P-9 & VCI	1	IA-8	4
	B7243178	Stop	C-2	P-9 & VCI	1	IA-8	4
	B7243179	Stop	C-2	P-9 & VCI	1	IA-8	4
	A7244652	Stop	C-2	P-9 & VCI	1	IA-1	4
	A7244653	Stop	C-2	P-9 & VCI	1	IA-1	4
	A7244654	Stop	C-2	P-9 & VCI	1	IA-8	4
	A7244655	Stop	C-2	P-9 & VCI	1	IA-1	4

NOTE: * Item shall be placed in a paperboard box before insertion into heat-sealed bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:56Z
Check the source to verify that this is the current version before use.