INCH-POUND

MIL-DTL-7034/4A
w/AMENDMENT 1
9 February 2011
SUPERSEDING
MIL-DTL-7034/4A
1 April 2005

DETAIL SPECIFICATION SHEET

PULLEY, CONTROL, ANTI-FRICTION BEARING, AIRCRAFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet, MIL-DTL-7034, and QPL-7034.




FIGURE 1. Configuration and dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:50Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions and interface characteristics.

Dash no. 1/ Nonmetallic sheave	Cable size (ref) (inches)	A Outside dia -0.010	B Groove dia -0.010	C Groove rad	D Bore dia -0.0005	E Width I.R. -0.005	F Shoulder dia (approx)	G Width sheave
-1B	1/16	1.250	0.972	0.055 -0.003	0.1900	0.297	0.297	0.250 -0.012
-2B	3/32	2.500	2.222				0.332	
-3B	1/8	2.000	1.510	0.112 -0.003	0.2500	0.484	0.390	0.422 -0.012
-4B	5/32 3/16	3.500	3.010					
-5B	3/16	5.000	4.374	0.145 -0.005	0.3750	0.620	0.591	0.507 -0.014
-6B	7/32 1/4	6.000	5.374					

TABLE I. Dimensions and interface characteristics - Continued.

Dash no. 1/ Nonmetallic sheave	H Flange width	J ±0.005	Pulley assembly weight max (lbs)	Pulley Strength Allowable limit load on pulley (lbs)	ABMA bearing (ref)
-1B	0.060 ±0.005	0.040	0.026	300	KP3AK
-2B			0.075	500	KP3K
-3B	0.086 ±0.006	0.086	0.090	600	KP4K
-4B			0.200	1,200	
-5B	0.092 ±0.007	0.092	0.500	3,000	KP6
-6B			0.660	4,000	

1/ See note 3 for example of complete part number.

REQUIREMENTS:

1. Material: Material shall be in accordance with MIL-DTL-7034.

2. Finish: Finish shall be in accordance with MIL-DTL-7034.

3. Surface roughness: Surface roughness shall be in accordance with MIL-DTL-7034.

4. Hub may be added to pulley sheave where width of bearing outer race is greater than the maximum width of the pulley sheave.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:50Z
Check the source to verify that this is the current version before use.

NOTES:


(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

1. Dimensions are in inches. Unless otherwise specified, decimal tolerances: +0.000, -0.010. End faces of all bearing hubs shall be flat and square with bore within ±1°.

2. -1B and -3B pulleys should not be installed on aircraft controls that bend the cable more than 15 degrees from a straight line.

3. The part or identifying number (PIN) to be used for pulleys acquired to this specification is created as shown below. In the transition of MS24566 to detail specification sheet MIL-DTL-7034/4, the MS24566 part numbers have been retained as follows:

EXAMPLE: MS 24566 - 2B



MS24566-2B Indicates: Size 2 nonmetallic sheave and fixed ball bearing with contact seal.

All dash numbers in table I are identical to and interchangeable with like dash numbers of MS24566.

4. The replacement sequence for this document is AN210 replaced by MS24566 replaced by MIL-DTL-7034/4.

5. For design feature purposes, this specification sheet takes precedence over the acquisition document referenced herein.

AMENDMENT NOTATIONS: The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:50Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - GS

Preparing Activity:
DLA - GS5

(Project 1640-2011-005)

Review Activity:
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:50Z
Check the source to verify that this is the current version before use.