A-A-1354
January 14, 1980

COMMERCIAL ITEM DESCRIPTION

WRENCH, OPEN END, SINGLE THIN HEAD, 15° HEAD


The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification GGG-W-636.

This commercial item description covers wrenches suitable for thin hexagon and square-headed bolts and nuts, assigned National Stock Numbers (NSN's) as listed below.

Salient characteristics:

Material:	Steel, Rockwell C hardness of 39 minimum, 49 maximum.
Finish:	Enameled and lacquered. Both faces shall have a maximum surface roughness of 125 microinches (A.A.).
Marking:	Marked in a plain and permanent manner with wrench opening size on the faces or on the handle as close to the head as practicable and with manufacturer's name or trademark.
Wrench opening:	Sized to pass the gaging requirements of Federal Standard 346.
Chamfer:	Tips chamfered or rounded to eliminate burrs.

National Stock Number	Wrench opening (distance across flats) (inches)	Width of heads (maximum) (inches)	Thickness of heads (maximum) (inches)	Overall length (minimum) (inches)	Test load (minimum) (in/lb)
5120-00-064-2614	7/16	1-3/16	11/64	3-7/8	320
5120-00-081-9072	1/2	1-3/16	11/64	3-7/8	320
5120-00-081-9073	3/16	1-3/8	3/16	4-7/16	475
5120-00-081-9074	5/8	1-9/16	13/64	5-1/16	650
5120-00-081-9075	11/16	1-9/16	13/64	5-1/16	650
5120-00-529-5117	3/4	1-27/32	15/64	5-7/8	950
5120-00-529-5116	13/16	2-3/32	17/64	6-5/8	1,350
5120-00-293-1325	15/16	2-5/16	19/64	7-1/2	1,800
5120-00-529-5119	1	2-5/16	19/64	7-1/2	1,800
5120-00-293-1797	1-1/4	3	13/32	9-3/4	3,400
5120-00-081-9082	1-5/16	3	13/32	9-3/4	3,780
5120-00-081-9083	1-1/2	3-3/8	15/32	11-1/4	5,800
5120-00-529-5118	1-5/8	3-15/16	17/32	13	9,000



Wrench, open end

Workmanship. Wrench shall be free from rust, burrs, fins, nodules, and other defects which may impair serviceability, durability, or appearance. The edges and corners of the wrench shall be clearly defined and smoothly finished.

The issue of Federal Standard 346 in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:13Z
Check the source to verify that this is the current version before use.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. Each wrench shall be preserved and packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

Federal Standards are available from GSA, Specification Sales, Building 197 (Washington Navy Yard), Washington, DC 20407.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.