A-A-283
October 11, 1979

COMMERCIAL ITEM DESCRIPTION

EXTRACTOR; SCREW AND PIPE: TAPERED, SPIRAL FLUTES OR RIDGES, DRILL STYLE

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification GGG-E-936.

This commercial item description covers commercially available, hand operated screw and pipe extractors for use in removing broken screws, studs, bolts, and pipes.

Salient characteristics:

Material: Steel, Rockwell C 52 - 60.
Conform to table I.
Similar to figure 1.



Figure 1. Screw and pipe extractor, tapered spiral flutes or ridges, drill style.

TABLE I. Dimensions and requirements

Extractor size number	Diameter, small end (inches)	Diameter, large end (inches)	Length of taper (inches)	Overall length (inches)	Torsional moment minimum (inch-lb)	National Stock Number
1	0.054 to 0.070	0.117 to 5/32	1/2 to 7/8	1-13/16 to 2-3/16	23	5120-00-240-5223
2	5/64 to 3/32	.174 to 13/64	11/16 to 1-1/16	2-3/16 to 2-9/16	53	5120-00-580-2359
3	7/64 to 9/64	15/64 to 17/64	13/16 to 1-3/16	2-9/16 to 2-15/16	153	5120-00-240-5221
4	11/64 to 13/64	5/16 to 11/32	15/16 to 1-5/16	2-13/16 to 3-3/16	630	5120-00-240-5222
5	15/64 to 17/64	27/64 to 15/32	1-11/32 to 1-29/32	3-3/16 to 3-9/16	1,050	5120-00-240-5219
6	11/32 to 3/8	19/32 to 5/8	1-1/2 to 2	3-9/16 to 3-15/16	3,010	5120-00-240-5220
7	7/16 to 1/2	3/4 to 7/8	1-15/16 to 2-5/16	3-15/16 to 4-5/16	6,552	5120-00-240-5217
8	23/32 to 3/4	63/64 to 1-3/64	1-15/16 to 2-5/16	4-3/16 to 4-5/8	16,800	5120-00-240-5218
9	31/32 to 1	1-1/4 to 1-5/16	2-1/16 to 2-7/16	4-7/16 to 5-1/32	30,000	5120-00-240-5215
10	1-7/32 to 1-1/4	1-1/2 to 1-9/16	2-5/16 to 2-3/4	4-13/16 to 5-1/4	48,000	5120-00-240-5216
11	1-15/32 to 1-1/2	1-13/16 to 1-7/8	2-13/16 to 3-1/4	5-7/16 to 5-7/8	-	5120-00-223-6954
12	1-27/32 to 1-7/8	2-1/4 to 2-3/8	3-5/16 to 3-11/16	6-1/16 to 6-1/2	-	5120-00-223-6955

Workmanship. The extractors shall not have rust, fins, burrs, or other imperfections which may affect appearance, usability, or durability.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The extractors shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking shall be in accordance with the contract or order.

GSA DC-91002130

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.