A-A-598
December 5, 1979

COMMERCIAL ITEM DESCRIPTION

BATTERY CHARGER, PORTABLE, FOR 6- AND 12-VOLT BATTERIES

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers all-weather, portable battery chargers for garage, fleet, and industrial applications.

Salient characteristics:

Designed for charging both maintenance-free and conventional (including dry charge activation) batteries.
Multiposition tap switch or self-adjusting charging system.
Scaled ammeter and automatic reset circuit breaker.
Full wave rectification with triple insulated transformer.
Copper charging cables, short-proof charging clamps and power cord with three-prong plug.
Thermal overheat and reverse polarity protection.
Boost start capability and on-off switch.
Equipped with handle.
Shipped ready for service.
Markings, including identifying, rating, and cautionary, in accordance with UL requirements.
UL listed (conform to UL Standard 1236); the issue of UL Standard in effect on the date of solicitation shall be used to determine compliance with stated requirements.

Battery charger specifications

Model	DC charging amps on 6-/12-volt batteries: Maximum rating discharged battery	DC charging amps on 6-/12-volt batteries: Continuous	AC input at 110 - 120 volts 60 Hz
A	75	60	11 amps
B	40	30	6 amps

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The battery chargers shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping containers shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

UL Standard 1236 is available from Underwriters's Laboratories (UL), Inc., 1285 Walt Whitman Road, Melville, Long Island, NY 11747.

FSC 6130

GSA DC-01003472

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.