COMMERCIAL ITEM DESCRIPTION

BAG, MOTION SICKNESS

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification PPP-B-23.

This description covers two types of bags: Type I - polyethylene film and type II - bleached kraft paper lined with polyethylene.

Salient characteristics:

The polyethylene used in type I bags shall be opaque, 6-1/8 inches wide, 12 inches long, with a 3 inch gusset ± 1/2 inch, and shall be folded and inserted in a paper or polyethylene envelope printed with a legend, as follows:

MOTION SICKNESS BAG

For use during moments of stomach upset. If an upset stomach is anticipated, remove bag from this container and keep ready for use. Do not be embarrassed by this precaution, as even veteran travelers are subject to occasional motion sickness.

Type II bags shall be of the self-opening type, 4-3/4 inches wide, 11 inches long, with a 3-1/8-inch gusset ± 1/2 inch. The paper bag and polyethylene liner shall be securely anchored at the top with waterproof adhesive.

Type I and II bags shall be provided with a method of closure designated to prevent leakage.

Characteristic	Requirement	Test method
Polyethylene film thickness	0.00125 in	
Kraft paper		
Basis weight	30 lb (24 x 36 - 500) ± 5%	T 410
Bursting strength	17 points, minimum	T 403
Tearing strength	42 g MD, minimum	T 414

The issue of each TAPPI test method in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The bags shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be in accordance with the contract or order.

Note. Purchasers should specify whether type I or type II bags are required.

TAPPI test methods are available from the Technical Association of the Pulp and Paper Industry, One Dunwoody Park, Atlanta, GA 30341.

FSC 8105

GSA FPI 3100050/3

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.