NOT MEASUREMENT SENSITIVE


MIL-I-3575/10F
14 August 1992
SUPERSEDING
MIL-I-3575/10E
14 September 1990

MILITARY SPECIFICATION SHEET

INSIGNIA, AIDE, GENERAL OFFICERS, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-3575.



DASH NO.

-1: Aide, General, Regular
-2: Aide, Lieutenant General, Regular
-3: Aide, Major General, Regular
-4: Aide, Brigadier General, Regular
-5: Aide, General, Subdued
-6: Aide, Lieutenant General, Subdued
-7: Aide, Major General, Subdued
-8: Aide, Brigadier General, Subdued

MATERIAL:

-1, -2, -3, -4: Gilding Metal
-5, -6, -7, -8: Red Brass or Zinc Aluminum

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:16Z
Check the source to verify that this is the current version before use.

FINISH:

-1, -2, -3, -4:

EAGLE (Front and Edges): Gold Plated, Bright Finish with Polished Edges and Highlights

SHIELD: Hard Enameled, Nickel Plated, Mirror-like Polished

-5, -6, -7, -8: Dull Flat Black Enamel

-4: Dull Flat Brown Enamel

DIMENSIONS:

EAGLE AND SHIELD:

HEIGHT (Overall): 1-1/4 inches (3.18 cm) (REF)

THICKNESS (At Thickest Point on Shield): 0.080 inch ± 0.005 inch (0.203 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Pierced areas shall be as indicated.

3. All insignia are identical with the exception of the location and number of stars on the chief of the shield.

4. Enameled colors for Dash No. 1 through 4 shall be as indicated. The colors shall conform to the TIOH chip numbers listed below or the standard sample:

COLOR	CHIP NO.
Red	1
Blue	18

5. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85 and incorporate an ultraviolet inhibitor.

6. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and 7/8 inch ± 1/64 inch (2.22 cm ± 0.04 cm) apart.

7. The enamel for Dash No. 5 through 8 shall match FED-STD-595 Chip No. 37038.

8. Shield for Dash No. 1 through 4 may be rhodium plated, mirror-like polished at the option of the manufacturer.

9. Insignia for Dash No. 1 through 4 may be manufactured using 22 karat gold plate with nickel underplating for commercial sale only.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-06b_)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:16Z
Check the source to verify that this is the current version before use.