MILITARY SPECIFICATION SHEET

Insignia, WARRANT OFFICERS, Army

This specification is mandatory for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-I-3575.

DASH NO.

-1: Regular
(A) -2: Subdued

MATERIAL:

-1: RED BRASS
(A) -2: RED BRASS OR ALUMINUM

DIMENSIONS (INCHES):

HEIGHT (OVERALL): 3/4 (REF)

THICKNESS (AT THICKEST POINT): .090 ± .005

FINISH:

-1: GOLD PLATED SATIN FINISH WITH POLISHED HIGHLIGHTS

(A) -2: DULL FLAT BLACK ENAMEL FINISH OR ANODIZED AND DYED, AS APPLICABLE

NOTES: 1. ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. PRONGS SHALL BE LOCATED AT BOTH INTERSECTIONS OF THE HORIZONTAL CENTER LINE OF THE INSIGNIA AND THE CENTER OF THE WREATH.

(A) 2. THE DASH NO. 1 INSIGNIA IS AUTHORIZED TO BE MANUFACTURED FROM ALUMINUM FOR COMMERCIAL SALE ONLY. THE INSIGNIA SHALL BE ANODIZED AND DYED TO MATCH THE FINISH ON THE STANDARD SAMPLE.

CUSTODIAN:
ARMY - IH
REVIEW ACTIVITY:
OTHER - DP
USER ACTIVITY:
ARMY - SM

Project No. 8455-0129

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY,
UNITED STATES ARMY

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:18Z
Check the source to verify that this is the current version before use.