O-D-235
AMENDMENT-2
April 20, 1976
SUPERSEDING
Interim Amendment-1
April 22, 1966

FEDERAL SPECIFICATION

DEVELOPER, PHOTOGRAPHIC, LOW ACTIVITY

This amendment, which forms a part of Federal Specification O-D-235 dated April 24, 1965, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

1.2 and 1.2.1: Delete in their entirety and substitute the following:

"1.2 Classification. The developer shall be furnished in the following sizes containing sufficient powder to prepare the quantities of working solution listed below (see 6.2):

Size	Working solution
1	1 gallon or 3.8 liters
2	2 gallons or 7.6 liters
3	3.5 gallons or 13.3 liters
4	5 gallons or 18.9 liters"

2.2 Under Federal Standards delete "Fed. Std. No. 102" in its entirety.

PAGE 2

3.3.2: Delete in its entirety and substitute the following:

"3.3.2 Formula. The developer powder shall contain the chemicals specified in table I in applicable proportions to make one gallons, two gallons, three and one-half gallons, or 5 gallons of working solution. The developer shall be a single-powder eparation."

Table I, columns, 1, 2, 3, and 4, lines 6 and 7: Delete "Sodium Hexametaphosphate," "None", "0.5," and "20," respectively.

Table I, column 4, last line: Delete "8" and substitute "15."

PAGE 3

Paragraph 3.6.1.1: Delete in its entirety and substitute the following:

"3.6.1.1 Can opener. When specified in the contract or order, one commerical, metal, puncture-type opener shall be included in each intermediate package (see 6.2)."

FSC 6750

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.

PAGE 4

Paragraph 4.3: Delete in its entirety and substitute the following:

"4.3 Sampling. Unless otherwise specified, sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105. The manufacturer's sampling and inspection procedures may be utilized providing such sampling and inspection methods will assure quality equal to or better than that obtained by the following provisions set forth in MIL-STD-105, and provide the manufacturer's methods have been approved by the procuring activity. For purposes of sampling, an inspection lot shall consist of all material of the same classification designator submitted for inspection and delivery at one time.

4.3.1 Inspection of materials and components. In accordance with 4.3 above, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or if none, in accordance with this specification. In the event of conflict, this specification shall govern."

PAGE 6

Section 5. PREPARATION FOR DELIVERY, delete parenthetical reference to Fed. Std. No. 102 in its entirety.

Paragraph 5.1.1: Delete in its entirety and substitute the following:

"5.1.1 Intermediate package. The developer powder unit package shall be overpackaged in intermediate containers conforming to PPP-B-636, type CF, class domestic, of any style. The intermediate container shall hold no more than 24 one-gallon or 12 two gallon or three and one-half gallon or five gallon sizes of unit packages as applicable.

5.2.1 Level A. Intermediate packages of developer powder shall be packed for shipment according to the requirements of PPP-P-16, type I, class 1, of any style. The intermediate container shall hold no more than 24 one-gallon or 12 two gallon or three and one-half gallon or five gallon sizes of unit packages as applicable."

PAGE 7

Paragraph 6.2: Add the following sub-paragraph:

"(h) Can opener when required (see 3.6.1.1)."

U. S. GOVERNMENT PRINTING OFFICE : 1976 - 210-818/2343

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.