MIL-C-6499E
AMENDMENT 2
1 July 1978
SUPERSEDING
AMENDMENT 1
3 December 1971

MILITARY SPECIFICATION

CLOCK, AIRCRAFT, MECHANICAL, TYPE A-13A

This amendment forms a part of Military Specification MIL-C-6499E, dated 7 July 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 19

4.6.6: Delete and substitute:

"4.6.6 Minus 35°C temperature test. The clock shall be fully wound and then subjected to a temperature of -35°C ±2°C (-31°F ±3.6°F) for a period of 6 hours. The clock shall not gain nor lose more than 75 seconds during this period."

4.6.7: Delete and substitute:

"4.6.7 Plus 55°C temperature test. The clock shall be fully wound and then subjected to a temperature of +55°C ±2°C (131°F ±3.6°F) for a period of 6 hours. The clock shall not gain nor lose more than 15 seconds during this period."

PAGE 24

* After 6.5 add:

"6.6 Reclaimed materiels. The use of reclaimed materiels shall be encouraged to the maximum extent possible."

* Concluding materiel: Delete and substitute:

"Custodians:
Air Force - 99
Army - AR
Navy - AS

Preparing activity:
Air Force - 99

Review activities:
Air Force - 99
Army - AV

User activity:
Navy - CG, MC"

Source: https://assist.dla.mil -- Downloaded: 202640-17T07:07Z
Check the source to verify that this is the currentversion before use.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Air Force - 99
Army - AR
Navy - AS

Review activities:
Air Force - 99
Army - AV

User activity:
Navy - CG, MC

Preparing activity:
Air Force - 99

(Project 6645-0332)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:07Z
Check the source to verify that this is the current version before use.