MIL-I-6533B
AMENDMENT 3
2 MARCH 83
SUPERSEDING
AMENDMENT 2
6 April 1976

MILITARY SPECIFICATION

INDICATOR, TEMPERATURE, ELECTRICAL RESISTANCE
MULTI-FUNCTION, TYPE G-10

This amendment forms a part of Military Specification MIL-I-6533B, 25 May 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

*Add the following beneficial comments statement to the bottom of page 1:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: the Engineering Division, SA-ALC, Kelly Air Force Base, TX 78241 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

PAGE 2

*Delete:

"3.1.1 Qualification. Indicators furnished under this specification shall be products which are qualified for listing on the applicable Qualified Products-List at the time set for opening of bids (see 4.1.1 and 6.3.1)."

PAGE 6

*Paragraph 4.1.1 delete and substitute:

"4.1.1 General specification. Qualification and Quality Conformance tests of MIL-I-7070 apply as First Article and acceptance tests of this specification, respectively."

*Add:

"4.1.3 First article samples. Unless otherwise specified, as soon as practicable, after the award of the contract or order, the contractor shall submit three indicators to the test as specified herein and detailed in MIL-I-7070."

PAGE 7

*TABLE I: Delete and replace with new TABLE I.

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:11Z
Check the source to verify that this is the current version before use.

TABLE I. Tolerances

Test Point	Test Resistance	Scale Error at Room Temperature	Reduced Voltage	Scale Error at Low Temperature	Scale Error at High Temperature	Scale Error at Room Temperature after Vibration
°C	Ohms	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C
-70	68.27	2.4 (2.4)	2.5 (2.5)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)
-50	74.24	2.4 (2.4)	0.5 (0.5)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)
-30	80.56	2.4 (2.4)	0.5 (0.5)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)
-10	87.04	2.4 (2.4)	0.5 (0.5)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)
0	90.38	2.4 (2.4)	0.5 (0.5)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)
+10	93.80	2.4 (2.4)	1.0 (1.0)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)
+30	100 91	2.4 (2.4)	1.0 (1.0)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)
+50	108.39	2.4 (2.4)	2.5 (2.5)	3.6 (3.6)	3.6 (3.6)	2.9 (2.9)

Test Point	Test Resistance	Scale Error at Room Temperature after Open and Short Circuit	Extreme Temperature Exposure			
			Scale Error at Low Temperature	Scale Error at Room Temperature after Low Temperature	Scale Error at Room Temperature after High Temperature	Scale Error With Bulb Lead Resistance
°C	Ohms	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C
-70	68.27	3.9 (3.9)	5.0 (5.0)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)
-50	74.24	3.9 (3.9)	4.5 (4.5)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)
-30	80.56	3.9 (3.9)	3.9 (3.9)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)
-10	87.04	3.9 (3.9)	3.9 (3.9)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)
0	90.38	3.9 (3.9)	3.9 (3.9)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)
+10	93.80	3.9 (3.9)	3.9 (3.9)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)
+30	100.91	3.9 (3.9)	5.0 (5.0)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)
+50	108.39	3.9 (3.9)	5.5 (5.5)	3.6 (3.6)	3.6 (3.6)	1.5 (1.5)

Source: https://assist.dla.mil - Downloaded: 2026-02-17T07:11Z
Check the source to verify that this is the current version before use.

*Delete:

"6.3.1 With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the San Antonio Air Logistics Center, Engineering Division, ATTN: MME, Kelly AFB, Texas 78241, and information pertaining to qualification of products may be obtained from that activity."

*The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

*Custodians:
Army - AV
Navy - AS
Air Force - 99

Preparing activity:
Air Force - 82

(Project 6685-0687)

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 20261O-17T07:11Z
Check the source to verify that this is the current version before use.

tubing. Tubing shall be corrosion-resistant steel, or a maximum 3.4.2.8