MIL-T-6480A
11 JUNE 1953

Superseding
MIL-T-6480(USAF)
19 March 1951

MILITARY SPECIFICATION

TIE DOWN, CARGO, AIRCRAFT, TYPE C-2

This specification has been approved by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers one type of aircraft cargo tie down, designated Type C-2.

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specifications, standard, and drawing, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-P-416	Plating, Cadmium (Electrodeposited)
QQ-Z-325	Zinc Plating (Electrodeposited)

Military

MIL-A-140	Adhesive, Water-Resistant, Waterproof Barrier-Material
MIL-C-6458	Chain Assembly, 10,000 Lb. Capacity, Type C-2 Cargo Tiedown
MIL-G-3278	Grease; Aircraft and Instruments (For Low and High Temperatures)
MIL-M-7911	Marking, Identification of Aeronautical Equipment, Assemblies, and Parts
JAN-P-105	Packaging and Packing for Overseas Shipment - Boxes, Wood, Cleated, Plywood
JAN-P-106	Packaging and Packing for Overseas Shipment - Boxes; Wood, Nailed
JAN-P-108	Packaging and Packing for Overseas Shipment - Boxes, Fiberboard, (V-Board and W-Board), Exterior and Interior
JAN-P-125	Packaging and Packing for Overseas Shipment - Barrier-Materials, Waterproof, Flexible

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:05Z
Check the source to verify that this is the current version before use.

STANDARDS

MIL-STD-129 Marking of Shipments

DRAWINGS

U. S. Air Force Drawing

50D7571 Tie down Assembly - Cargo, Aircraft, 10,000 Lb Capacity, Type C-2

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The requirements specified on Drawing 50D7571 and the details thereof are applicable as requirements of this specification. Additional requirements shall be as specified herein.

3.1.1 In the event the requirements of Drawing 50D7571, the details thereof, and this specification conflict, the requirements of this specification shall govern.

3.1.2 The tie-down chain assembly, in accordance with Specification MIL-C-6458, shall not be tested to a tensile load in excess of 12,000 pounds.

3.2 Finish.- The tie down shall be cadmium plated in accordance with Specification QQ-P-416, type I, class C or zinc plated in accordance with Specification QQ-Z-325.

3.3 Lubrication.- Grease required for any moving parts shall be in accordance with Specification MIL-G-3278.

3.4 Identification of product.- The tie down shall be durably and legibly marked with the information listed below. The information marked in the spaces provided on the nameplate shall be in accordance with Specification MIL-M-7911.

TIE DOWN, CARGO, AIRCRAFT
TYPE C-2
Specification MIL-T-6480A
Stock No. (USAF or Navy, as applicable)
Part No. 50D7571
Manufacturer's Part No.
Manufacturer's Serial No.
Contract or Order No.
Manufacturer's name or trade-mark
US Property

For Navy contracts, the marking shall include the full contract number, for example, NOa(S)12345.

3.5 Workmanship.- Workmanship shall be of high quality consistent with construction of this type. All metal parts shall be clean and free from burrs and sharp edges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:05Z
Check the source to verify that this is the current version before use.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 General.- All the tests required for the testing of tie downs are classified as inspection tests, for which necessary sampling techniques and methods of testing are specified in this section.

4.2 Test conditions.- To conduct the tensile testing of the tie down device as required by paragraph 4.3.2.3, a test fixture shall be fabricated to replace the chain assembly. This fixture shall have one end which will have the outside dimensions of the chain link and fit the pocket of the tie-down device.

4.3 Individual tests.- Each tie down shall be subjected to the following test. In addition, each tie down shall be subjected to any other test specified herein which the Inspector considers necessary to determine compliance with the requirements of this specification.

4.3.1 Examination of product.- Each tie down shall be inspected to determine compliance with the requirements specified herein with respect to materials, workmanship, and marking.

4.3.2 Sampling tests.- Not less than two tie downs shall be selected at random from each lot of 500 tie downs, or less, manufactured under essentially the same conditions and submitted for inspection at substantially the same time and subjected to the Sampling tests. These tests shall be in addition to the Individual tests specified herein.

4.3.2.1 Tests shall be conducted to demonstrate that a 3,000-pound tensile load may be released by application of a maximum torque of 80 inch-pounds to the release mechanism for 25 cycles without perceivable wear of working parts.

4.3.2.2 The tightening mechanism shall be tested for 25 cycles to demonstrate that a pretension of 400 pounds can be obtained manually without causing visual wear of parts.

4.3.2.3 Twenty-five cycles of tensile loading from zero to 8,460 pounds shall be applied to the tie down to test the gripping mechanism. At the completion of the above number of cycles, each inspection sample shall be subjected to a load of 14,100 pounds for 30 seconds. Upon removal of the load, the release and tensioning mechanisms shall operate freely.

4.3.2.4 Rejection and retest.- When tests are specified on a quantity of tie downs that are selected as representative of a certain lot, and one or more of this number fails to meet the specified tests, additional tie downs of the lot represented shall be tested immediately to determine the extent of failure. Individual performance tests shall not be interrupted, unless the defect is of such a nature that it will seriously affect the performance or safe use of the tie down.

4.4 All parts, specimens, or assemblies destroyed in making tests required by this specification or drawings, to determine compliance with the specification or drawings, shall be in addition to the quantity specified in the contract or purchase order and shall be furnished without increasing the cost of the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:05Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Application.- The requirements specified herein apply only to direct purchases by or direct shipments to the Government.

5.2 Packaging.- Unless otherwise specified, interior packaging shall consist of one tie-down device sealed within a corrugated or solid fiberboard box conforming to Specification JAN-P-108. As an alternative to Specification JAN-P-108, commercial fiberboard boxes of comparable dry strength may be used, provided the boxes are wrapped with waterproof barrier-material conforming to Specification JAN-P-125, and sealed with adhesive conforming to Specification MIL-A-140.

5.3 Packing.- Unless otherwise specified, all items shall be packed for domestic shipment. Shipping containers, insofar as possible, shall contain an identical number of articles, shall be of uniform size, and shall be designed to enclose the contents in a snug, tight-fitting manner. The gross weight of the exterior shipping container when packed for shipment shall not exceed 200 pounds.

5.3.1 Domestic packing.- Unless otherwise specified, packages shall be packed in substantial commercial shipping containers so constructed as to insure acceptance by common or other carrier for safe transportation, at the lowest rate, to the point of delivery. Except as specified herein, the container shall conform to the requirements of Consolidated Freight Classification Rules in effect at the time of shipment. Containers shall be able to withstand storage, rehandling, and reshipment without the necessity of repacking.

5.3.2 Overseas packing.- Unless otherwise specified, for overseas shipment, the packages shall be packed in shipping containers in accordance with Specification JAN-P-105 or JAN-P-106. Plywood, when used, shall be type B, condition I.

5.4 Marking of shipments.- Interior packages and exterior shipping containers shall be marked in accordance with Standard MIL-STD-129. The nomenclature shall be as follows: Tie down, Cargo, Aircraft, 10,000 Lb Capacity, Type C-2, Part No. 50D7571, Specification MIL-T-6480A, Federal Stock No. * (if no FS No. available, leave space therefor).

* Applicable data to be entered by the manufacturer.

5.4.1 In addition, the following marking shall be added for shipments to the Air Force only:

IF IN STORAGE AFTER (DATE)**, THE TIE DOWN SHALL BE TESTED AND INSPECTED BEFORE ISSUE.

** This date shall be 3 years from the date of inspection and shall be inserted by the Inspector at the time of acceptance.

6. NOTES

6.1 Intended use.- The type C-2 tie down covered by this specification is intended to provide a flexible high-strength tie-down means to secure cargo and heavy equipment in aircraft for air transportation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:05Z
Check the source to verify that this is the current version before use.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army - Transportation Corps
Navy - Bureau of Aeronautics
Air Force

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

ORGANIZATION (Of submitter) | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity) | DATE

DD, FORM 1426, APR 63 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:05Z
Check the source to verify that this is the current version before use.