MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6336B

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Twin triode, low-Mu, series regulator

Outline	---	See figure 1
Base	---	B8-98 (glass-bonded mica)
Envelope	---	T16
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7	8
Element	---	2g	2a	2k	1g	1a	1k	h	h

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec	Ib/a	Ehk	Rk/k	Rg/g	Pp/a	TE	tk	Alt
Unit:	V	Vdc	Vdc	mAdc	v	Ohms	Ohms	W	°C	---	ft
Maximum:	6.9	400	---	400	+300	---	500,000	30	250	---	Note 1
Minimum:	5.7	---	-300	---	-300	Note 2	500 (Note 3)	---	---	Note 4	---
TEST CONDITIONS:	6.3	190	0	---	---	200	500 (min)	---	---	---	---

GENERAL:

Qualification - Required

Ⓕ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:48Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS			UNIT
						MIN	BOGEY	MAX	
	Qualification inspection								
Ⓕ 1216	Base material insulating quality	Glass-bonded mica, zone 5 minimum	---	---	---	---	---	---	---
	Quality conformance inspection, part 1								
1231	Emission	Eb = Ec = 10 Vdc; Rk = 0 (see note 5)	0.65	II	Is	150	---	---	mAdc
1256	Electrode current (1) (anode)	See note 6	0.65	II	Ib	165	185	200	mAdc
1256	Electrode current (3) (anode)	Eb = 200 Vdc; Ec = -100 Vdc; Rk = 0 (see note 6)	0.65	II	Ib	---	---	10	mAdc
1266	Total grid current	Rg = 0.05 Meg (see note 7)	0.65	II	Ic	0	---	-4	μAdc
1336	Heater-cathode leakage	Ehk = +300 Vdc Ehk = -300 Vdc (see note 8)	0.65	II	Ihk	---	---	40	μAdc
1201	Short and discontinuity detection		0.65	II	---	---	---	---	---
	Quality conformance inspection, part 2								
1301	Heater current		---	---	If	4.75	5.00	5.25	A
1316	Amplification factor	See note 6	---	---	Mu	2.0	2.7	3.4	---
1306	Transconductance (1)	See note 6	---	---	Sm	11,000	13,500	16,000	μmhos
1306	Transconductance (2)	Ef = 5.7 V (see note 6)	---	---	ΔSm Ef	---	---	15	%
1261	Electrode voltage (anode)	Rk = 0; Ec = 0; Eb/Ib = 400 mAdc	---	---	Eb	---	---	95	Vdc
1256	Electrode current (2) (anode)	Eb = 40 Vdc; Ec = 0; Rk = 0 (see note 6)	---	---	Ib	150	---	---	mAdc
1211	Insulation of electrodes		4.0	S3	---	---	---	---	---
---	Tap shorts	Ebb = 400 Vdc; Ec = -300 Vdc (see note 9)	---	---	---	---	---	---	---
1031	Variable-frequency vibration	Rp = 2,000 ohms; Ec/Ib = 75 mAdc (see note 10)	---	---	Ep	---	---	300	mVac
1031	Vibration fatigue	50 to 500 to 50 Hz; 2.5 G; time of sweep 50 to 500 to 50 Hz = 3 minutes (min) to 15 minutes (max)	6.5	See note 11	---	---	---	---	---

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:48Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS BOGEY	LIMITS MAX	UNIT
	Quality conformance inspection, part 2 -Continued								
---	Long duration shock	Shock = 11 ±2 ms; accel = 100 G peak (min); total impacts = 18, Ef = 6.3 Vac (see note 12)	15	S4	---	---	---	---	---
---	Post-shock and vibration-fatigue test end points	Electrode current (1) (anode)	---	---	Ib	150	---	---	mAdc
		Total grid current	---	---	Ic	---	---	-8	µAdc
		Transconductance (1)	---	---	Sm	9,000	---	---	µmhos
		Heater-cathode leakage Ehk = +300 Vdc Ehk = -300 Vdc	---	---	Ihk	---	---	100	µAdc
1101	Secureness of base, base insert, or cap		---	---	---	---	---	---	---
1111	Base pin solder depth		---	---	---	---	---	---	---
1131	Metallic base sleeve quality		---	---	---	---	---	---	---
1105	Permanence of marking		---	---	---	---	---	---	---
	Quality conformance inspection, part 3								
1501	Intermittent life	Group A; Rg = 0.5 Meg; TE = 250° ±25° C; Ehk = 300 Vdc (see notes 13 and 14)	---	---	---	---	---	---	---
---	Intermittent life-test end points (1,000 hours)	Electrode current (1) (anode)	---	---	Ib	150	---	---	mAdc
		Electrode current (grid)	---	---	Ic	---	---	-8	µAdc
		Transconductance	---	---	Sm	9,000	---	---	µmhos
		Heater-cathode leakage Ehk = +300 Vdc Ehk = -300 Vdc	---	---	Ihk	---	---	100	µAdc

NOTES:

1. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage in the basic document.
2. Minimum resistance per cathode leg shall be 27 ohms or that resistance necessary to provide 10 percent of the grid bias voltage, whichever is greater.
3. Maximum grid circuit resistance in regular service or with fixed bias shall be 200,000 ohms. Maximum resistance for cathode bias operation shall be 500,000 ohms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:48Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

4. The cathode-conditioning time is 30 seconds minimum. This is especially necessary in regulator circuits where the anode of the amplifier tube ties back to the anode-side of the passing tube. With no clamping diode between grid and cathode in this type of circuit, the grid may swing highly positive causing the cathode to lose its ability to sustain current.

5. Each unit shall be read separately. Ground unit not under test.

6. Voltages shall be applied to both sections, but each section shall be read separately. Values specified herein are for individual sections, except for heater current. Readings shall be taken after tube has been drawing current at least 5 minutes.

7. With both units operating, Ic is the sum of I1c and I2c.

8. Tie 1k to 2k.

9. Test in circuit of figure 2. Manual tapping, in accordance with method 1201, shall be employed. Any visible flashing of the neon lamps shall be considered indication of a tap short. If a short indication is obtained, the tapping cycle shall be repeated two more times. If a short indication is again obtained, the tube shall be rejected.

10. Tie 1k to 2k, 1g to 2g, and 1a to 2a.

11. This test shall be conducted on the initial lot and thereafter on a lot approximately every 6 months. When one lot has passed, the 6-month rule shall apply. In the event of lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes. MIL-STD-105, sample size code letter E, shall apply.

12. The tubes shall be subjected to the specified acceleration in the X, Y, and Z axes, with six shocks in each axis. Tubes showing any permanent shorts, or more than one temporary short during the test, shall be rejected. Method of short testing is with thyratron controlled, short indicator as described in method 1041. The applied shock shall be an approximate half-sine wave motion with duration measured at the zero axis level.

13. Sections shall be operated in parallel with separate 200-ohm cathode resistors.

14. The heater-to-cathode voltage shall be cycled 30 seconds positive and 30 seconds negative.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy -
Air Force - 99
DSA - ES


User activities:
Army - WC
Navy - AS, OS, MC, CG
Air Force - 11, 19

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-3130)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:48Z
Check the source to verify that this is the current version before use.




Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
Quality conformance inspection, part I		
A	---	4.750 (120.65)
B	---	2.070 (52.58)
C	---	4.175 (106.05)
Reference dimension (see note)		
D	1.750 (44.45)	

NOTE:
Dimensions without tolerances are for information and are not required for inspection purposes.

FIGURE 1. Outline drawing of electron tube type 6336B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:48Z
Check the source to verify that this is the current version before use.



NOTE:
Type NE 34 lamp shall conform to MIL-L-15098.

FIGURE 2. Tap shorts circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:48Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D.C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

OFFICAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202640-15T14:48Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)* .

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:48Z
Check the source to verify that this is the current version before use.