INCH-POUND

MIL-PRF-1/1458E
27 July 2009
SUPERSEDING
MIL-PRF-1/1458D
25 June 1999

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING
TYPE 7788

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and the latest issue of MIL-PRF-1.

DESCRIPTION: Pentode, miniature, RF, sharp cutoff, high transconductance

Outline	---	6-2 (EIA)
Base	---	E9-1
Envelope	---	T6-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	1	2	3	4	5	6	7	8	9
Element	k	g1	k	h	h	g2	a	g3	g2

ABSOLUTE RATINGS:

Parameter: / Unit:	Ef V	Eb V dc	Ec1 V dc	Ec2 V dc	Ec3 V dc	Ehk v	egk v	Rg1 MegΩ
Maximum:	6.6	250	-25	165	0	100	± 50	1/
Minimum:	6.0	---	---	---	---	---	---	---
Test conditions:	6.3	135	+12.5	165	0	0	---	---

ABSOLUTE RATINGS:

Parameter: / Unit:	Ik mA dc	Pg1 W	Pp W	Pg2 W	TE °C	Rk Ohms	Alt ft
Maximum:	50	0.01	5.0	1.0	+170	---	2/
Minimum:	---	---	---	---		---	---
Test conditions:	---	---	---	---	---	360	---

See footnotes at end of table I.

GENERAL: Qualification – Not required

AMSC N/A

FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:45Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

Inspection	Method MIL-STD-1311	Conditions	Acceptance Level 9/	Symbol	Limits		Unit
					Min	Max	
First Article Inspection							
Sweep-frequency vibration	1031	Ebb = 155 V dc; Ec2 = 160 V dc; Rp = 680 ohms; Ec1 = +7 V dc; Rk = 220 ohms unbypassed	---	Ep	---	500	mV dc
Conformance inspection, part 1							
Heater current	1301		0.65	If	320	360	mA
Heater-cathode leakage	1336		0.65	Ihk	---	13	μA dc
Total grid current	1266	3/	0.65	Ic1	0	-0.1	μA dc
Electrode current (1) (anode)	1256	Ebb = 120 V dc; Ecc1 = 0; Ecc2 = 150 V dc; Ecc3 = 0; Rk = 47 ohms	0.65	Ib	29.0	41.0	mA dc
Electrode current (2) (anode)	1256	Ebb = 120 V dc; Ec1 = -6.0 V dc; Ecc3 = 0; Rk = 47 ohms; Ecc2 = 150 V dc	0.65	Ib	---	150	μA dc
Electrode current (screen grid)	1256		0.65	Ic2	4.2	5.8	mA dc
Transconductance (1)	1306		0.65	Sm	42,000	58,000	μmhos
Short and discontinuity detection	1201	egk = 50 v (max)	0.65	---	---	---	---
Conformance inspection, part 2							
Insulation of electrodes	1211	E (g1-all) = -50 V dc; E (a-all) = -250 V dc	2.5 2.5	---	---	---	---
Transconductance (2)	1306	Ef = 5.7 V	2.5	ΔSm Ef	---	10	%
Electrode current (3) (anode)	1256		2.5	Ib	31	39	mA
Noise and microphonics	2201	Ehk = 0; Ebb = Ecc2 = 200 Vdc; Ec1 = 0; Ecal = 600 mV ac; Rk = 1,000 ohms; Rp = 0.1 MegΩ; Rg2 = 0.5 MegΩ; Cg2 = 2 μF	2.5	---	---	---	---
Direct-interelectrode capacitance	1331	Shield No. 315	6.5	Cg1p Cin Cout	--- 12.5 3.7	0.036 17.0 4.5	pF pF pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:45Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

Inspection	Method MIL-STD-1311	Conditions	Acceptance Level /9	Symbol	Limits		Unit
					Min	Max	
Conformance inspection, part 2 - Continued							
High-frequency vibration	1031	Rp = 680 ohms; Eb = 155 V dc; Ec2 = 160 V dc; Ec1 = +7 V dc; Rk = 220 ohms unbypassed	6.5	Ep	---	50	mV ac
Shock	1041	450 G 4/	6.5	---	---	---	---
Vibration-fatigue	1031		6.5	---	---	---	---
Shock and vibration-fatigue test end points:	---		---	---	---	---	---
High-frequency vibration	1031	Rp = 680 ohms; Eb = 155 V dc; Ec2 = 160 V dc; Ec1 = +7 V dc; Rk = 220 ohms unbypassed	---	Ep	---	80	mV ac
Heater-cathode leakage	1336		---	Ihk	---	25	µA dc
Transconductance (1)	1306		---	Sm	40,000	---	µmhos
Total grid current	1266		---	Ic1	---	-0.2	µA dc
Base strain	1121	6/	---	---	---	---	---
Envelope strain	2126		2.5	---	---	---	---
Permanence of marking	1105		---	---	---	---	---
Conformance inspection, part 3							
Heater-cycling life	1506	Ef = 7.5 V; Ehk = 60 V dc; Eb = Ec1 = Ec2 = 0	---	---	---	---	---
Heater-cycling life-test end point::	---		---	---	---	---	---
Heater-cathode leakage	1336		---	Ihk	---	25	µA dc
Stability life	1516	Rk = 360 ohms; Rg1 = 0.47 MegΩ; TA = room	---	---	---	---	---
Stability life-test end point:	---		---	---	---	---	---
Change in transconductance (1) of individual tubes	1306		---	ΔSmt	---	15	%
Intermittent life	1501	Rk = 360 ohms; Rg1 = 0.47 MegΩ 7/ 8/	---	---	---	---	---
Intermittent life-test end points (500 hours)	---	9/	---	---	---	---	---

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:45Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

Inspection	Method MIL-STD-1311	Conditions	Acceptance Level /9	Symbol	Limits		Unit
					Min	Max	
Conformance inspection, part 3 - Continued							
Total grid current	1266		---	Ic1	---	-0.9	μA dc
Change in transconductance (1) of individual tubes	1306		---	ΔSmt	---	20	%
Transconductance (2)	1306	Ef = 5.7 V	---	ΔSmEf	---	15	%
Heater-cathode leakage	1336		---	Ihk	---	25	μA dc
Insulation of electrodes	1211	E (g1-all) = -50 V dc E (a-all) = -250 V dc	---	---	---	---	---
Transconductance (1), average change	1306		---	AvgΔSmt	---	15	%
Intermittent life-test End points (1,000 hours)	---	9/	---	---	---	---	---
Total grid current	1266		---	Ic1	---	-0.9	μA dc
Change in transconductance (1) of individual tubes	1306		---	ΔSmt	***	25	%
Heater-cathode leakage	1336		---	Ihk	---	25	μA dc
Insulation of electrodes	1211	E (g1-all) = -50 V dc E (a-all) = -250 V dc	---	---	---	---	---

1/ Rg1 shall be 0.2 MegΩ for fixed bias, 0.6 MegΩ if Rk = 47 ohms, or 3.5 MegΩ if Rk = 360 ohms.

2/ See “Reduced pressure (altitude) rating”, and altitude, maximum peak voltage in the basic document.

3/ This test shall be performed at the conclusion of the holding period.

4/ A grid resistor of 0.1 MegΩ shall be added, except when a thyratron-type short indicator is used.

5/ This test shall be conducted on the initial lot and thereafter on a lot approximately every 12 months. When one lot has passed, the 12-month rule shall apply. In the event of lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes.

6/ Acceptance sampling procedure shall be in accordance with method 1121, except that acceptance and rejection criteria shall be modified as follows:

a Accepted if not more than one defective for class, A, B, or C defects, respectively, or if not more than a total of two defectives are found in the sample

b. Rejected if two or more defectives for class A, B, or C defects, respectively, or if a total of three or more defectives are found in the sample

7/ Envelope temperature (TE) requirements, when measured in accordance with the temperature by conduction-band measurement (method 1226), will be satisfied if a TUT having bogey Ib (±5 percent) under normal test conditions, is determined to operate at or above minimum specified temperature at any position in the life-test rack.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:45Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

8/ The life-test sample shall consist of 20 tubes per lot and not 1 tube failure shall be permitted. In the event of rejection of the first sample, a second sample of 40 tubes shall be selected from the lot. Acceptance shall then be based on the combined first and second samples and shall not exceed a total of one tube failure.

9/ This specification sheet uses accept on zero defect sampling plan in accordance with MIL-PRF-1, table III.

Referenced documents. In addition to MIL-PRF-1, this document references the following:
MIL-STD-1311

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5960-2009-023)

Review activities:
Army - MI
Navy - AS, CG, MC, OS, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:45Z
Check the source to verify that this is the current version before use.