MILITARY SPECIFICATION SHEET

ELECTRON TUBE, MICROWAVE (NEGATIVE GRID) TYPE 7698

This amendment forms a part of MIL-E-1/1470C(EC), dated 15 April 1976, and is approved for use within the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Preamble, delete in its entirety and substitute:

"This specification is approved for use within the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 4

Note 15, delete in its entirety and substitute:

"15. This test shall be performed during the initial production and once each succeeding 12-calendar month period in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes having an acceptance number of zero, and a second sample of three tubes having a combined acceptance number of one. In the event of failure, the test shall be made as a part of quality conformance inspection, part 2, inspection level S3, with an AQL of 6.5. The regular "12 calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted."

Review activity:
DLA - ES

User activities:
Navy - AS, CG, MC, OS

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5960-N198)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:47Z
Check the source to verify that this is the current version before use.