MIL-C-48103 A(AR)
6 June 1977

Superseding
MIL-C-48103(MU)
13 June 1972

MILITARY SPECIFICATION

CONTAINER, METAL, AMMO, FOR FUZE, TRAINING: M555 WITH TEST PLUG

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and preparation for delivery criteria for one type of container, metal, for fuze, training: M555 with test plug.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS (see 6.4)

MILITARY

MIL-C-10464 - Containers, Metal, Light Gage, Integral Tear Strip Type (For Ammunition Other Than Small Arms)

STANDARDS

MILITARY

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

NUOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1169	- Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
PRODUCT AND PACKAGING DRAWINGS

8861940	- Cap, Protective
8861941	- Cup, Nose
8861942	- Cushion, Bottom
8861944	- Cushion, Top
8861946	- Cushion, Support, Bottom
8861947	- Cushion, Support, Top
8861948	- Pad
8861955	- Can, Hermetically Sealed
8864047	- Container, Metal, Ammo, for Fuze, Training: M555 with Test Plug
10985722	- Cable
10985732	- Receptacle
10985724	- Receptacle Hermetic
EL8864047	- Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The container shall comply with all requirements specified on the drawing (dwg) 8864047, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Mating assembly. Each electrical connector shall be capable of being mated and unmated with its proper receptacle, without the use of tools, when tested as specified in 3.4.1.

3.4 Circuit resistance. The circuit resistance shall comply with table I when tested as specified in 4.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

Table I

Circuit Resistance

From Connector 10985724	To Connector 10985723	Ohms Max.
A	A	0.01
B	B	0.01
C	C	0.01
E	E	0.01

3.5 Insulation resistance. The insulation resistance of any circuit shall not be less than 100 megohms when subjected to a potential of 500 + 50 volts direct current (vdc) with the current limited to 5 milliamperes (ma) when tested as specified in 4.4.3.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, includions, porosity, or any similar characteristics.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.6.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. Not applicable.
4.3 Quality conformance inspection.
4.3.1 Lot formation.
4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristics table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48103 A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.1.1	Cushion, top				8861944
					NEXT HIGHER ASSEMBLY 8864047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Outside diameter, min.		Table II		*Measure
102.	Inside diameter		Table II		*Measure
103.	Thickness, min.		Table II		*Measure
104.	Material		100%	3.1	Visual
Minor:					
201.	Workmanship		Table III	3.6	Visual/Manual

NOTES:
*Measure with suitable scale

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48103 A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8861942
4.3.2.1.2	Cushion, Bottom				NEXT HIGHER ASSEMBLY 8864047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Outside diameter, min.		Table II		*Measure
102.	Thickness, min.		Table II		*Measure
103.	Material		100%	3.1	Visual
Minor:					
201.	Workmanship		Table III	3.6	Visual/Manual

NOTES: *Measure with suitable scale

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.1.3	Cushion, support, top				8861947
					NEXT HIGHER ASSEMBLY 8864047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Outside diameter, min.		Table II		*Measure
102.	Large inside diameter		Table II		*Measure
103.	Small inside diameter		Table II		*Measure
104.	Length of large inside diameter		Table II		*Measure
105.	Total length		Table II		*Measure
106.	Material		100%	3.1	Visual
Minor:					
201.	Workmanship		Table III	3.6	Visual/Manual

NOTES:
*Measure with suitable scale

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.1.4	Cushion, support, bottom		8861946
			NEXT HIGHER ASSEMBLY 8864047

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Outside diameter, min.		Table II		*Measure
102.	Inside diameter		Table II		*Measure
103.	Length, min.		Table II		*Measure
104.	Material		100%	3.1	Visual
Minor:					
201.	Workmanship		Table III	3.6	Visual/Manual

NOTES: *Measure with suitable scale

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.1.5	Cup, nose				8861941
					NEXT HIGHER ASSEMBLY 8864047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Large inside diameter		Table II		*Measure
102.	Small inside diameter		Table II		*Measure
103.	Outside diameter, min.		Table II		*Measure
104.	Length, min.		Table II		*Measure
105.	Length of small inside diameter		Table II		*Measure
106.	Material		100%	3.1	Visual
Minor:					
201.	Radius present		Table III		Visual
202.	Workmanship		Table III	3.6	Visual/Manual

NOTES:
*Measure with suitable scale

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8861948
4.3.2.1.6	Pad				NEXT HIGHER ASSEMBLY 8864047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Material		100%	3.1	Visual
Minor:					
201.	Diameter, min.		Table III		*Measure
202.	Width of slot		Table III		*Measure
203.	Location of slot		Table III		*Measure
204.	Thickness, min		Table III		*Measure
205.	Workmanship		Table III	3.6	Visual/Manual

NOTES: *Measure with suitable scale

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.3.2.1.7	Cap, protective (see dwg 8861940); receptacle, hermetic (see dwg 10985724); receptacle (see dwg 10985723) Cable (see dwg 10985722) covering details of dwg 8864047.	1	1	See Title
				NEXT HIGHER ASSEMBLY: 8864047

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Objective evidence for component in accordance with applicable drawing		100%	6.2	Visual
Minor:					
201.	Workmanship		Table III	3.6	Visual/Manual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8861955
4.3.2.1.8	Can, hermetically sealed				NEXT HIGHER ASSEMBLY 8864047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Can in accordance with MIL-C-10464 with limitations specified on dwg 8861955		100%		Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.1.9	Container, Metal, ammo for fuze, training: M55 with test plug (see dwg 8864047) without fuze.				8864047
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	All components present and properly packed		100%		Visual/Manual
102.	Contents tight in container		Table II		Manual
Minor:					
201.	Marking		Table II		Visual
202.	Workmanship		Table III	3.6	Visual/Manual

NOTES:

14

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.1.10	Preparation for delivery				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169		100%	5 & 6.2	Visual
Minor:	None defined.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

4.3.3 Testing. All tests shall be performed. Tests need not be performed in the order specified.

	Test	Test Classification
a	Mating	Major
b	Circuit resistance	Major
c	Insulation resistance	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Mating assembly (see 3.3). Each connector shall be tested in accordance with 4.4.1. If any item fails to comply with 3.3, the item shall be rejected and removed from the lot.

4.3.3.2 Circuit resistance (see 3.4). Each container shall be tested in accordance with 4.4.2. If any item fails to comply with 3.4, the item shall be rejected and removed from the lot.

4.3.3.3 Insulation resistance (see 3.5). Each container shall be tested in accordance with 4.4.3. If any item fails to comply with 3.5, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). ELs for assemblies are listed on the Equipment Tabulation, ET-8864047. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

4.4.1 Mating assembly (see 3.3). Each receptacle shall be mated with its associated connector without the use of tools.

4.4.2 Circuit resistance (see 3.4). The circuit resistance shall be measured in accordance with Table I (see 3.4) with approved measuring equipment.

4.4.3 Insulation resistance (see 3.5). The insulation resistance shall be measured with approved insulation resistance measuring equipment in accordance with Table IV.

Table IV

Insulation Resistance

Connector 10985724 Positive Potential to	Connector 10985723 Negative Potential to all other pins except pin
A	A
B	B
C	C
E	E

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The container shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The container shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing.

5.2.1 Levels A and C. The container shall be packed in accordance with the applicable instructions contained in MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 or specification when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, US Army Armament Research and Development Command, Attn: DRDAR-OAN-I, Dover, New Jersey 07801.

6.4 Drawings and specifications. Drawings and specifications listed in Section 2 of this specification under the heading of US Army Armament Research and Development Command (ARRADCOM) may also include drawings and specifications prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings and specifications. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army - (AR)

Preparing activity:
Army - (AR)

Project No. NUOR-A077

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

Container, Meral, Ammo, for Fuze, Training: M555 With Test Plug MIL-C-48103A

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

FORM 1426
1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAN
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.