MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE, MINE

This specification is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the container used in the packaging of the M74, M75 and M79 mines.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of thes documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes. (ABC-STD-105)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1595 - Qualification of Aircraft, Missle and Aerospace Fusion Welders.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise sepecified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.5)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9313655* - Shipping and Storage Container, Mine.
9342676** - Shipping and Storage Container, Mine.

* For mines stored in plastic sleeves.
** For mines stored in fiberboard sleeves.

(Copies of specifications, standards, drawings and publications listed above or in the item detail specification required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.3 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951 - Commercial Packaging.

(ASTM materials are available from ASTM, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets of MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Material shall be in accordance with the applicable drawings, specifications and standards.

3.2 Container. The container shall comply with all requirements specified on Drawing (Dwg.) 9313655 or 9342676, as applicable, and all associated drawings and with all requirements specified in applicable specifications.

3.3 Welding. Welds shall be reasonably smooth and free from craters. They shall exhibit characteristics of fusion, penetration and soundness of weld deposits representative of good welding practice. All welding fluxes, scale, and excessive weld spatter, acids or basic solutions shall be completely removed prior to application of any finish. All welding shall be in accordance with applicable specifications. All welding shall be performed by operators who are currently certified as Class B Operators in accordance with MIL-STD-1595.

3.4 Performance characteristics. The container, when loaded with inert mines in the appropriate sleeve assemblies, shall comply with all requirements specified on applicable drawings and with all requirements specified in this specification without evidence of bent, loose or broken parts or structural members or cracks which render the container unsafe. Minor dents or creases in non-structural members shall not be considered objectionable. The container shall be serviceable after completion of the tests listed below. All tests shall be conducted at a temperature of 72 $\pm$ 18°F.

3.4.1 Stacking. The loaded container shall be capable of supporting a simulated stacking load equal to nine (9) times the weight of a loaded container without evidence of permanent set or breakage in any of its structural members. The test shall be conducted as specified in 4.5.3.

3.4.2 Edgewise drops. The loaded container shall meet the requirements of 3.4 when allowed to fall freely on its edge onto a hard surface when tested as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

3.4.3 Vibration. The loaded container shall meet the requirements of 3.4 when subjected to vibrations in the vertical axis as specified in 4.5.5.

3.4.4 Free fall drop. The loaded container shall meet the requirements of 3.4 when allowed to drop freely on its base onto a hard surface when tested as specified in 4.5.6.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. All parts and assemblies shall be fabricated, assembled and finished in a thorough workmanlike manner, and all manufacturing, processing, and assembling operations shall be correctly performed. All parts and assemblies shall be clean, free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. Exterior surface coating shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection . Unless otherwise specified herein, or in the contract, the provisons of MIL-A-48078 shall apply and are hereby made a part of this specification. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:46Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Shipping and Storage Container, Mine	9313655/9342676	4
Gasket, Container	9313658/9345263	6

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I as specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63392A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Shipping and Storage Container, Mine				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shipping and Storage Container, Mine (Dwg. 9313655/9342676)				
	Examination for Defects	4		3.2	4.4.2.4
	Stacking Test	4		3.4.1	4.5.3
	Edgewise Drop Test	4		3.4.2	4.5.4
	Vibration Test	4		3.4.3	4.5.5
	Free Fall Drop Test	4		3.4.4	4.5.6
	Air Leakage Test - See Note 1	4		3.2	4.5.2
	Gasket, Container (Dwg. 9313658/9345263)				
	Examination for Defects	6		3.2	4.4.2.3
	Vulcanized Joint Strength Test	6		3.2	4.5.1

NOTES:

1. Air leakage test shall be conducted after all other tests have been performed.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots shall contain:

a. Metal parts assemblies of one lot interfix number from one manufacturer.

b. Container gaskets of one lot interfix number from one manufacturer.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equivalent continuous sampling plans in accordance with MIL-STD-1235A may be utilized. The choice of the plan shall be subject to approval by the procuring activity. In any case, inspection for critical defects, as required, shall be maintained at 100%.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63392A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Base Assembly				9313656/9345261
					NEXT HIGHER ASSEMBLY
					9313655/9342676
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Welds missing or improper		0.40%	3.2,3.3	Visual
102	Locating pin missing		0.40%	3.2	Visual
103	Weld or spatter on mating surface of flange		0.40%	3.2	Visual
104	Hole(s) missing		0.40%	3.2	Visual
105	Any component missing or damaged		0.40%	3.2	Visual
106	Total inside height		0.40%	3.2	Gage
107	Inside height to surface of flange		0.40%	3.2	Gage
108	True position of base stand-off hole (4 holes)		0.40%	3.2	Gage
109	Base assembly does not freely accept right parallelipiped gage (Ref. Note 9)		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63392A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cover Assembly				9313657/9345262
					NEXT HIGHER ASSEMBLY
					9313655/9342676
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weld(s) missing or improper		0.40%	3.2,3.3	Visual
102	Hole(s) missing		0.40%	3.2	Visual
103	Slot(s) missing		0.40%	3.2	Visual
104	Dimple(s) missing		0.40%	3.2	Visual
105	Weld or spatter on mating surface of flange		0.40%	3.2	Visual
106	Inside length		0.40%	3.2	Gage
107	Inside width		0.40%	3.2	Gage
108	Straightness of top plate (no warpage)		0.40%	3.2	Visual
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63392A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Gasket, Container				9313658/9345263
					NEXT HIGHER ASSEMBLY 9313655/9342676
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Developed length (before vulcanizing)		0.40%	3.2	Gage
102	Diameter of rubber		0.40%	3.2	Gage
103	Vulcanized Joint Strength Test		0.40%	3.2	4.5.1
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63392A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Shipping and Storage Container, Mine				9313655/9342676
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any component missing or damaged		0.40%	3.2	Visual
102	Any fastener(s) missing or damaged		0.40%	3.2	Visual
103	Container damaged		0.40%	3.2	Visual
104	Cover and Base assemblies do not line up		0.40%	3.2	Visual
105	Air Leakage Test		100%	3.2	4.5.2
106	Difficulty in assembling Tee Bolts through rectangular slots in cover		0.40%	3.2	Manual
107	Welded joint(s) improper		0.40%	3.2	Visual
Minor					
201	Paint missing or damaged		0.65%	3.2	Visual
202	Marking missing, incorrect or illegible		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this specification is identified, either directly or by reference, in the "Paragraph Reference/Inspection Method" column of the First Article or Quality Conformance Inspection Tables herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Methods of inspection

4.5.1 Gasket vulcanized joint strength. The gasket shall be held in an approved test fixture on either side of the vulcanized joint and the specified pull force shall be applied. Observation shall be made for conformance with the applicable drawing requirements. Any gasket that fails to comply with the specified requirement shall be classed defective. (Non-Destructive test)

4.5.2 Air leakage test. After assembly, with the fasteners and locking devices secured tightly and with the pressure equalizing valve blocked off, the container shall be subjected to the air leakage test specified on Dwg. 9313655 or 9342676, as applicable. The container shall be connected to equipment having gage(s) with the capability and sensitivity for measuring and monitoring the test pressure and any pressure drop during the specified test interval. Observation shall be made for conformance with the applicable requirements. Any container that fails to comply with the specified requirements shall be classed defective. (Non-Destructive test)

4.5.3 Stacking. The required load (2250 pounds, min) shall be placed on top of the loaded container in such a manner as to simulate stacking of nine (9) additional loaded containers thereon. Observation shall be made for compliance with the requirement of 3.4.1. (Non-Destructive Test)

4.5.4 Edgewise drops. The container, loaded with a simulated load of 190 pounds min. evenly distributed within the container, shall be supported at one end of its base on a platform approximately five (5) inches in height. The other end of the container shall be raised and allowed to fall freely from a 24 inch height to a concrete or similar hard surface. The test shall be applied to both ends of the container. Observations shall be made for compliance with the requirement of 3.4.2. (Non-Destructive test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.5.5 Vibration. The loaded container shall be subjected to the vibrations in the vertical axis as specified below. The container shall be assembled to an approved fixture with the cover closed and all latches fastened in a normal manner. Adequate safety precautions shall be observed to preclude endangering personnel and equipment. Observation shall be made for compliance with the requirements of 3.4.3. Any container failing to conform with the applicable requirements shall be classed defective. (Non-Destructive test)

Frequency (Hertz)	Acceleration (G's)
5.5 to 10.0	1.0
10.0 to 50.0	1.5

Sweep rate: 0.8 octaves per minute for total of 60 minutes.

4.5.6 Free fall drop. The container, loaded as in 4.5.4, shall be raised to a height of 12 inches and allowed to fall freely on its base to a concrete or similar hard surface. Observation shall be made for compliance with the requirements of 3.4.4. (Non Destructive test)

5. PACKAGING

5.1 Preservation and packaging. The container shall be preserved and packaged in accordance with the commercial requirements of ASTM-D-3951.

5.2 Packing. Packing shall be in accordance with ASTM-D-3951.

5.3 Marking. Marking shall be in accordance with ASTM-D-3951.

5.4 Shipping. When containers from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The container is intended to be used for the shipping and storage of the M74 AP, the M75 AT and M79 practice mines. These mines are used with the Ground Emplaced Mine Scattering System (GEMSS).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078.) Submit equipment designs as required to Commander, US Army Armament Research, Development and Engineering Center, AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.4 Distribution of ammunition data cards and test data. Distribution of data cards and test data shall include the following: Commander, U.S. Army Armament Research, Development and Engineering Center, AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data orginally prepared by these activities is now under the cognizance of ARDEC.

6.6 Change from previous issue. Due to the extensiveness of the changes, asterisks to identify changes with respect to the previous issue are not used in this revision.

6.7 Subject term (keyword) listing.

Mine
Container
Vibration
Gasket
Vulcanized
Joint

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A340)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.