MIL-S-62293C
28 September 1988
SUPERSEDING
MIL-S-62293B
18 October 1982

MILITARY SPECIFICATION

SCOOTERS, MOTOR: ELECTRIC MOTOR DRIVEN, THREE- AND FOUR-WHEEL, COMMERCIAL

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers electric motor driven, three and four wheel scooters. The scooters are for on-station transport of personnel and cargo under both indoor and outdoor operating conditions. Over-highway operation is not intended. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

1.2 Classification. The scooter shall be of the type and payload and model specified (see 6.2). Unless a specific model is specified (see 6.2), the vehicle may be either a model 3 (3-wheel) or a model 4 (4-wheel), at the manufacturer's option. Combinations specified will be limited to those shown in table I.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC-2340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

TABLE I. Body type, payload capacity and model combinations.

Type	Body type	Payload capacity (pounds)	Rated speed loaded (mph)	
			model 3	model 4
I	Stake and platform	1000	6	18
		1500	6	12
		2000	9	9
		3000	-	9
II	Pickup	1000	6	18
		1500	6	12
		2000	9	9
		3000	-	9
III	Personnel carrier, open	1000	-	10
		1500	-	10
IV	See 6.3	-	-	-
V	See 6.3	-	-	-
VI	Refuse collection	1000	-	9
VII	Burden carrier	4000	-	6
		6000	-	6

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS), and supplement thereto, cited in the soliciation.

SPECIFICATIONS
STANDARDS
FEDERAL
FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:29Z
Check the source to verify that this is the current version before use.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)
Occupational Safety and Health Standards.

(Application for copies of OSHA publications should reference the Code of Federal Regulations 29 CFR, Part 1910, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

(Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-Government document which is current on the date of solicitation.

SAE, INC.
SAE Standards and Recommended Practices

J551	- Performance Levels and Methods of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J695	- Turning Ability and Off Tracking - Motor Vehicles.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Yearbook.

(Application for copies of Tire and Rim Association publications should be addressed to The Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards),

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.5, the vehicle, components, assemblies and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. All items shall be as represented in the manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available in the engineering offices of the procuring activity prior to delivery of the items. The model furnished shall be not older than the manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment and painting shall be in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate military service (see 6.2), the exterior color, identification markings and data plates, shall be in accordance with MIL-STD-1223. When specified (see 6.2), concealed markings shall be furnished.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with the truck requirements of FED-STD-297.

3.1.1.3 Towing devices. When specified (see 6.2), not less than two towing devices, for towing the vehicle, shall be provided on the front of the vehicle.

3.1.1.4 Pintle assembly. When specified (see 6.2), a pintle assembly with associated reinforcements and safety chain attachment devices shall be installed on the rear of the vehicle. The pintle assembly shall be of the fixed type, five-ton capacity, with locking pin and chain, Holland Hitch Model T60AL, or equal. The pintle assembly shall be installed on the chassis or reinforced bumper with reinforcements to transfer pintle loads directly to the chassis. The rearmost part of the pintle shall be not more than four inches forward of the rearmost part of the vehicle. The pintle hook mounted height

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

measured from level ground to the centerline of the pintle hook on an unloaded vehicle shall be from 12 to 18 inches. Two trailer chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment shall provide an ultimate strength not less than the gross vehicle weight of the vehicle furnished. The pintle hook shall be secured with a minimum of four 1/2-inch bolts.

3.1.1.5 Trailer lighting receptacle. When specified (see 6.2), on pintle-equipped vehicles, a trailer lighting receptacle shall be installed at the rear of the vehicle adjacent to the pintle assembly. The lighting receptacle shall conform to SAE J560 with its conductors connected and color-coded as specified therein.

3.2 General design.

3.2.1 Design standards. The scooter shall be in accordance with the electric vehicle requirements set forth in OSHA standards, section 1910.178 for powered industrial trucks, type E designation.

3.2.2 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity. For weight ratings, the operator and the front seat passenger weights shall be computed at 175 pounds each. The payload capacity specified in table I does not include the weight of the operator and the front seat passenger.

* 3.2.3 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.2.4 Dimensions. The vehicle shall conform to the dimensions specified in table II.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:29Z
Check the source to verify that this is the current version before use.

TABLE II. Dimensions.

Feature	Vehicle type I (Stake and platform)		II (Pickup)		III (Open personnel)		VI (Refuse collection)		VII (Burden carrier)	
	Model 3	Model 4	Model 3	Model 4	Model 3	Model 4	Model 3	Model 4	Model 3	Model 4
Wheelbase (in. min.)	57	54	57	54	-	54	-	54	-	55
* Width (in. min.)	42	42	42	42	-	42	-	42	-	41
(in. max.)	49	49	49	49	-	49	-	49	-	49
Overall length (in. min.)	119	106	119	106	-	106	-	110	-	118
Platform area (sq. ft., min.)	19	19	19	19	-	10	-	-	-	21
Cab overall height (in. * max.)	72	72	72	72	-	72	-	72	-	80

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

3.3 Performance. The scooter shall meet the performance requirements specified herein with the tires inflated to the rated tire pressure when operated on smooth, dry, level (except for gradeability requirements), hard surfaced, paved roads, and under standard temperature conditions that will allow for full battery capacity.

3.3.1 Speed. The scooter shall be capable of transporting the operator at the rated speed for the specified scooter type and specified payload capacity (see table I) for a duration of not less than three minutes.

3.3.2 Range. The scooter shall be capable of transporting the operator, a front seat passenger, and the specified payload capacity over the range specified in table III at an average speed of not less than 70 percent of the rated speed (see table I).

3.3.3 Gradeability. The scooter shall be capable of transporting the operator, a front seat passenger, and the specified payload capacity up the grade specified in table III for a duration of not less than three minutes.

TABLE III. Performance (minimum).

Body type	Payload capacity (pounds)	Range (miles)		Gradeability (percent grade)	
		Model 3	Model 4	Model 3	Model 4
I	1000	20	20	7	7
	1500	25	25	7	7
	2000	20	20	5	5
	3000	-	15	-	3
II	1000	20	20	7	7
	1500	25	25	7	7
	2000	20	20	5	5
	3000	-	15	-	3
III	1000	-	20	-	7
	1500	-	20	-	7
VI	1000	-	15	-	4
VII	4000	-	6.5		11
	6000	-	7	-	11

3.3.4 Turning clearance. The scooter shall turn within a vehicle clearance circle of not more than 23 feet for types I to VI, and not more than 25 feet for body type VII, measured in accordance with SAE J695.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

3.3.5 Service brake performance. The service brakes shall stop and hold the scooter with the rated payload on grades of 20 percent. The brakes shall stop the fully loaded scooter within a distance of 30 feet when the vehicle is moving at maximum speed or 20 mph (whichever is lower), on a smooth, dry, level, hard-surfaced road.

3.3.6 Parking brake performance. The parking brakes shall be capable of holding the fully loaded scooter on a 20 percent grade.

3.3.7 Waterproofness. The scooter shall be capable of being driven at speeds up to the maximum speed through standing water on paved surfaces without leakage of water into the enclosed cab (when furnished), and without entry of water into the electrical system, wheel bearings, steering column bearings, or other lubricated areas. The frequency of adjustment required to maintain bearings watertight shall be not greater than the manufacturer's recommended lubrication frequency. The cab instrument panel controls, meters, switches and horn shall be protected against moisture and adverse weather conditions.

3.4 Construction. Type I and type II scooters shall be of the three-wheel type with a single front and two rear wheels, or shall be of the four-wheel type. Type III, VI and VII scooters shall be four-wheel only. Front wheel steering and rear wheel driving shall be provided. The steering column assembly shall be mounted in ball, roller, or needle bearings, and shall be constructed to withstand all radial, thrust, and bending loads imposed. Steering control shall be of the tiller type or of the automotive steering wheel type; except when specified (see 6.2), automotive type steering shall be furnished.

3.4.1 Power train.

3.4.1.1 Motor(s). Direct current (dc), series-wound electric motor(s) shall be furnished, of sufficient power to provide the performance specified in 3.3.1 through 3.3.3 without overheating.

* 3.4.1.2 Transmission. The means of transferring power to the rear wheels shall have sufficient torque capacity for sustained full-load operation. Differential action shall be provided. Gear ratios (single or multiple) shall be properly selected to match maximum gross vehicle weight (GVW), motor torque, vehicle rated speed, and gradeability requirements. The system shall be asbestos free.

3.4.1.3 Speed controller. The speed controller shall be of the step type, silicon controlled rectifier (SCR), transistor, or resistorless type. If an SCR is provided, it shall be heavy duty and designed for continuous use. Resistors shall not be used in series with the motor armature for speed control. The controller shall be operated by an accelerator pedal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

3.4.1.4 Speed selector. A heavy duty speed selector lever shall be furnished, permitting selection of all forward and reverse speeds. When specified (see 6.2), means shall be provided to limit the rate of power application when the directional controller is reversed with the throttle depressed.

3.4.1.4.1 Accelerator pedal. The motor speed shall be controlled by a foot pedal similar to an automotive accelerator. When specified (see 6.2), means shall be provided to limit the rate of power application, after the operating key switch is turned on, to prevent abrupt acceleration when the key is turned on with the accelerator pedal depressed.

3.4.1.5 Operating key switch. An operating key switch, similar to an automotive ignition switch, shall be required to be in the "ON" position before power is supplied to the motor. Accessories may be operated independently of the key switch. A visual warning device shall be activated when the key is placed in the "ON" position to alert the operator that the vehicle is operable.

* 3.4.1.6 Deadman seat switch. A deadman seat switch shall be provided to prevent vehicle operation when the operator is not in a seated position. Provisions shall be made to prevent power cutoff due to momentary lifting of the operator from the seat.

3.4.1.7 Motor overload protection. Means shall be provided to reduce or cut off power to the propulsion motor automatically when the motor is overloaded or drawing excessive current. Continued or repeated attempts to operate the vehicle in an overloaded condition shall result in either partial or complete power shutdown to the motor. All power circuit wires and switches shall be adequately sized for the maximum current flow possible prior to a shutdown.

3.4.1.8 Enclosed components. All switches and controls associated with the motor shall be protected to the extent required to prevent entrance of moisture and foreign matter.

3.4.1.9 Batteries. All batteries, whether for propulsion or accessory operation, shall be of the deep-cycle type. The quantity, voltage, and ampere-hour ratings of the batteries shall be sufficient to provide the performance specified in 3.3.1 through 3.3.3. When specified for type I through VI scooters (see 6.2), 250-ampere hour capacity batteries shall be furnished to provide maximum range and time between charges. Ready access for battery servicing shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

3.4.1.9.1 Battery condition meter. A visual meter shall be furnished to indicate to the operator the state of charge of the propulsion system batteries and to indicate that the batteries are in need of recharge.

3.4.1.9.2 Battery charging system. A battery charging system consisting of a charger and the accessories required to connect the vehicle batteries through the charger to an alternating current (ac) power source shall be provided. The charger shall be of the fully automatic, line compensating type, equipped with a voltage sensing device that shall automatically reduce charging current and shall shut down at the end of the charge cycle. The charging system shall be capable of fully charging vehicle battery sets within 12 hours from a minimal charge state. Chargers for all scooter types shall be furnished as separate units and shall operate from 60 Hertz (Hz) ac power sources. Chargers for type I, II, III and VI vehicles shall operate from 120-volt power sources and shall have an ac cable length of not less than 90 inches. For type VII vehicles, chargers shall operate from 240-volt sources and shall have an ac cable length of not less than 52 inches. When specified (see 6.2), chargers for type I, II, III and VI vehicles shall be built into the scooter and shall have an ac cable length of not less than 80 inches.

* 3.4.1.10 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation within the limits specified by SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.2 Accessory electrical equipment.

* 3.4.2.1 Accessories. Accessory electrical equipment shall be of 12-volt potential. Electrical equipment shall include at least one headlight, taillight, stoplight or combination stoplight and taillight, turn signals, horn, and light switch. Headlights shall be not less than four inches in diameter. All wiring shall be adequately sized and equipped with circuit breakers or other overload protection devices whenever necessary. When separate accessory batteries are used, provision shall be made for simultaneous charging with the propulsion batteries. When specified (see 6.2), two headlights and two taillights shall be furnished.

3.4.2.2 Turn signals. Turn signal lamps conforming to SAE J588 shall be furnished. A turn signal switch conforming to class B of SAE J589 shall be furnished and shall be mounted on the left side of the steering column. Single lens directional signals shall be furnished at the rear.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:29Z
Check the source to verify that this is the currentversion before use.

3.4.2.3 Hour meter. When specified (see 6.2), an hour meter having a totalizing mechanism of not less than 9,999 hours shall be installed.

* 3.4.2.4 Vehicle approach warning device. A pulsating alarm warning device (beeper) shall be provided. The device shall operate only when the vehicle is in motion and shall have an audible range sufficient to alert nearby personnel of approach of the vehicle.

3.4.3 Vehicle frame. The vehicle frame materials and construction arrangement shall be appropriate to the load, size and function of the vehicle. Materials subject to rapid deterioration due to aging or exposure to weather shall not be used without adequate protection.

3.4.4 Suspension. A suspension system shall be furnished which shall include springs or manufacturer's heavy duty shear mounts on the front and springs on the rear. Shock absorber(s) shall be furnished on both front and rear. Suspension components shall have a rated capacity at least equal to the load imposed on each member, measured at the ground, with the scooter loaded to the maximum GVW.

* 3.4.5 Wheels, rims, tires and tubes. The scooter shall be equipped with single wheels. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Tire and rim sizes and load ratings shall be the same for all wheels on the scooter, except for type VII. Multi-piece rims shall not be provided.

* 3.4.5.1 Tires. Tires shall be pneumatic, tube or tubeless type with highway tread, except for type VII, which shall be equipped with solid tires. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground, with the scooter loaded with specified payload, operator and passenger.

* 3.4.5.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of the heavy duty type, and shall be of the proper size for the tires furnished.

* 3.4.6 Service brakes. Service brakes shall be hydraulic or mechanical, and shall meet the brake performance requirements specified in 3.3.5. Brake linings shall be of nonasbestos material.

3.4.6.1 Parking brakes. A hand operated mechanical parking brake conforming to 3.3.6 shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

* 3.4.7 Bumper. The manufacturer's standard full width front bumper shall be provided, except for type VII, which shall be equipped with not less than 3/16 inch thick diamond plate lower front panel.

3.4.8 Rearview mirrors. Adjustable rearview mirrors shall be provided on the right and left sides of the vehicle. The mirrors shall furnish the driver with an adequate view to the rear.

3.4.9 Light bar. When specified (see 6.2), a light bar shall be provided and shall be mounted on the roof of the cab. The light bar shall be fabricated of not less than 16 gage (0.0598 inch) steel and shall measure not less than 32 inches in length and 11 inches in width.

* 3.4.10 Cab. Type I, II, III, VI and, when specified (see 6.2), type VII scooters shall be provided with a detachable, enclosed cab of rigid construction. Side closures on type I, II, III, VI and VII shall be weatherproof cloth doors or, when specified (see 6.2), weatherproof, lockable rigid doors.

3.4.10.1 Windshield. A safety plate windshield shall be provided. The windshield shall be of sufficient size and shall be located to provide good visibility for the operator. A power operated windshield wiper assembly shall be furnished.

3.4.10.2 Cab area seats. The scooter shall be provided with the manufacturer's standard full width front seat or individual front seats to provide comfortable seating for the driver and one passenger for 4-wheeled vehicles. Type VII may have a single front seat for the driver. For 3-wheeled vehicles and for type VII or, when specified for 4-wheeled vehicles (see 6.2), seating for the driver only shall be furnished. When specified for type VII (see 6.2), one additional front seat for a passenger shall be furnished, and need not be covered by the cab. The seat(s) shall be of deep foam construction with padded backrest.

3.5 Bodies.

3.5.1 Type I (stake and platform). The type I scooter shall be provided with a diamond tread steel flatbed platform to the rear of the cab. The dimensions shall be in accordance with table II. The platform shall be provided with stake pockets and a stake type body with front, rear, and full length side racks made of hickory, oak, ash, or southern yellow pine. A rigid headboard may be used in lieu of front racks. The racks shall be removable. The rack height above the platform bed shall be not less than 12 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

3.5.1.1 Package space cover. When specified (see 6.2), a tarpaulin package space cover with tiedowns shall be furnished.

3.5.2 Type II (pickup). Type II scooter shall be provided with a rigid-construction package compartment to the rear of the cab. The floor area of the package compartment shall be not less than 2,100 square inches with one dimension (either length or width) of not less than 50 inches. The height of the package compartment shall be not less than 12 inches. When specified (see 6.2), a box type package compartment cover shall be furnished with a covered area of not less than 1,500 square inches. The cover shall be of rigid construction with a hinged opening equipped with a handle and lock. Inside height under the cover, measured from the floor, shall be not less than 18 inches. When the cover size is shorter than the total floor length, a removable bulkhead shall be provided to close off the lockable compartment.

3.5.3 Type III (open personnel carrier). The type III scooter shall be provided with padded personnel seat(s) with backrest(s) for passengers to the rear of the cab. The personnel seat(s) shall face forward. The personnel seat(s) shall be similar in construction and shall provide passenger comfort equivalent to the driver's seat. Stake pockets and racks shall be provided behind the second passenger seat to accommodate cargo. Racks shall be not less than 12 inches high, measured from the cargo bed.

3.5.4 Type VI (refuse collection). The type VI scooter shall be provided with a hydraulically operated refuse hopper to the rear of the cab. The hopper shall have not less than 1.5 cubic yards capacity. The hopper shall be capable of dumping refuse into a receptacle which has an upper edge not less than 43 inches above the ground. Full hydraulic dumping with hydraulic dump cylinder(s) and a hydraulic control valve shall be provided. Power for hydraulic operations shall be provided by an electrically driven hydraulic pump.

3.5.5 Type VII (burden carrier). The type VII scooter shall be provided with a flatbed platform with dimensions in accordance with table II. The floor area of the deck shall be constructed of not less than 5/8-inch thick plywood or equivalent diamond tread steel.

3.6 Servicing and adjusting. Prior to acceptance of the vehicles by the Government, the contractor shall service and adjust each vehicle for operational use, including at least the following: alinement of light(s); adjustment of the electrical and brake systems; filling and charging of batteries; inflation of all tires; and complete lubrication of chassis with grades of lubricants recommended for the ambient air temperature at the delivery point.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle. The first vehicle of each type and model produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

4.3.1 Road test. The first production vehicle shall be examined and road tested with rated payload by the contractor to assure that the vehicle will operate in accordance with contractual requirements. The gradeability test shall be initiated with the motor at ambient air temperature. Operational tests shall be conducted to determine conformance to 3.3 through 3.3.7.

4.3.2 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PREPARATION FOR DELIVERY

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general nontactical use by the Government in transporting personnel and cargo within the confines of military installations, over improved roads, and under conditions of weather encountered within the continental United States. The vehicles are to be limited to on-station operation and are not intended for over-highway use, or for use in explosive atmospheres.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Body type and payload capacity required (see 1.2).
(c) Model, if a specific model is required (see 1.2).
(d) Identification of appropriate service for painting and marking (see 3.1.1.1).
(e) Concealed markings, if required (see 3.1.1.1).
(f) Rustproofing, if required (see 3.1.1.2).
(g) Towing devices, if required (see 3.1.1.3).
(h) Pintle assembly, if required (see 3.1.1.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

(i) Trailer lighting receptacle, if required (see 3.1.1.5).
(j) Automotive type steering, if required (see 3.4).
(k) Power application limitation during direction reversal, if required (see 3.4.1.4).
(l) Power application limitation during starting, if required (see 3.4.1.4.1).
(m) 250 ampere-hour batteries, if required for type I through type VI vehicles (see 3.4.1.9).
(n) Built-in charger for types I, II, III, and VI, if required (see 3.4.1.9.2).
(o) Two headlights and two taillights, if required (see 3.4.2.1).
(p) Hour meter, if required (see 3.4.2.3).
(q) Light bar, if required (see 3.4.9).
(r) Detachable cab for type VII, if required (see 3.4.10).
(s) Rigid doors on types I, II, III and VI, if required (see 3.4.10).
(t) Seating for driver only, if required (see 3.4.10.2).
(u) Seating for one passenger on type VII, if required (see 3.4.10.2).
(v) Package space cover for type I, if required (see 3.5.1.1).
(w) Package compartment cover for type II, if required (see 3.5.2).

6.3 Change in body types. Type IV (personnel carrier, enclosed) and type V (van, cargo) bodies were deleted due to lack of availability.

* 6.4 Subject term (key word) listing.
Deadman switch
Electric motor drive
Motor overload protection
Scooter, motor
Speed controller
Speed selector.

6.5 Identification of changes. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Navy - YD

Preparing Activity:
Army - AT

Project No. 2340-0032

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE: MIL-S-62203C, SCOOTERS, MOTOR: Electric Motor Driven, Three and Four Wheel, Commercial

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:29Z
Check the source to verify that this is the current version before use.