MILITARY SPECIFICATION

WARHEAD SECTION, 762MM ROCKET,

TRAINING: M42

1. SCOPE

1.1 This specification covers one type of warhead section, designation as Warhead Section, 762MM Rocket, Training: M42.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-P-416	-	Plating, Cadium (Electrodeposited)
QQ-Z-325	-	Zinc Plating (Electrodeposited)

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-C-5541	-	Chemical Treatment of Aluminum and Aluminum Alloys
MIL-I-6866	-	Inspection, Penetrant, Method of
MIL-I-45607	-	Inspection Equipment, Acquisition Maintenance and Disposition of
MIL-T-5021	-	Test, Aircraft Welding Operators, Certification of

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

MIL-W-8604 - Welding of Aluminum Alloys, Process for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

MIL-STD-109 - Quality Assurance Terms and Definitions

MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

US ARMY MUNITIONS COMMAND

8863620 - Warhead Section, 762MM Rocket, Training: M42

8881082 - Shipping and Storage Container, Warhead Section, XM473 & XM473E1 for 762MM Warheads, Packing and Marking

PUBLICATIONS

ARMY

ET-8863620 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

ASTM E 8-69 *Standard Methods of Tension Testing of Metallic Materials*

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts and assemblies shall comply with all requirements specified on Drawing (Dwg) 8863620, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Welding.-The weld of each warhead section shall be such as to produce satisfactory joined parts. All welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of good fusion, penetration and soundness of deposit representative of good welding practice. The process shall be such as to prevent warpage beyond dimensional requirements. The satisfactoriness of the weld shall be based upon compliance with 3.3.1, 3.3.2, 3.3.3, 3.3.4, 3.3.5 and 3.4.2.

3.3.1 Electrodes.-Electrodes shall be of a coated type, except as specified in 3.3.2. The coating shall be uniform and without bare spots, except those used to introduce current to the electrode. All types of electrodes to be used shall be approved by the Government.

3.3.2 Process.-Gas shielded arc-welding or other automatic arc-welding in which bare or lightly coated wire is used with the arc bathed in a reducing gas or other atmosphere excluding media, may be used.

3.3.3 Qualification.

3.3.3.1 Welding operators.-Welding operators shall be qualified in accordance with MIL-T-5021.

3.3.3.2 Welding equipment.-Welding equipment shall be qualified in accordance with MIL-W-8604.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

3.3.3.3 All welding shall be accomplished in conformance with the process used to qualify the first article sample.

3.3.4 Acceptable weld imperfections permitted in warheads section.

3.3.4.1 Sag.-Sag of the material in the area adjacent to the weld shall not be more than .010 inch below the surface of the joined part.

3.3.4.2 Porosity.-Porosity or other discontinuities shall not extend as surface cracks in excess of those defined in 3.3.5 as determined by examination in accordance with 4.4.1, except that microporosity as evidence by partial penetration into skins by penetrant, shall be acceptable.

3.3.4.3 Blow-outs.-Blow-outs may be repaired by hand welding operations, provided they are no greater than one quarter (1/4) inch in width and one (1) inch in length and not more than three (3) such areas may be repaired in any one skin.

3.3.5 Surface cracks.-Surface cracks shall not be in excess of the following:

3.3.5.1 There shall be no more than one (1) surface crack 1/2 inch long in each one (1) inch of weld.

3.3.5.2 There shall be no more than a total of two (2) inches of surface cracks in each weld.

3.4 Mechanical properties.

3.4.1 Component parts.-The aluminum used in the fabrication of the component parts shall comply with the minimum (min) properties specified on the applicable drawing and the heat treat condition required, when tested as specified in 4.2.2.1 or 4.3.3.2, as applicable.

3.4.2 Welds (aluminum).-The mechanical properties of the welds shall not be less than 30,000 pounds per square inch (psi) tensile strength when tested as specified in 4.2.2.2. Unless otherwise directed by the Contracting Officer, this test shall be performed on the first article sample only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

3.5 Workmanship.-All parts and assemblies shall be fabricated, finished, and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Surface coatings shall be continuous except for a few small scratches not exposing base material. All required markings shall be neat and sharply defined.

3.6 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (See 6.4)

3.7 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection

4.2.1 Submission.-The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2. (See 6.1) The first article sample shall consist of one (1) complete M42 Warhead Section, one (1) bag, together with required contents, and three (3) complete sets of parts (i.e. three (3) each of every component and every sub-assembly). All parts and completed assemblies submitted shall have been produced by the contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. A first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply as to significantly affect product

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in this specification and any or all requirements of the applicable drawings. In addition, any or all of the following examinations and tests will be performed.

4.2.2.1 Mechanical properties of component parts (Destructive test).-Sixteen (16) specimens complying with method specified in ASTM E8-69 (part 6), shall be taken from one (1) Warhead Section for tensile and yield strength tests. The 16 specimens shall be taken as follows: Four (4) shall be taken from each skin (Nose skin, forward skin, base skin and Rear skin), of each set of four, two (2) specimens shall be taken parallel to the longitudinal axis and two (2) normal to the axis of the skin. Test shall be in accordance with the offset method of ASTM E8-69, using a 0.20 percent offset.

4.2.2.2 Tensile properties of skin welds (Destructive tests).- Four (4) specimens, complying with the type specified in ASTM E8-69 (part 6) shall be taken as follows: two (2) taken transverse to the welded joint from each skin tested and two (2) specimens shall be taken parallel to the longitudinal axis of the welded joint. Each weld shall be tested for Conformance to the requirements of 3.4.2. using method specified in ASTM E8-69 (part 6).

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

4.3.2.1 Skin, base (See Dwg. 8863646 covering a detail of Dwg. 8863620).-

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor	AQL 1.50 Percent		
201.	Length	Gage	01001
202.	Thickness	Gage	01002
203.	Evidence of poor workmanship (See 3.5)	Visual	01003

4.3.2.2 Skin, forward (See Dwg. 8863652 covering a detail of Dwg. 8863620).-

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor	AQL 1.50 Percent		
201.	Length	Gage	02001
202.	Thickness	Gage	02002
203.	Evidence of poor workmanship (See 3.5)	Visual	02003

4.3.2.3 Skin, rear (See Dwg. 8863653 covering a detail of Dwg. J-8863620).-

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor	AQL 1.50 Percent		
201.	Length	Gage	03001
202.	Thickness	Gage	03002
203.	Evidence of poor workmanship (See 3.5)	Visual	03003

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:44Z
Check the source to verify that this is the current version before use.

4.3.2.4 Base and Ballast Assembly (See Dwg. 8882305 covering a detail of Dwg. J-8863620).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Lifting eye loose	Visual-Manual	04001
Minor	AQL 1.00 Percent		
201.	Screws missing or loose	Visual-Manual	04002
202.	Evidence of poor workmanship (See 3.5)	Visual	04003

4.3.2.5 Base Assembly (See Dwg. 8863654 covering a detail of Dwg. 8863620).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 1.00 Percent		
101.	Location of mounting hole	Gage	05001
102.	Pitch diameter of mounting hole thread	Gage	05002
103.	Minor diameter of mounting hole thread	Gage	05003
104.	Base fitting assembly missing	Visual	05004
105.	Dowel missing	Visual	05005
Minor	AQL 1.00 Percent		
201.	Drain hole missing	Visual	05006
202.	Evidence of poor workmanship (See 3.5)	Visual	05007

4.3.2.6 Fuze Ring Assembly (See Dwg. 8863754 covering a detail of Dwg. 8863620).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

Major	AQL 0.40 Percent		
101.	Part missing or loose	Visual-Manual	06001
102.	Part damaged (cracked, bent, chipped, etc.,)	Visual	06002
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.5)	Visual	06003

4.3.2.7 Skin Assembly (See Dwg. 8863655 covering a detail of Dwg. 8863620).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Gap (max)	Gage	07001
102.	Rivet missing	Visual	07002
Minor	AQL 1.50 Percent		
201.	Length (max).	Gage	07003
202.	Drain hole missing	Visual	07004
203.	Evidence of poor workmanship (See 3.5)	Visual	07005

4.3.2.8 Skin Nose (See Dwg. 8798084 covering a detail of Dwg. 8863699)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor	AQL 1.50 Percent		
201.	Length	Gage	08001
202.	Thickness	Gage	08002
203.	Evidence of poor workmanship (See 3.5)	Visual	08003

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.3.2.9 Ogive, Rocket (See Dwg. 8863699 covering a detail of Dwg. 8863620)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Screw above flush, excessive	Gage	09001
102.	Part missing or loose	Visual-Manual	09002
103.	Part damaged (cracked, bent, chipped etc)	Visual	09003
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.5)	Visual	09004

4.3.2.10 Warhead Section, 762MM Rocket, Training M-42, (See Dwg. 8863620)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Weight	Balance	10001
102.	Part missing or loose	Visual-Manual	10002
103.	Part damaged (cracked, bent chipped, etc)	Visual	10003
Minor	AQL 1.00 Percent		
201.	Marking misleading or unidentiable	Visual	10004
202.	Evidence of poor workmanship (See 3.5)	Visual	10005

4.3.2.11 Shipping and Storage Contr: Warhd. Section: M473 and M473E1 for 762MM, Warheads Pkg and Mkg, prior to Assembly of sides ends and Top (See Dwg. 8881082)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:44Z
Check the source to verify that this is the current version before use.

Major	AQL 0.65 Percent		
101.	Nose strap missing	Visual	11001
102.	Bolt missing	Visual	11002
103.	Fuze and/or container missing	Visual	11003
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.5)	Visual	11004

4.3.2.12 Shipping and Storage Contr. Warhd Sect: M473 and M473E1 for 762MM Warheads Pkg and Mkg (See Dwg. 8881082).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Sides, ends or top improperly assembled	Visual	12001
102.	Quick lock missing	Visual	12002
Minor	AQL 1.5 Percent		
201.	Marking misleading or unidentifiable	Visual	12003
202.	Wood damaged or loose	Visual	12004
203.	Socket head screw key missing	Visual	12005
204.	Evidence of poor workmanship (See 3.5)	Visual	12006

4.3.3 Testing.

4.3.3.1 Penetrant examination of welds (See 3.3.4.2) Major Defects Code No. 13001.-Each weld shall be examined as specified in 4.4.1.

4.3.3.2 Mechanical properties (See 3.4) Major Defect, Code No. 14001.-Samples cut from the nose skin, forward skin, base skin and rear skin shall be tested for conformance to applicable material specification using test methods described in ASTM E8-69. Unless, in the opinion of the procuring activity, further verifications of mechancial properties is necessary, the mechanical properties test shall be made on the First Article sample only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.3.3.3 Longitudinal center of gravity (See Dwg. 8863620) Major Defect, Code No. 15001.-Each warhead section shall be subjected to this test. The test shall be performed as specified in 4.4.2. Any warhead section which fails to comply with the specified requirement shall be classified defective and removed from the lot.

4.3.3.4 Salt spray for corrosive resistance (See applicable drawing) Major defect, Code No. 16001.-Sample coupons or specimens representative of the material and finish of the finished parts shall be prepared in the quantity and manner specified in QQ-Z-325, QQ-P-416 or MIL-C-5541, as applicable. If any part fails to comply with the corrosive resistance requirement, action shall be taken as specified in applicable specification and the batch or lot represented by the failing sample shall be rejected.

4.3.4 Inspection equipment.-Equipment Tabulation (ET) number 8863620 and Equipment Lists (EL's) referenced thereon identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3. Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed.

4.4 Test methods and procedures.

4.4.1 Penetrant examination of skin welds.-The Skin weld shall be examined as specified in MIL-I-6866. This is a nondestructive test. Parts so tested may be returned to the lot.

4.4.2 Longitudinal Center of gravity.-The metal parts assembly shall be mounted in a fixture listed on the Equipment List and tested for conformance to drawing requirements. This is a nondestructive test. Parts so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4.3 Salt spray.-The plated or treated parts shall be tested as specified in QQ-Z-325, QQ-P-416 or MIL-C-5541, as applicable.

4.4.4 Mechanical properties.-The ogive specimens shall be subjected to the mechanical properties testing in accordance with ASTM E8-69 (Part 6). All data shall be recorded.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 Level A.-The metal parts assembly shall be packed in accordance with drawing 8881082.

5.2 Marking.-Marking shall be in accordance with drawing 8881082.

5.3 Shipping.-When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission or first article samples.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. These code numbers shall be listed on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

6.3.1 Equipment Lists.-Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings of Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army design fall into two basic classifications: Mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an equipment list references mandatory Army Designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such contractor-prepared designs (see 6.3.4) or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views,

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the currentversion before use.

dimensions, materials, finishes, notes and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to Specification MIL-D-1000, Category A, Form 3. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor design.-All submitted designs shall contain a reference to the applicable 5-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND13. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed to the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

6.4 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

6.5 Supersession data.-This military specification includes the requirements of and supersedes, Purchase Specification AEI-105, preliminary, dated 14 September 1962.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1340-A

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet *is to be filled out by personnel* either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining *information on* the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing *activity*.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:44Z
Check the source to verify that this is the current version before use.