MILITARY SPECIFICATION

LAUNCHER, ROCKET LAU-10/A

This amendment forms a part of Military Specification MIL-L-21910(AER) dated 15 February 1959 and has been approved by the Bureau of Naval Weapons, Department of the Navy.

By this amendment basic MIL-L-21910(AER) is changed to MIL-L-21910(WEP) and throughout the specification Bureau of Aeronautics shall be changed to Bureau of Naval Weapons.

Page 6, paragraph 4.4.8.2: Delete and substitute

"4.4.8.2 Fairings - The grenade type fairings shall be subjected to static loads simulating aerodynamic loads as follows:

(1) AXIAL (externally applied) - 1,390 pounds total load on forward grenade type fairing and 700 pounds total load on aft grenade type fairing, applied in such a manner that the peak load force is at the tip of the cone and gradually diminishing to zero at the base, with equal forces applied over the periphery of the cone.

(2) SIDE (externally applied) - a side load of 437 pounds total load to both forward and aft grenade type fairings equally distributed from the tip of the cone to the base shall be applied in a manner that also distributes the load over approximately one-half of the circumference. The fairings shall withstand the above loads without showing any visible signs of failure or damage other than a slight pull of the material at the fairing to fairing band rivets."

FSC 1055

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:45Z
Check the source to verify that this is the current version before use.