NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND
MIL-PRF-8805/8E
AMENDMENT 1
12 April 1996

PERFORMANCE SPECIFICATION SHEET

SWITCHES, SENSITIVE, SPDT, LEAF
ACTUATOR, LOW LEVEL TO 4 AMPS, HERMETIC SEAL

This amendment forms a part of MIL-S-8805/8E, dated 24 August 1978 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1, wire leads for MS24216-2 and -4 (two places), delete "PER-MIL-W-16878 TYPE E."

PAGE 3

Low level circuit, after "Applicable to MS27216-6.", add "25,000 cycles.".

PAGE 4

TABLE II, 115 Vac 400 Hz resistive lload rating for MS27216-1, -2, -3, and -4, delete "4" (amperes) and substitute "2" (amperes).

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AV, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
Navy - EC

(Project 5930-1523-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:00Z
Check the source to verify that this is the current version before use.