# MILITARY SPECIFICATION

## ALTIMETER, SERVO CONTROLLED, AUTOMATIC

## PRESSURE STANDBY

This amendment forms a part of MIL-A-83419C(USAF) dated 15 October 1979, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete "2.1" and add: "2.1 Government documents."

Add: "2.1.1 Specifications and standards. The following specifications, and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Under Specifications, Federal, delete "QQ-P-416" and add: "PPP-B-601 Boxes, Wood, Cleated Plywood," "PPP-B-636 Box, Shipping, Fiberboard."

Delete "beneficial comments block" in its entirety, and add new beneficial comments block:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

Under Specifications, Military, delete "DOD AIMS 65-852 (1)" and add: "MIL-C-83488 Coating, Aluminum, Ion Vapor Deposited".

Under Standard, Military, delete "MIL-STD-100", "MIL-STD-810", MIL-STD-749" and add: "DOD-STD-100", "MIL-STD-810C" and "MIL-STD-965 Parts Control Program."

PAGE 3


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:04Z
Check the source to verify that this is the current version before use.

Add: "2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documetns which is current on the date of the solicitation.

American Society For Testing And Materials (ASTM)

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

* Add: "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

PAGE 14

Delete "3.4.13.1.1" and add: "3.4.13.1.1 Maintenance task test and demonstration. If any failures occur during reliability testing, the cognizant Government inspector shall be notified to witness the fault isolation, repair, and checkout of the repair. The altimeter shall than be returned to reliability teesting. All failures, actual and simulated, shall be considered as being a part of the timed corrective maintenance task demonstration. If required by the contractor a record of the events shall be submitted to the contracting activity in accordance with the approprite line items on of DD Form 1423 entitled Maintainability Demonstration Reports. When demonstrating simulated failures, the replacement components shall be from a simulated spares inventory and not the same parts that were just removed for the demonstration. Also, alternate source components shall be used as the replacement component or parts on all simulated failure demonstrations.

PAGE 21

* Delete "3.4.24" and add: "3.4.24 Compatibility. The altimeter input requirements shall be compatible with the output characteristics of the CPU-46, the CPU-66, and the following Central Air Data Computers:

| NSN | P/N | Manufacturer |
|---|---|---|
| (1) 6610-01-099-6186 | 2101984-3-1 | AiResearch (64547) |
| (2) 6610-00-110-9455 | 948312-6-1 | AirResearch (70210) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:04Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| (3) 6610-01-047-6627 | 2100756-3-1 | AiResearch (70210) |
| (4) 6610-01-041-0555 | 4025116-904 | Sperry (07187) |
| (5) 6610-01-089-1018 | 4025116-905 | Sperry (07187) |

The altimeter shall also be compatible with the TTU-229/E Test Set."

PAGE 26

3.6 Line 4 delete "MIL-STD-100" and add: "DOD-STD-100".

PAGE 28

3.9 Line 3 delete "MIL-STD-749" and add: "MIL-STD-965".

PAGE 30

Delete "3.15.2" and add: "3.15.2" Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfatory and approved by the preparing activity. Cadmium plating must be avoided when satisfatory alternative processes can be used.

PAGE 31

Add: "4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 44

4.6.23 Line 3 delete "MIL-STD-810" and add: "MIL-STD-810C".

PAGE 45

* 4.6.33 Add: "This test will be conducted by the Government."

Delete Section 5 in its entirety and add:

"5. PACKAGING

5.1 Preservation. Preservation shall be level A, C, or Industrial, as specified (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:04Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Cleaning. Altimeter shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2 Drying. Altimeter shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not aplicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each altimeter shall be packaged in quantity unit packs of one each in accordance with Method IA-5 of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each altimeter shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of Altimeter shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Altimeter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping containers shall be of uniform shape, size, minimum tare and cube consistant with the protection required.

5.2.2 Level B. Altimeter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regualtions.

5.2.4 Industrial. The packaged altimeter shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:04Z
Check the source to verify that this is the current version before use.

PAGE 50

6.4 Linese 9 and 10 delete "the Aeronautical Systems Divisions, Attn: ASD/ENAID, Wright-Patterson Air Force Base, Ohio 45433" and add: "OC-ALC/MMEDO Tinker Air Force Base, OK 73145-5990."

Delete "6.5".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
AIR FORCE -99

Preparing activity:
AIR FORCE -71

Project Number:
6610-F236



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:04Z
Check the source to verify that this is the current version before use.