INCH-POUND
MS18203G
7 March 2013
SUPERSEDING
MS18203F
26 April 1990


DETAIL SPECIFICATION SHEET

SHELL, ELECTRICAL, CONNECTOR, PLUG,
RECTANGULAR, POLARIZING

Reinstated after 10 July 2009 and may be used for new and existing designs and acquisitions.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28748.




Plug shell polarizing

FIGURE 1. Plug shell, configurations.

AMSC N/A FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:17Z
Check the source to verify that this is the current version before use.



Plug shell M18203, polarizing

Inches	mm	Inches	mm
.001	0.03	.109	2.77
.002	0.05	.116	2.95
.003	0.08	.12	3.0
.005	0.13	.120	3.05
.016	0.41	.135	3.43
.021	0.53	.140	3.56
.060	1.52	.150	3.81
.063	1.60	.156	3.96
.070	1.78	.452	11.48
.099	2.51	.719	18.26
		.936	23.77

FIGURE 1. Plug shell, configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:17Z
Check the source to verify that this is the current version before use.

Designator see note 6	Connector size (number of contacts)	A max	B max	C min	D min	E ±.005 (0.13 mm)	F ±.005 (0.13 mm)	G ±.005 (0.13 mm)	R
MS18203-9( )	9	1.440 (36.58)	.500 (12.70)	.375 (9.53)	.864 (21.95)	1.000 (25.40)	---		.141 (3.58)
MS18203-1( )	14	1.380 (35.05)	.567 (14.40)	.440 (11.18)	.800 (20.32)	.938 (23.83)	---		.141 (3.58)
MS18203-17( )	18	1.440 (36.58)	.680 (17.27)	.580 (14.73)	.880 (22.35)	1.000 (25.40)	---	---	.141 (3.58)
MS18203-2( )	20	1.700 (43.18)	.567 (14.40)	.440 (11.18)	1.097 (27.86)	1.250 (31.75)	---		.141 (3.58)
MS18203-10( )	26	1.755 (44.58)	.688 (17.48)	.565 (14.35)	1.182 (30.02)	1.312 (33.32)	---		.141 (3.58)
MS18203-3( )	34	2.130 (54.10)	.880 (22.35)	.745 (18.92)	1.400 (35.56)	1.688 (42.88)	.468 (11.89)		.141 (3.58)
MS18203-4( )	42	2.442 (62.03)	.880 (22.35)	.745 (18.92)	1.700 (43.18)	2.000 (50.80)	.468 (11.89)		.141 (3.58)
MS18203-5( )	50	2.846 (72.29)	1.005 (25.53)	.745 (18.92)	2.026 (51.46)	2.281 (57.94)	.468 (11.89)		.188 (4.78)
MS18203-6( )	66	2.410 (61.21)	1.254 (31.85)	1.115 (28.32)	1.696 (43.08)	1.969 (50.01)	.500 (12.70)		.375 (9.53)
MS18203-7( )	75	2.850 (72.39)	1.365 (34.67)	1.104 (28.04)	2.026 (51.46)	2.281 (57.94)	.234 (5.94)	.766 (19.46)	.187 (4.75)
MS18203-8( )	104	2.890 (73.41)	1.670 (42.42)	1.476 (37.49)	2.073 (52.65)	2.375 (60.33)	.875 (22.23)		.422 (10.72)
MS18203-11( ) see note 8	34	2.130 (54.10)	.880 (22.35)	.745 (18.92)	1.400 (35.56)	1.688 (42.88)	.468 (11.89)		.141 (3.58)
MS18203-12( ) see note 8	42	2.442 (62.03)	.880 (22.35)	.745 (18.92)	1.700 (43.18)	2.000 (50.80)	.468 (11.89)		.141 (3.58)
MS18203-13( ) see note 8	50	2.846 (72.29)	1.005 (25.53)	.745 (18.92)	2.026 (51.46)	2.281 (57.94)	.468 (11.89)		.188 (4.78)
MS18203-14( ) see note 8	66	2.410 (61.21)	1.254 (31.85)	1.115 (28.32)	1.696 (43.08)	1.969 (50.01)	.500 (12.70)		.375 (9.53)
MS18203-15( ) see note 8	75	2.850 (72.39)	1.365 (34.67)	1.104 (28.04)	2.026 (51.46)	2.281 (57.94)	.234 (5.94)	.766 (19.46)	.187 (4.75)
MS18203-16( ) see note 8	104	2.890 (73.41)	1.670 (42.42)	1.476 (37.49)	2.073 (52.65)	2.375 (60.35)	.875 (22.23)		.422 (10.72)

Polarization designators ( ) indicate location of polarization plug A through G (see note 6).

Plug shell MS18203, polarizing

FIGURE 1. Plug shell configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:17Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.016 inch (0.41mm).
4. Material aluminum alloy in accordance with SAE AMS4015, temper O, or ASTM B209, temper H12, .040 inch (1.02mm) thick.
5. Finish anodize in accordance with MIL-A-8625, type I or type II.
6. PIN examples:
   a. Polarization required, specify as MS18203- # (A through G): Example: MS18203-14D (see note 7).
   b. Polarization not required, specify as MS18203- #: Example: MS18203-5.
7 One polarization pin is used when applicable. Polarization pin will be packaged lose. If a polarization pin only is required order separately as MS18205.
8. MS18203-11, -12, -13, -14, -15, and -16 are not used with one-piece jackscrew shields of MS24133.

FIGURE 1. Plug shell configurations - Continued.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-28748, this document references the following:

MIL-A-8625
MS18205
MS24133
ASTM B209
SAE AMS4015

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2009-168)

Review activities:
Army - AM, AR, AT, CR4, MI
Navy - AS, MC, OS
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:17Z
Check the source to verify that this is the current version before use.