INCH-POUND
MS21389E
W/AMDMENDMENT 1
24 August 2026
SUPERSEDING
MS21389E
24 August 2007


PERFORMANCE SPECIFICATION SHEET

COILS, RADIO FREQUENCY, MOLDED, FIXED, SUBMINIATURE, PHENOLIC CORE, TYPES LT4K

Inactive for new design
after 21 February 2003

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described
herein shall consist of this specification and MIL-PRF-15305.



Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
A	.168 (4.27)	.193 (4.90)
B	.420 (10.67)	.440 (11.18)
C	1.300 (33.02)	
D	.023 (0.67)	.027 (0.69)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. These coils are intended to be supported by their leads.
4. Tinned copper lead wire, AWG number 21.

FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1.

Weight: 0.03 ounce, maximum.

Operating temperature range: -55° to +125°C.

Ambient temperature: + 90°C maximum.

Temperature rise: 35°C maximum.

Power dissipation: .500 watt maximum.

Terminal pull: 5 pounds minimum.

Altitude: 60,000 feet.

Shock, specified pulse: MIL-STD-202-213, test condition I, is applicable. Vibration (high frequency): MIL-STD-202-204, test condition G.

Dielectric withstanding voltage (sea level): MIL-STD-202-301, test voltage 700 V rms minimum.

Barometric pressure (reduced): MIL-STD-202-105, test condition C, test voltage 100 V rms minimum.

Electrical characteristics: See tables I and II.

Inductance: See tables I.

Q values: See table I.

Self-resonant frequency (SRF): See table I.

DC resistance (DCR): See table I.

Part or Identifying Number (PIN): MS21389 - (dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.

TABLE 1. Electrical characteristics (initial).

Dash number 1/	Inductance (µH)	Test frequency (MHz)		Q (min)	SRF min (MHz) 1/	Maximum DCR (ohms)	Rated dc current (mA)
		Q	L				
-01	.10 ±20%	50	25	75	500	.02	4000
-02	.12 ±20%	50	25	75	500	.025	3500
-03	.15 ±20%	50	25	75	500	.03	3000
-04	.18 ±20%	50	25	65	500	.03	3000
-05	.22 ±20%	50	25	65	500	.03	3000
-06	.27 ±20%	45	25	65	470	.04	2700
-07	.33 ±20%	40	25	65	440	.05	2500
-08	.39 ±20%	40	25	60	400	.08	2000
-09	.47 ±20%	25	25	55	360	.08	2000
-10	.56 ±20%	25	25	50	330	.10	1700
-11	.68 ±20%	25	25	50	300	.12	1500
-12	.82 ±20%	25	25	45	275	.18	1300
-13	1.0 ±20%	20	25	45	250	.24	1100
-14	1.2 ±20%	20	7.9	45	220	.35	1000
-15	1.5 ±10%	15	7.9	45	200	.43	850
-16	1.8 ±10%	15	7.9	45	180	.65	720
-17	2.2 ±10%	15	7.9	45	165	.80	610

1/ Minimum self-resonant frequency to be not less than 80% of the specified value.

TABLE II. Electrical characteristics (final). 1/

Inspection group	Allowable variation from Initial measurement		Allowable percent from specified minimum value in electrical characteristics (initial) table	
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±2	---	---	-10
Group III	±5	±(3% +.001 ohm)	-8	-10
Group IV	±5	±(2% +.001 ohm)	-10	-10

1/ Test fixture allowance of +.01 µH shall be added to all change in inductance limits ±(_ percent +.01 µH).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical line to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced publications. MIL-PRF-15305, MIL-STD-202-105, MIL-STD-202-204, MIL-STD-202-213, MIL-STD-202-301

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA – CC

(Project 5950-2026-024)

Review activities:
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.