
FED. SUP CLASS
1670



ASSEMBLY

DASH NO
-1
-2

NOTES:

MATERIAL: HOOK, STEEL, MIL-S-5626 OR MIL-S-6049.
GUARD, STEEL, MIL-S-7952 OR QQ-S-698.
SPRING, STEEL, QQ-W-470.
RIVET, CRES, FF-R-556, TYPE XII, CLASS 3, GRADE C, DIAMETER AND LENGTH TO SUIT.

METHOD OF FORMING: HOOK - HOT FORGE.

HEAT TREATMENT: HOOK - 170,000 TO 190,000 LBS/SQ IN. TENSILE STRENGTH IN ACCORDANCE WITH MIL-H-6875.
GUARD - NONE.
SPRING - AS REQUIRED BY FINISH SPECIFICATION.

SURFACE ROUGHNESS SHALL BE $\sqrt{125}$ MAX. IN ACCORDANCE WITH ANSI B46.1

FINISH: HOOK, SPRING AND GUARD BEFORE ASSEMBLY
-1, CADMIUM PLATE, QQ-P-416, CLASS 1, TYPE I.
-2, PHOSPHATE COAT, MIL-C-16232, TYPE Z, CLASS 4B FOLLOWED BY WAX EMULSION MIL-W-3688 (OPTIONAL FINISH FOR SPRING -1 AS ABOVE).

DIMENSIONS IN INCHES. EXCEPT AS OTHERWISE SPECIFIED HEREIN, TOLERANCES: DECIMALS ± .03, ANGLES ± 2°. WIRE AND METAL GAGES EXCLUDED.

PROOF LOAD: SNAP HOOK SHALL BE SUBJECTED TO THE PROOF LOAD SPECIFIED, AS INDICATED BY ARROWS.

ALL PERPENDICULAR SURFACES SHALL INTERSECT WITH A .04-.11 RADIUS UNLESS OTHERWISE SPECIFIED.

SNAP HOOK ASSEMBLY SHALL PASS FREELY OVER A .281 DIA. ROD.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

Ⓐ ENTIRE STANDARD REVISED.

APPROVED 12 MAY 61 REVISED Ⓐ 11 APR 75

Preparing activities:
NAVY-MC
ARMY-AV

Review activities:
AIR FORCE-11

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.


P.A. AIR FORCE-82 Other Cust NAVY-AS ARMY-GL	TITLE SNAP HOOK-QUICK CONNECTOR, PARACHUTE HARNESS	MILITARY STANDARD MS22042
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES: AN6507	SHEET 1 OF 3

DD FORM 1 SEP 67 672-1 (Coordinated)


PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-23T14:44Z
Check the source to verify that this is the current version before use.

FED: SUP CLASS
1670




HOOK




SECTION A-A



SECTION B-B



SECTION C-C



SECTION D-D

SECTION E-E

" FOR CHANGES SEE SHEETS 1, 2 & 3.

APPROVED 12 MAY '61

User activities:
NAVY - MC
ARMY - AV

Review activities:
AIR FORCE - 11

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.


P.A. AIR FORCE-82 Other Cust NAVY-AS ARMY-GL	TITLE SNAP HOOK-QUICK CONNECTOR, PARACHUTE HARNESS	MILITARY STANDARD MS22042
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES: AN6507	SHEET 2 OF 3

DD FORM 1 SEP 57 672-1 (Coordinated)


PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-23T14:44Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
1670



GUARD



SPRING

APPROVED 12 MAY '61

" FOR CHANGES SEE SHEETS 1, 2 & 3 "

User activities:
NAVY - MC
ARMY - AV

Review activities:
AIR FORCE - 11

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. AIR FORCE-82 Other Cust NAVY-AS ARMY-GL	TITLE SNAP HOOK-QUICK CONNECTOR, PARACHUTE HARNESS	MILITARY STANDARD MS22042
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES AN6507	SHEET 3 OF 3

DD FORM 1 SEP 57 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-23T14:44Z
Check the source to verify that this is the current version before use.