
FED. SUP CLASS
6640



PART NUMBER	DIMENSIONS (cm) WIDTH	DEPTH	HEIGHT	DESCRIPTION
MS36224-1	68.9	59.7		hout blower
MS36224-2	68.9			1/10 hp blower FM @ .25" S.P.
MS36224-3 MS36224- MS3622.				fix letter ired equip-

CANCELLED
CANCELLED AFTER 10 JUN 1991
NO SUPERSEDING STANDARD

MATERIAL: ... resin and

DESIGN: Th... ...e fire-resistant fiberglass; ext... ...all hoods shall include the follow-ing: ...unt counterbalanced sash, removable access pane... ...per and servicing, 100 watt incandescent light and s... ...ne hood shall be shipped fully assembled, requiring only w... ... connection to an electrical source; it may be mounted on any con... ...ional base. Color of body shall be soft white. Color of access panel shall be as available and specified.

Part numbers MS36224-3 thru -5 must have a suffix letter to complete the description of the fume hood. Models with suffix letters A, B, C and D have by-pass air flow systems. This system minimizes fluctuation in face velocity by permitting air to flow above and below the sash, when the sash is in a down position. Hoods with suffix letters E, F, G and H are models with an additional source of outside air, which is introduced into the hood exhaust and limits the percentage of room air exhausted.

Suffix J is for including factory installed service fixtures for gas, air, vacuum or water. The fixtures can be operated with the sash in any position. Suffix J can be added to the part number after any of the other suffix letters.

Description of equipment covered by each suffix letter:

Suffix A includes integral exhaust blower, equipped with .5 hp motor, 115V AC 60Hz, providing minimum face velocity of 30.5 M/M (20.4 M^3/M) at external static pressure of 6.25 mm H_2O. Unit shall have a vapor proof light, internal wiring and switches.

Ⓐ CANCELLATION

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
EA		HOOD, FUME, LABORATORY, FIBERGLASS MODELS	MS 36224
Other Cust MS 99			
Procurement Specifications NONE	SUPERSEDES:		SHEET 1 OF 2

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE CANCELLATION

Project Number 6840-1712-01

APPROVED 22 JUN 1983 REVISED Ⓐ 10 JUN 1991

USER ACTIVITIES:

REVIEWER ACTIVITIES:

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:36Z
Check the source to verify that this is the current version before use.

APPROVED 22 JUN 1983 REVISED (A) 10 JUN 1

USER ACTIVITIES:

REVIEWER ACTIVITIES:

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

...mm at 30.5 M/M face velocity
...ough add-air plenum of hood shall
/M (50% add-air/exhaust ratio). Unit
ight, 115V AC 60Hz. Wiring not included.

conform to the standards of Underwriters

ary Standard by minor variations in design
andard under this document, provided such
nance and are not in conflict with the
herein.

Suffi
proof
(20.4
an ex

Suffi
loss
(20.4

Suffi
loss
(20.4
Wirin

Suffi
115V
exter
hp mo
of 6.
proof

Suffi
proof
(20.4
blowe
M^3/M
ratio

FUME, LABORATORY, FIBERGLASS MODELS	MILITARY STANDARD
	MS36224
	SHEET 2 OF 2

...US EDITIONS OF THIS FORM ARE OBSOLETE

DATE

nd
sha

Suff
loss
(20.4
not e
shall

All e
Labor

FED. SUP CLASS
6640

NOTE: Items
or di
varia
mater

...ust blower, equipped with .5 hp explosion
...viding minimum face velocity of 30.5 M/M
pressure of 6.25 mm H_2O. Unit shall have
ng not included.

located motor/blower. Static pressure
exceed 12.5 mm H_2O at 30.5 M/M velocity
a vapor proof light, 115V AC, 60Hz.

located motor blower. Static pressure
exceed 12.5 mm H_2O at 30.5 M/M face velocity
n explosion proof light, 115V AC, 60Hz.

...ust blower, equipped with .5 hp motor,
m face velocity of 30.5 M/M (20.4 M^3/M) at
5 mm H_2O. Integral add-air blower with .5
m of 10.2 M^3/M at external static pressure
aust ratio). Unit shall have a vapor
d switches.

...ust bl...
...

5 hp explosion
v of 30.5 M/M
ntegral add-air
nimum of 10.2M
·/exhaust
ot included.

pressure
face velocity
...d shall
Unit

P.A. EA	
Other Custodians MS 99	
Procurement Specifications NONE	

DD FORM 672 (COORD...

...LLED

AFTER 10 JUN 1991

...STANDARD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:36Z
Check the source to verify that this is the current version before use.