MIL-C-24593A(SH)
13 January 1986
SUPERSEDING
MIL-C-24593(SH)
29 June 1979
(See 6.5)

MILITARY SPECIFICATION

CLEANER, VACUUM, ASBESTOS REMOVAL

This specification is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. The vacuum cleaners covered by this specification are to be used for pickup of debris, including dry asbestos dust and fibers.

1.2 Classification. Vacuum cleaners covered by this specification shall be of the following types, as specified (see 6.2.1):

Type I - The type I cleaner shall weigh no more than 60 pounds with attachments, when full, and shall have a waste capacity of 4 to 8 gallons.
Type II - The type II cleaner shall weigh no more than 100 pounds with attachments, when full, and shall have a waste capacity of 8 to 13 gallons.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7910

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-P-15024 - Plates, Tags and Bands for Identification of Equipment.
MIL-P-15024/5 - Plates, Identification.
MIL-E-16298 - Electric Machines Having Rotating Parts and Associated Repair Parts: Packaging of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-740 - Airborne and Structureborne Noise Measurements and Acceptance Criteria of Shipboard Equipment.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government publication. The following other Government publication forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF LABOR

Code of Federal Regulations, Title 29
Part 1910 - Occupational Safety and Health Standards, Section 145 and 1001.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging. (DoD adopted)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

UNDERWRITERS LABORATORIES, INC. (UL)

UL 1017 - Vacuum Cleaning Machines and Blower Cleaners.

(Application for copies should be addressed to Underwriters Laboratories, 333 Pfingsten Road, Northbrook, IL 60062.)

Source: https://assist.dla.mil -- Downloaded: 20261O-19T23:12Z
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. The materials used shall be free from defects affecting the appearance or serviceability of the cleaners.

3.1.1 Recovered materials. Unless otherwise specified herein, all equipment, material, and articles incorporated in the products covered by this specification shall be new and may be fabricated using materials produced from recovered materials to the maximum extent practicable without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specifically specified.

3.2 Fire and casualty hazards.

3.2.1 Safety compliance. The cleaner shall conform to the requirements of UL 1017 including methods of testing and test results. UL listing under UL 1017 is evidence that the cleaner conforms to this requirement (see 6.2.2).

3.3 Construction.

3.3.1 Components. Type I and type II cleaners shall consist of a housing, handles or grips for carrying, vacuum producer assembly, filter assembly, switch, cord assembly, hose, wand, and specified tools and attachments (see 3.14).

3.3.2 Interchangeability. Component parts and assemblies for identical model number cleaners from any one contractor shall be fully interchangeable; such interchangeability shall not require any alteration or modification.

3.3.3 Each cleaner shall be complete, fully lubricated, and ready to operate (minor assembly is permitted). The design shall be simple in construction and assembly, shall permit ready accessibility to component parts for inspection, cleaning, or replacement, and shall provide reliable operation. Cleaners once assembled shall not require any external adjustment by the operator to assure performance of the cleaner. Hose and wand attachment shall be secure (see 4.3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

3.4 Filtration system. The filtration system shall remove 99.95 percent of polydisperse dioctyl phthalate (DOP) generated by blowing compressed air through the DOP to give a cloud of droplets with a mean diameter of 0.7 micrometers (µm) when the vacuum is operating at its rated volume. A certificate of compliance with the above criteria shall be provided in accordance with the data ordering document specified in the contract or purchase order (see 6.2.2). The filters comprising the filtration system shall be fastened securely to their respective mounting assemblies, in such a manner as to be resistant to accidental misalignment or displacement during normal use of the cleaner. The security of the filtration system fasteners shall be demonstrated by a 3-foot drop test (see 4.3.4). The filtration system shall contain the following filters as specified in 3.4.1 through 3.4.4 (see 4.3.5).

3.4.1 Primary filter. The primary filter shall be a disposable paper bag filter to contain the majority of waste. Each filter shall be marked or labeled with the precautionary marking (see 3.12).

3.4.2 Intermediate filters. The intermediate filters shall be fiberglass or tight weave cloth prefilters or other similar devices to protect and extend the life of the high efficiency particulate air (HEPA) filter. The intermediate filters shall prevent the passage of any waste larger than 50 µm into the HEPA filter. Each filter shall be marked or labeled with the precautionary marking (see 3.12).

3.4.3 Final filter. The final filter shall be a HEPA filter which shall effectively remove 99.97 percent of thermally generated monodisperse DOP smoke particles with a diameter of 0.3 µm.

3.4.4 The primary filter and intermediate filters shall remove the majority of asbestos dust and fibers to prevent premature clogging of the HEPA filter, thereby extending the HEPA filter's service life.

3.5 Motor. The motor shall be in accordance with UL 1017 and the following:

Voltage - nominal 115 volts (V) (110-120), alternating current (ac).
Frequency - 60 hertz (Hz).
Enclosure - enclosed.
Duty rating - continuous or intermittent.
Power rating - minimum 1 horsepower (hp).
70 degrees Celsius (°C) rise allowed over 50°C ambient temperature.

3.6 Switch. The switch shall be in accordance with UL 1017.

3.7 Power cord assembly. The cleaner's cord and plug assembly shall be 3-wire grounded type or shall be 2-wire type if the cleaner is double insulated, in accordance with UL 1017. Minimum power cord length shall be 20 feet for type I and 35 feet for type II.

3.8 Cord storage. Each cleaner shall have provision for power cord storage, such as coiling, wrapping or reeling.

3.9 Sound pressure level. When measured 3 feet from all surfaces of the unit (see 4.3.6), the cleaner shall not emit greater than 84 decibels (dB) while in use, either full or empty.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

3.10 Suction. Cleaners shall possess suction to collect asbestos debris present on flat work surfaces as well as from crevices, using attachments. The minimum performance criterion shall be a suction of 50 inches of water vacuum when tested in accordance with 4.3.1 with the cleaner container empty of debris and clean filters installed, and 5 inches of water vacuum with the cleaner full and filters clogged with fiberglass.

3.10.1 Crush resistance. The hose shall demonstrate crush resistance when tested in accordance with 4.3.2.

3.11 Portability.

3.11.1 Type I cleaner. The type I cleaner shall pass through an 18-inch diameter hole (attachments may be removed), and be carried through 30- by 36-inch hatches.

3.11.2 Type II cleaner. The type II cleaner shall pass through a 27-inch wide doorway, when being carried in a normal position.

3.11.3 Wheels and casters shall be provided for ease of use of the unit.

3.12 Labeling. The cleaner shall be provided with two "CAUTION" labels, prominently located, one on each side of the cleaner, in letters not less than 3/8-inch high. The primary and intermediate filters shall be provided with "CAUTION" labels. The "CAUTION" labels shall read as follows:

"CAUTION
CONTAINS ASBESTOS FIBERS
AVOID CREATING DUST
BREATHING ASBESTOS DUST MAY CAUSE
SERIOUS BODILY HARM"

The "CAUTION" labels shall conform to OSHA Regulations, Part 1910; Sections 145 and 1001.

3.12.1 Each cleaner shall also bear a manufacturer's nameplate in accordance with MIL-P-15024 and MIL-P-15024/5 on the outside shell citing the manufacturer's name, UL listing number if available, contract number, and model number of the cleaner.

3.13 Finish. Exterior surfaces and those interior surfaces impinged upon by the air flow and surfaces subject to contact by the operator, shall be smooth and free from surface defects or obstructions which may contribute to dirt adherence or operator injury. Exterior surfaces shall be smooth, of uniform appearance, and plated or finished to resist abrasion and corrosion. Platings and finishes shall be in accordance with the best commercial practice.

3.14 Attachments. The following attachments shall be supplied with each cleaner:

(a) Wands, 1- or 2-piece, or telescoping assembly, 1-1/4 inches outside diameter (od), minimum, and 4 feet in length, minimum.
(b) Hose, 1-1/4 inches, od, minimum, 6 feet long, minimum, to connect wands to vacuum cleaner.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

(c) Flat surface nozzle, for connection to wand.
(d) Crevice nozzle, for connection to wand.

3.14.1 When specified (see 6.2.1), optional attachments shall be provided.

3.15 Technical manual. Technical manuals shall be furnished in accordance with the data ordering document specified in the contract or purchase order (see 6.2.2).

3.16 Workmanship. The cleaner, tools and attachments shall be constructed, assembled, and finished to assure good quality equipment of a neat general appearance and free from imperfections which may affect durability, operability or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 End item inspection.

4.2.1 Sampling. The inspection lot shall consist of all vacuum cleaners of one type offered for inspection at one time. The sample unit for this inspection shall be one complete vacuum cleaner.

4.2.2 Visual examination. Examination shall be made of the end item for defects listed in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-19T23:12Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects.

Examine	Defects	Major	Minor
Finish	Finish not as specified in 3.13.		X
	Dirt, grit or other foreign matter imbedded in finish.		X
	Not finished where required.		X
	Finish not adherent.		X
Construction and workmanship	Fractured, split, bowed, or malformed.	X	
	Parts or components missing.	X	
	Assembly locks and clamps do not provide tight fit.	X	
	Filters not as specified.	X	
	Handle not securely attached.	X	
	Parts loose or not tight fit where required, not properly assembled.	X	
	Sharp burrs, edges, slivers or projections.		X
Hose	Not as specified.	X	
Attachments	Not as specified.	X	
	Not interchangeable.	X	
Electrical assembly	Wiring cut, abraded.	X	
	Adequate slack not provided for wiring or excessive insulation stripped from wiring.		X
	Cord length not as specified.	X	
	Motor not as specified.	X	
Marking for identification and caution	Missing, incorrect, illegible or incomplete.	X	
Manuals	Not as specified.	X	

4.2.3 Dimensional and weight examination. Examination shall be made of the end item for compliance with dimensions and weight specified (see 1.2). Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units in accordance with MIL-STD-105.

4.2.4 End item testing. Each sample cleaner shall be tested in accordance with the tests of 4.3. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units in accordance with MIL-STD-105.

4.3 Tests.

4.3.1 Performance tests. Cleaners shall be connected to a 120 V, 60 Hz power source and shall be tested by one continuous run (after temperature has stabilized) at normal full load operating condition for dry pickup. The degree of vacuum shall be determined during the run by connecting one end of

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

the specified hose to the air inlet and the attachment end to a static pressure chamber containing an orifice of 9/16-inch. The manometer reading shall be not less than the vacuum values specified in 3.10. Any noncompliance with the suction requirement of 3.10 shall constitute a defect.

4.3.1.1 One sample cleaner of each type shall be subjected to the performance test of 4.3.1 with the container full of fiberglass debris and the filters clogged with fiberglass to the point of replacement. Minimum acceptable suction in this loaded condition is 5 inches of water vacuum. Failure of the sample to meet this criterion shall be cause for rejection of that type cleaner.

4.3.2 Hose test. A compressive load of 150 pounds shall be applied to any portion of the hose by means of parallel surfaces having a length of not more than 3 inches parallel to the axis of the hose for not less than 2 minutes then released. Rupture or perforation of the hose shall constitute a defect.

4.3.3 Attachment test. A tensile force of 25 pounds shall be applied to the engaged cleaner hose and each attachment for not less than 2 minutes in accordance with 3.3.3. Separation of hose and attachments shall constitute failure of this test.

4.3.4 Drop test. The fit of filters in the sample units shall be checked. Filters shall not be dislodged when the cleaner is subjected to a 3-foot drop test (see 3.4). Breaking or bending of wheels or casters or their supports is permissible as a result of the drop test. One sample cleaner of each type shall be so tested, both empty and full. Any damage to the cleaner or dislodgement of filters (as determined by a disassembly and visual inspection of the unit) resulting in loss or decrease of function as a result of this drop test shall be cause for rejection of that type cleaner.

4.3.5 Filtration tests. Filtration tests to meet the requirements of 3.4 shall be performed by a testing laboratory.

4.3.6 Sound pressure level. The sound pressure level shall be determined using test procedures of MIL-STD-740 except that airborne noise levels shall be not greater than 84 dB (see 3.9).

4.4 Examination of packaging. An examination shall be made to determine that packaging, packing, preservation, and marking as specified in section 5 of this specification are complied with. Defects shall be scored as specified in table II. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one shipping container fully prepared for delivery. The inspection level shall be S-2 and the AQL shall be 4.0 defects, expressed in terms of defects per hundred units in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202640-19T23:12Z
Check the source to verify that this is the currentversion before use.

TABLE II. Examination of packaging.

Examination	Defects
Preservation Markings (exterior and interior) Materials Workmanship	Missing, not performed as specified. Missing; incorrect; illegible; of improper size, location, sequence or method of application. Component missing or damaged. Inadequate application of components such as bulging or distortion of containers; or blocking, bracing, cushioning, caseliners inadequate or missing.

4.4.1 Examination of shipping containers. Examination for defects in closure and strapping of shipping containers shall be in accordance with the appendix of the applicable container specification.

5. PACKAGING

(The packaging requirements specified herein apply only for direct Government acquisition. For the extent of applicability of the packaging requirements of referenced documents listed in section 2, see 6.3.)

5.1 Packaging.

5.1.1 Cleaners. Each clearner shall be preserved level A or C, packed level A, B or C as specified (see 6.2.1) and marked in accordance with MIL-E-16298. When specified (see 6.2.1), each cleaner shall be commercially packaged and marked in accordance with ASTM D 3951.

5.1.2 Attachments. Attachments (see 3.14) shall be preserved level A or C as specified (see 6.2.1) in accordance with MIL-E-16298 and consolidated in an intermediate corrugated fiberboard container minimum grade 200 domestic class. The attachments containers shall be packed in the cleaner shipping container but shall not be enclosed with the cleaner flexible barrier bag. When specified (see 6.2.1), attachments shall be preserved and packed in accordance with ASTM D 3951.

5.1.3 Manuals. Technical manuals (see 3.15) shall be preserved in a minimum 4 mil polyethylene bag, heat sealed and packed in the cleaner shipping container. Manuals shall not be placed within the cleaner flexible barrier bag.

6. NOTES

6.1 Intended use. The vacuum cleaners covered by this specification are intended for use aboard Navy ships, when ship's force repairs have been accomplished on asbestos insulation, and the resultant dust and fibers must be removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type desired (see 1.2).
(c) Special accessories or attachments, if required (see 3.14.1).
(d) Levels of preservation-packaging and packing required (see 5.1).

6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

Paragraph no.	Data requirement title	Applicable DID no.	Option
3.2.1, 3.4	Certificate of compliance	DI-E-2121	----
3.15	Manuals, technical	DI-M-2071	----

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L., Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.2.2.1 The data requirements of 6.2.2 and any task in sections 3, 4, or 5 of this specification required to be performed to meet a data requirement may be waived by the contracting/acquisition activity upon certification by the offeror that identical data were submitted by the offeror and accepted by the Government under a previous contract for identical item acquired to this specification. This does not apply to specific data which may be required for each contract regardless of whether an identical item has been supplied previously (for example, test reports).

6.3 Sub-contracted material and parts. The packaging requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped.

6.4 Provisioning. Provisioning Technical Documentation (PTD), spare parts, and repair parts should be furnished as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

6.4.1 When ordering spare parts of repair parts for the equipment covered by this specification, the contract should state that such spare parts and repair parts should meet the same requirements and quality assurance provisions as the parts used in the manufacture of the equipment. Packaging for such parts should also be specified.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 7910-N064)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-24593A(SH)	CLEANER, VACUUM, ASBESTOS REMOVAL

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:12Z
Check the source to verify that this is the current version before use.

DD FORM 1426