INCH-POUND

MIL-V-24569(SH)
AMENDMENT 3
2 November 1992
SUPERSEDING
AMENDMENT 2
8 November 1983

MILITARY SPECIFICATION

VALVE, QUICK-CLOSING, FOR FUEL AND OIL
AND AUXILIARY STEAM EMERGENCY SHUTDOWN

This amendment forms a part of MIL-V-24569(SH), dated 17 July 1978, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, line 2: Delete "1000" and substitute "600".

1.2.1: Delete "Type I - Steel, flanged." and substitute:

"Type IA - Steel, flanged, steam or fuel service.
Type IB - Steel, flanged, fuel service."

1.2.2: Delete and substitute:

"1.2.2 Rating. Types IA and IB valves shall be class 600, in accordance with ANSI B16.34, and type II valves shall have class 150 flanges in accordance with MIL-F-20042 (see 6.2.1)."

Beneficial comments statement at bottom of page, line 3: Delete "Naval Ship Engineering Center, SEC 6124" and substitute "Naval Sea Systems Command, SEA 05Q42".

* 2.1: Add the following military specification:

"MIL-A-24780 - Actuating Assembly, Single Linear Motion, for the Remote Actuation of Quick Acting Valves, General Specification for."

AMSC N/A FSC 4820

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

PAGE 3

TABLE I, under "Part" column: Add "(see 3.3.12.4)" under "Gaskets".

TABLE I, under "Applicable documents": Delete "Type I valves" and substitute "Types IA and IB valves".

PAGE 4

* Add new paragraph 3.3.6.1:

"3.3.6.1 Valve junction box shall be compatible with actuating assembly of MIL-A-24780."

PAGE 5

3.3.12, line 1: Delete "type I" and substitute "types IA and IB".

Add new paragraph 3.3.12.4:

"3.3.12.4 Type IA valves shall employ bonnet gaskets in accordance with MIL-G-21032, type I. Type IB valves may use commercial seals."

* Add new paragraph 3.4.1:

"3.4.1 Shock. The valve and actuating assembly shall withstand the requirements of grade A, class I, type C shock in accordance with MIL-S-901, MIL-STD-798, and MIL-A-24780."

* Add new paragraph 3.5.1:

"3.5.1 Vibration. The valve and actuating assembly shall withstand the requirements of vibration tests in accordance with MIL-STD-167-1, type I, and MIL-A-24780."

3.6.1, line 1: Delete "type I" and substitute "types IA and IB".

3.7: Delete and substitute:

"3.7 Line pressure. The valve shall open against a line pressure of 600 lb/in^2 fuel or steam for type IA and IB valves, and 150 lb/in^2 for a type II valve without the aid of an external equalizing bypass."

3.12: Delete and substitute:

"3.12 Seat leakage and pressure drop. The valve shall have a maximum initial seat leakage of 10 cubic centimeters per hour (cm^3/h) per inch of nominal size for a valve 1 inch and larger, and 10 cm^3/h total for a valve less than 1 inch in size. The test shall be conducted at 600 lb/in^2 for types IA and IB valves and 150 lb/in^2 for type II valves. The testing medium shall be clean tap water with no additives other than mineral cutting oil or clean hydraulic oil with no suspensions. The pressure drop through the valve shall be 0.5 lb/in^2 maximum at the rated flow condition."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

PAGE 8

4.6.1.1: Delete and substitute:

"4.6.1.1 The valve shall be pressurized each cycle to 600 lb/in^2 for type IA and IB valves and 150 lb/in^2 for type II valves."

* Add new paragraph 4.6.2.1:

"4.6.2.1 Shock. The valve and actuating assembly shall be shock tested to ensure compliance with the requirements specified in 3.4 and MIL-A-24780."

* Add new paragraph 4.6.3.1:

"4.6.3.1 Vibration. The valve and actuating assembly shall be vibration tested to ensure compliance with the requirements specified in 3.5 and MIL-A-24780."

4.6.5, second sentence: Delete and substitute: "Test pressure shall be 600 lb/in^2 for types IA and IB valves and 150 lb/in^2 for type II valve."

PAGE 9

6.1: Add "(see 1.2.1)".

LAST PAGE

DD 1426, Standardization Document Improvement Proposal: Delete address and substitute:

"COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 05Q42)
2531 NATIONAL CENTER BUILDING 3
WASHINGTON, DC 20362-5160"

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 4820-N055)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.