INCH-POUND
MIL-DTL-24569A(SH)
13 October 2020
SUPERSEDING
MIL-V-24569(SH)
17 July 1978

DETAIL SPECIFICATION

VALVE, QUICK-CLOSING, FOR FUEL OIL AND AUXILIARY STEAM EMERGENCY SHUTDOWN

Reactivated after 13 October 2020 and may be used for new and existing designs and acquisitions.

This specification is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a flanged, one-way, quick-closing valve for fuel oil up to 600 pounds per square inch (lb/in^2) (41 bar) at ambient temperature and auxiliary steam service at 600 lb/in^2 (41 bar) and 775 °F (413 °C), for emergency shutdown use aboard naval vessels.

1.2 Classification. Valves are of the following types and ratings (see 1.2.1 and 1.2.2) as specified (see 6.2).

1.2.1 Types.

a. Type IA – Steel, flanged, steam or fuel service

b. Type IB – Steel, flanged, fuel service

c. Type II – Bronze, flanged

1.2.2 Ratings. Type IA and IB valves are class 600 in accordance with ASME B16.34. Type II valves have class 150 flanges in accordance with MIL-PRF-20042.

1.3 Part or identifying number (PIN). PINs are for general information only. The acquisition requirements (see 6.2) take precedence. The PINs to be used for valves acquired to this specification are created as follows:

M	**24569**	**-**	**XX**	**-**	**XXXX**
Prefix for Military Specification	Specification Number	-	Type (see 1.2.1)	-	Nominal Pipe Size (NPS) (see 1.3.1)

1.3.1 NPS PIN code. The NPS PIN code is a four-digit digital representation of NPSs from ¼ to 24 in accordance with ASME B16.5. For example, NPS 2½ is PIN code 0250, NPS 5½ is PIN code 0550, and NPS 12 is PIN code 1200.

1.3.2 Example PINs. M24569-IB-0300 is a steel, flanged valve of NPS 3 for fuel service use. M24569-II-0200 is a bronze, flanged valve of NPS 2.

Comments, suggestions, or questions on this document should be addressed to Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 4820

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

FEDERAL SPECIFICATIONS

QQ-N-281 - Nickel-Copper Alloy Bar, Rod, Plate, Sheet, Strip, Wire, Forgings, and Structural and Special Shaped Sections

QQ-N-286 - Nickel-Copper-Aluminum Alloy, Wrought (UNS N05500)

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-DTL-901 - Shock Tests, H.I. (High-Impact) Shipboard Machinery, Equipment, and Systems, Requirements for

MIL-R-17131 - Rods and Powders, Welding, Surfacing

MIL-PRF-20042 - Flanges, Pipe, Bronze (Silver Brazing)

MIL-B-24480 - Bronze, Nickel-Aluminum (UNS No. C95800) Castings for Seawater Service

MIL-G-24716 - Gaskets, Metallic-Flexible Graphite, Spiral Wound

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-167-1 - Mechanical Vibrations of Shipboard Equipment (Type I – Environmental and Type II – Internally Excited)

MIL-STD-798 - Design Evaluation Requirements for Valves for Naval Shipboard Use

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

GENERAL SERVICES ADMINISTRATION

GSA Global Supply Catalog

(Copies of this document are available online at https://www.gsaglobalsupply.gsa.gov.)

NAVAL SEA SYSTEMS COMMAND (NAVSEA) DRAWINGS

803-1385541 - Valves, Bronze, Flanged, In-Line & Angle Stop & Stop Check 2-1/2 - 12

803-2145505 - Fuel Service System Emergency Shut Downs

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

(Copies of these documents are available from the applicable repositories listed in S0005-AE-PRO-010/EDM, which can be obtained online via Technical Data Management Information System (TDMIS) at https://mercury.tdmis.navy.mil/. Copies of these documents may also be obtained from the Naval Ships Engineering Drawing Repository (NSEDR) online at https://199.208.213.105/webjedmics/index.jsp. To request an NSEDR account for drawing access, send an email to NNSY_JEDMICS_NSEDR_HELP_DESK@navy.mil.)

NAVAL SEA SYSTEMS COMMAND (NAVSEA) PUBLICATIONS

S9074-AR-GIB-010/278 - Requirements for Fabrication Welding and Inspection, and Casting Inspection and Repair for Machinery, Piping, and Pressure Vessels

(Copies of this document are available online via Technical Data Management Information System (TDMIS) at https://mercury.tdmis.navy.mil/ by searching for the TMIN without the suffix. Refer questions, inquiries, or problems to: DSN 296-0669, Commercial (805) 228-0669. This document is available for ordering (hard copy) via the Naval Logistics Library https://nll.ahf.nmci.navy.mil. For questions regarding the NLL, contact the NLL Customer Service at nllhelpdesk@navy.mil, (866) 817-3130, or (215) 697-2626/DSN 442-2626.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR QUALITY (ASQ)

ANSI/ASQ Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at www.asq.org.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME B1.12 - Class 5 Interference-Fit Thread

ASME B16.5 - Pipe Flanges and Flanged Fittings: NPS 1/2 through NPS 24 Metric/Inch Standard

ASME B16.10 - Face-to-Face and End-to-End Dimensions of Valves

ASME B16.34 - Valves--Flanged, Threaded, and Welding End

ASME B18.2.1 - Square, Hex, Heavy Hex, and Askew Head Bolts and Hex, Heavy Hex, Hex Flange, Lobed Head, and Lag Screws (Inch Series)

ASME B18.3 - Socket Cap, Shoulder, Set Screws, and Hex Keys (Inch Series)

(Copies of these documents are available online at www.asme.org.)

ASTM INTERNATIONAL

ASTM A105/A105M - Standard Specification for Carbon Steel Forgings for Piping Applications

ASTM A182/A182M - Standard Specification for Forged or Rolled Alloy and Stainless Steel Pipe Flanges, Forged Fittings, and Valves and Parts for High-Temperature Service

ASTM A193/A193M - Standard Specification for Alloy-Steel and Stainless Steel Bolting for High Temperature or High Pressure Service and Other Special Purpose Applications

ASTM A194/A194M - Standard Specification for Carbon Steel, Alloy Steel, and Stainless Steel Nuts for Bolts for High Pressure or High Temperature Service, or Both

ASTM A216/A216M - Standard Specification for Steel Castings, Carbon, Suitable for Fusion Welding, for High-Temperature Service

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

ASTM A479/A479M - Standard Specification for Stainless Steel Bars and Shapes for Use in Boilers and Other Pressure Vessels

ASTM A582/A582M - Standard Specification for Free-Machining Stainless Steel Bars

ASTM B61 - Standard Specification for Steam or Valve Bronze Castings

(Copies of these documents are available online at www.astm.org.)

SAE INTERNATIONAL

SAE AMS-QQ-S-763 - Steel, Corrosion Resistant, Bars, Wire, Shapes, and Forgings

SAE J1086 - Numbering Metals and Alloys

(Copies of these documents are available online at www.sae.org.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample valve with tripping actuator shall be subjected to first article inspection in accordance with 4.2.

3.2 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.3 Materials. Materials shall be as specified in table I or, where not specified, shall be manufacturer-selected materials compatible to the purpose intended. Fasteners shall be in accordance with 3.3.1.

TABLE I. Materials.

Part	Material form	Applicable documents	
		Type IA and IB valves	Type II valves
Body and bonnet	Forgings and castings	ASTM A105/A105M; ASTM A216/A216M, grade WCB	ASTM B61, alloy C90300 or C92200; MIL-B-24480 (C95800)
Gaskets (see 3.4.3)	Spiral wound, metal crush elastomer	MIL-DTL-24716, type I, metal, commercial	Commercial
Pressure boundary penetration seal	Bellows; plastic, metallic; plastic non-metallic	Commercial	Commercial
Seats, discs, or seat and disc facings	Hard-facing, investment cast or bar stock	MIL-R-17131, type MIL-RCoCr-A	QQ-N-281; QQ-N-286
Stems or pressure boundary penetration rods	Forged or rolled	ASTM A182/A182M, grade F6 (S41000); ASTM A582/A582M, type 416 (S41600); ASTM A479/A479M, 3.4.3 type 410 (S41000); SAE AMS-QQ-S-763	QQ-N-281; QQ-N-286

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

TABLE I. Materials – Continued.

Part	Material form	Applicable documents	
		Type IA and IB valves	Type II valves
Studs, cap screws and through-bolts		ASTM A193/A193M, grades B7 (G41400) and B16	QQ-N-281; QQ-N-286; ASTM B105
Nuts for pressure containment	Heavy semi-finished hexagon; carbon and alloy steel for temperature bolting	ASTM A194/A194M, grades 2, 2H, and 4	QQ-N-281; QQ-N-286; ASTM B105
NOTE: Alloys are cited by their Unified Numbering System (UNS) number in accordance with SAE J1086.			

3.3.1 Threaded fasteners for pressure containing parts. Threaded fasteners for pressure containing parts shall be any of the following:

a. Through-bolts threaded the entire length and fitted with a nut on each end. Threads on the bolts and nuts shall be class 2 fit.

b. Tap end studs with interference class 5 fit at tap end and a class 2 fit at nut end. Stud engagement length shall be in accordance with ASME B1.12.

c. Hex head cap screws in accordance with ASME B18.2.1 or hexagon socket head cap screws in accordance with ASME B18.3. The cap screws shall be engaged a minimum of one diameter length of fully formed threads.

3.4 Design and construction. Design and construction shall be as specified in 3.4.1 through 3.4.4.

3.4.1 Design characteristics of all valves.

a. The valves shall be capable of being actuated locally and remotely. Remote actuation may be from multiple locations. The valve shall be actuated by a distinct positive linear pull motion. An actuating motion requiring the operator to hold the lever at the tripped position or prior to the tripped position to effect actuation shall be prohibited.

b. The valves shall be actuated by a single acting mechanism.

c. The valves shall have a maximum closing time of 1 second.

d. The valves shall have an anti-slamming feature protecting the valve seating and internal components. This feature shall not prevent tight closure.

e. Valve design shall not require disconnecting the remote actuator(s) to reset the actuating mechanism.

f. The valve junction box shall be compatible with actuating assembly of 803-2145505.

g. The valves shall be reset to open by conventional valve motions, such as lifting of the stem by means of turning of a handwheel or pulling of a lever. Where the rotational motion to reset the valve requires initially turning the handwheel clockwise to engage a latch to permit subsequent counterclockwise action to open and reset the valve, the mechanism shall be rugged or protected.

h. The valves shall have a positive means of preventing any shaft penetrating the pressure boundary from being removed through the boundary during operating conditions.

i. The valves shall have a position indicator.

3.4.2 Size of handwheel. The valve handwheel shall be sized so that a tangential force of not more than the value specified in table II is required to be exerted on the rim of the handwheel to reset the valve against a differential pressure of 100 lb/in^2 (6.9 bar). The valve lever, where used instead of the handwheel, shall be so sized that the length is equal to the diameter of handwheels in table II, and the force does not exceed the force required for the handwheel. The maximum allowable operator-applied tangential force to open and operate the valve shall not exceed 40 pounds-force (lbf) (178 newtons [N]).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

TABLE II. Maximum allowable tangential force to seat valve based on valve handwheel size.

Handwheel diameter, inches (millimeters)	Maximum allowable tangential seating force, lbf (N)
2 (50) and below	90 (400)
3 (75)	98 (436)
4 (100)	106 (472)
5 (125)	112 (498)
6 (150)	118 (525)
7 (175)	121 (538)
8 (200)	124 (552)
9 (225)	127 (556)
10 (250)	130 (578)
11 (275)	133 (592)
12 (300)	135 (601)
14 (350)	138 (614)
16 (400)	141 (627)
18 (450)	144 (641)
21 (525)	147 (654)
24 (600)	150 (667)
27 (675)	150 (667)
30 (750)	150 (667)
36 (900)	150 (667)

3.4.3 Type I. Type IA and IB valves shall have the following additional design features:

a. The valve shall have face-to-face and center-to-face dimensions in accordance with ASME B16.10, class 600 globe valves. Flanges shall be in accordance with ASME B16.5, class 600.

b. Type IA valves shall employ bonnet gaskets in accordance with MIL-DTL-24716, type I. Type IB valves may use commercial seals.

3.4.4 Type II. Type II valves shall have flanges in accordance with MIL-PRF-20042, class 150. The valves shall have face-to-face and center-to-face dimensions in accordance with 803-1385541.

3.5 Shock and vibration. All valves and actuators under this specification shall withstand the requirements of grade A, class I, type C shock in accordance with MIL-DTL-901 and MIL-STD-798 and shall withstand the requirements of type I vibration in accordance with MIL-STD-167-1.

3.6 Structural soundness. Valves shall withstand an internal hydrostatic test at the pressure specified in 3.6.1 or 3.6.2, as applicable, in the open position for 5 minutes with no external leakage, weeping, or structural distortion (see 4.6.4).

3.6.1 Type I. Type IA and IB valves shall withstand the hydrostatic shell test pressures in accordance with ASME B16.34.

3.6.2 Type II. Type II valves shall withstand hydrostatic shell test pressures of 225 lb/in^2 (15.5 bar).

3.7 Line pressure. The valve shall open against a line pressure of 600 lb/in^2 (41 bar) fuel or steam for type IA and IB valves and 150 lb/in^2 (10.3 bar) for type II valves without the aid of an external equalizing bypass.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

3.8 Welding. Welding shall be in accordance with S9074-AR-GIB-010/278. Other welding techniques shall not be used unless specifically accepted by the Technical Authority (see 6.5).

3.9 Threads. Pipe plugs and mating threads or threaded components, where used, shall have straight machined threads.

3.10 Impregnation. Impregnation, where required, shall be in accordance with S9074-AR-GIB-010/278.

3.11 Operating styles. The valve shall be capable of operating for a minimum of 1,000 trip-reset cycles without the replacement of parts or adjustments.

3.12 Seat leakage and pressure drop. The valve shall have a maximum initial seat leakage of 10 cubic centimeters per hour (cm^3/h) per inch of NPS for a valve of NPS 1 and larger, and 10 cm^3/h total for a valve of less than NPS 1. The pressure drop through the valve shall be a maximum of 0.5 lb/in^2 (0.03 bar) at the rated flow condition.

3.13 Marking.

3.13.1 Body marking. The valve body shall be marked with a flow direction indicator, the pressure rating, and the manufacturer's name or trademark etched, stamped, or cast integral with the body.

3.13.2 Identification plates. The valve shall have an identification plate made of corrosion-resistant steel, anodized aluminum, or brass. The identification plate shall be permanently fastened to a part of the valve not subjected to the working pressure or to the edge of a flange. The identification plate shall include the following information:

a. Manufacturer's name or trademark
b. Size of valve and rating
c. Body and bonnet or cover composition
d. Manufacturer's identification number
e. Specification: "MIL-DTL-24569"
f. Allowance parts list (APL) number, if known

3.13.3 Resetting instructions. Where the valve design requires initial counterclockwise rotational motion to reset the valve, the resetting instructions shall be forged or cast into the handwheel or shall have an instruction plate permanently attached to the valve.

3.14 Maintainability and special tools. Installation and maintenance of valves shall be accomplished with standard tools. The actuating mechanism shall be sufficiently strong so that valves will not be damaged or require maintenance from improper turning of the handwheel. Special tools shall not be required to install or service the valve. Special tools are defined as those tools not listed in the GSA Global Supply Catalog.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. First article inspection shall be performed on one valve of each type and size when a first article sample is required (see 3.1). This inspection shall include the examination of 4.5 and the tests of 4.6.1 through 4.6.6.

4.3 Conformance inspection. Every valve offered to the Government shall be tested in accordance with 4.6.4. Conformance inspection shall include the examinations and tests specified in table III. Conformance inspection samples shall be selected from each lot in accordance with 4.4 or as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

TABLE III. Examination and tests.

Inspection	Requirement	First article inspection	Conformance inspection
Visual and dimensional examination	3.4, 3.4.1, 3.4.2, 3.4.3, 3.4.4, 3.8, 3.9, 3.10, 3.13, 3.14	4.5.1	4.5.1
Materials	3.3, 3.3.1	4.5.2	-
Operation	3.7, 3.11	4.6.1	4.6.1.1
Shock	3.5	4.6.2	-
Vibration	3.5	4.6.3	-
Hydrostatic	3.6	4.6.4	4.6.4
Seat leakage	3.12	4.6.5, 4.6.6	-

4.4 Sampling.

4.4.1 Sampling for examinations and tests. A random sample of valves shall be selected from each lot offered to the Government in accordance with ANSI/ASQ Z1.4 at inspection level II and the Acceptance Quality Limit (AQL) specified (see 6.2).

4.4.2 Lot. A lot shall consist of all valves of the same type and size produced under the same conditions and offered for delivery at one time, as specified. A sample valve shall consist of one completely assembled quick-closing shutdown valve with tripping actuator installed.

4.5 Examination.

4.5.1 Visual and dimensional examination. Sample valves shall be visually examined to verify compliance with the non-operational requirements of this specification. Each of the sample valves selected shall be examined in accordance with table III and table IV. Any valve in the sample containing one or more major defects shall be rejected, and if the number of defective valves in any sample exceeds the acceptable number for that sample, the lot represented by the sample shall be rejected. Minor defects shall be corrected before the lot is inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of defects.

Categories	Defects
Major defects	
	Design and Construction:
101	Not design specified
102	Not material specified
103	Component missing or damaged
104	Not assembled correctly
	Workmanship:
105	Poor assembly
106	Bonnet not properly aligned
107	Welding not in accordance with S9074-AR-GIB-010/278
108	Poor finish on machining
Minor defects	
	Identification and Marking:
201	Improper, missing, or illegible

4.5.2 Examination of materials. Materials used in the manufacture of valves shall be examined to determine conformance to 3.3.

4.6 Tests.

4.6.1 Operational cycle test. The valve shall be cycled 1,000 times from full open to full closed by tripping and resetting. During the test, the mechanisms shall not be adjusted or parts replaced. The valve shall be pressurized during each cycle at 600 lb/in^2 (41 bar) for type IA and IB valves and 150 lb/in^2 (10.3 bar) for type II valves.

4.6.1.1 Conformance inspection operational cycle test. Sample valves for conformance inspection shall be cycled from full open to full closed by tripping and resetting.

4.6.2 Shock. The valve and actuating assembly shall be shock tested in accordance with the grade A shock test of MIL-DTL-901. Valves shall be pressurized during each blow at 600 lb/in^2 (41 bar) for type IA and IB valves and 150 lb/in^2 (10.3 bar) for type II valves. Valve tripping, permanent deformation, misalignment, or functional impairments shall be cause for rejection.

4.6.3 Vibration. The valve shall be subjected to the type I vibration test in accordance with MIL-STD-167-1. In addition to the criteria therein, valve tripping due to vibration shall be cause for rejection.

4.6.4 Hydrostatic shell test. The valve shall be subjected to the pressure specified in 3.6.1 and 3.6.2 for a minimum duration of 5 minutes. The fluid temperature shall not exceed 100 °F (38 °C). Any weeping, leakage, or permanent deformation shall be cause for rejection. The valve shall be open and shall not be back-seated. Slight leakage past the packing of stuffing boxes shall not be cause for rejection.

4.6.5 Seat tests (tightness). The valve shall be pressurized from the side tending to close the valve. The valve shall be examined for seat tightness. The test pressure shall be 600 lb/in^2 (41 bar) for type IA and IB valves and 150 lb/in^2 (10.3 bar) for type II valves. The testing medium shall be clean tap water with no additive other than mineral cutting oil at temperatures not more than 100 °F (38 °C). The duration of the test shall be a minimum of 1 minute. There shall be no visible signs of leakage. Should there be any visible leakage, this test shall be continued for the length of time required to accurately determine the rate of leakage. Leakage shall not exceed 10 cm^3/h per inch of NPS. For valves less than 1 inch in size, the leakage rate shall be not more than 10 cm^3/h.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

4.6.6 First article completion test. Upon completion of the operational cycle tests, the valve shall be repressurized in accordance with 4.6.4 to ensure continued integrity of the assembly and shall be tested for seat tightness in accordance with 4.6.5 to determine any change in leakage rate from testing. Failing the leakage criteria of 4.6.5 shall be cause for rejection.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Valves covered by this specification are intended for steam and oil service (see 1.2.1) on naval ships and must withstand shock conditions. Current stock of quick-closing shutdown valves may be used until depleted; future requisitions for quick-closing shutdown valves should refer to the current version of this specification.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Type and size of valve required (see 1.2).

c. Quantity required.

d. Service condition (steam or fuel).

e. When first article inspection is required (see 3.1).

f. Requirements for selecting conformance inspection samples if other than as specified in 4.4 (see 4.3).

g. AQL of 1.0 (see 4.4.1).

h. Packaging requirements (see 5.1).

i. Documentation, if required (see 6.4).

6.3 First article inspection. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection as to those bidders offering a product which has been previously procured or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending procurement.

6.4 Recommended documentation. The following list of documentation is recommended to be requested as part of the acquisition of any new valve under this specification (see 6.2).

6.4.1 Technical manuals. If required, technical manuals in accordance with MIL-DTL-24784 should be requested.

6.4.2 Drawings. If required, drawings should contain the following content:

a. Accurately scaled sectional assembly that clearly depicts the design and construction of the valve.

b. Bill of material listing specification, grade, condition, and any other data required to fully identify the properties of the materials proposed.

c. Details of the seat, disc, stem assembly, and all other replaceable internal trim.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.

d. Layout of the pressure-containing envelope (body, bonnet, and bottom cap) giving dimensions that control compression of the spiral-wound gaskets. This is to ensure that where remachining is necessary to repair the gasket-sealing surfaces on these parts, compensating cuts can be accurately made to restore original gasket compression. This layout should also specify the dimensional limits of such corrective remachining within which function of the valve remains unaffected.

e. Recommended assembly torques or equivalent procedures for making up all joints and threaded assemblies.

f. Tabulation of required gasket characteristics including all dimensions (with tolerances) and load versus compression characteristics (with tolerances).

6.5 Technical Authority. The Technical Authority has the authority, responsibility, and accountability to establish, monitor, and approve technical standards, tools, and processes in conformance to higher authority policy, requirements, architectures, and standards. NAVSEA 05S may be contacted to determine the appropriate Technical Authority for any given requirement related to equipment and systems of U.S. Navy ships and submarines.

6.6 Subject term (key word) listing.

Actuator

Remote

Trip

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Preparing activity:
Navy – SH
(Project 4820-2020-015)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:02Z
Check the source to verify that this is the current version before use.