MIL-C-45443B (MU)
15 May 1964
SUPERSEDING
MIL-C-45443A (Ord)
6 September 1961

MILITARY SPECIFICATION

CARTRIDGE, 76MM, TP-T, M340A1E1
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling, and packing for one type of cartridge designated as Cartridge, 76MM, TP-T, M340A1E1, for use in 76MM Guns, M32 and M48.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons; General Specification for.
MIL-I-45208	-	Inspection Requirements, General Specification for.
MIL-I-45607	-	Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and Definitions.
MIL-STD-414	-	Sampling Procedures and Tables for Inspection by Variables for Percent Defective.
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ORDNANCE CORPS

8886611	-	Cartridge, 76MM, TP-T, M340A1E1, Assembly and Marking Diagram.
7548613	-	Container, Ammunition, Fiber, M264, for Cartridge 76MM AP-T M339 or TP-T M340A1 for Guns M32 and M48.
7548614	-	Box, Packing, Ammunition, for 76MM Gun Ammunition in Fiber Container M264, Assembly Details and Packing.
8796521	-	Marking and Sealing for Ammunition Fiber Containers.
8796522	-	Marking Diagram and Sealing for Wooden Packing Boxes.

FSC:1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:00Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

IEL-8886611 - Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.- Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Complete round.- The cartridge shall comply with all requirements specified on Drawing (dwg.) 8886611 and with all requirements specified in applicable specifications.

3.3 Propellant weight.- The weight of propellant shall not differ by more than plus or minus 0.25 ounce avoirdupois from that designated by the loading authorization for the particular lot of propellant used.

3.4 Proving ground.- The cartridge shall comply with the following requirements when tested as specified in 4.3.2.

3.4.1 Muzzle Velocity.- The corrected muzzle velocity of the cartridge when tested at ambient temperature shall not be more than 3250 feet per second (f.p.s) nor less than 3150 f.p.s and the standard deviation of the lot shall not exceed 6.5 f.p.s.

3.4.2 Tracer functioning.- The tracer shall ignite and there shall be visible evidence of burning of the tracer composition to the 1000 meter target.

3.4.3 Security of parts.- There shall be no evidence of metal parts failure in the gun bore or in flight.

3.5 Workmanship. The cartridge and all components shall be free from chips, dirt, grease, rust, burrs, cracks, and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The cartridge shall not be damaged in any manner during the loading operation. The painting and marking shall be restored by the loading and assembling contractor on any components furnished him when such painting and marking has been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.- Suppliers responsibility will be as specified in the contract or purchase order. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Contractor quality assurance system.- The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL-I-45208. The contractor's quality assurance system shall contain a procedure for the reporting of critical defectives found during the coarse of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be reported within 48 hours. A monthly summary report covering those critical

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:00Z
Check the source to verify that this is the current version before use.

defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.7. The reports shall contain, as a minimum, the following information:

a. Contractor and contract number.
b. Number and revision date of specification.
c. Characteristic code number.
d. Lot or serial number.
e. Number of defectives found.
f. Assignable cause or analysis of occurrence.
g. Corrective action taken or recommended. When the corrective action is beyond the control of the contractor or the scope of the contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 Submission of product.- At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
b. Number of units of product inspected.
c. Results obtained for all inspection performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of analysis on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.- Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "Critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 Lot formation.- A lot shall consist of cartridges produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, or fit, as determined by the Government shall not necessitate changing the lot number. Product shall be submitted in accordance with MIL-STD-105 (or MIL-STD-1235, when applicable). Each lot shall contain:

a. Cartridge cases from not more than one lot of resized cases, or,
b. Cartridge cases of new manfacture of one interfix lot number from one manufacturer.
c. Projectiles of one lot interfix number from one manufacturer.
d. Loaded tracers of one lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:00Z
Check the source to verify that this is the current version before use.

e. Loaded primers of one lot interfix number from one manufacturer.
f. Propellant from not more than one lot.

4.2.2 Examination.- Inspection for critical defects shall be 100 percent. Sampling plans and procedures for Major or Minor defects shall be in accordance with Standard MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to to individual characteristics listed using an AQL of 0.40 percent for each minor defect and an AQL of 0.25 percent for each major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Primer, prior to assembly to cartridge case (see dwg. 8838153 covering a detail of dwg. 8886611)

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:			
1.	Any flash hole missing	Visual	01001*
Major:	None defined.		
Minor:	None defined.		

4.2.2.2 Projectile prior to assembly to cartridge case (see dwg. 8886611)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Tracer plug fails to withstand disassembly torque	Test	02001
102.	Tracer closing disc damaged	Visual	02002
103.	Sealing compound missing from rotating band	Visual	02003
Minor:	AQL 1.0 percent		
201.	Incorrect color code	Visual	02004
202.	Evidence of poor workmanship (see 3.5)	Visual	02005

4.2.2.3 Liner, prior to assembly with cartridge case (see dwg. 8886818 and dwg. 8886819 covering a detail of dwg. 8886611)

Categories	Defects	Method of Inspection	Code No
Critical:	None defined.		
Major:	AQL 0.25 percent		
101.	Adhesive not tacky	Manual	03001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:00Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.5 percent		
201.	Excessive amount of uncoated surface	Visual	03002
Categories	Defects	Method of Inspection	Code No
202.	Length	Gage	03003
203.	Length of slits	Gage	03004
204.	Evidence of poor workmanship (see 3.5)	Gage	03005

4.2.2.4 Cartridge case and liner assembly (see dwg. 8886818 covering a detail of dwg. 8886612).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.0 percent		
201.	Depth of liner from mouth of case	Gage	04001
202.	Evidence of poor workmanship (see 3.5)	Visual	04002

4.2.2.5 Cartridge case and liner, prior to loading propellant (see dwg. 8886611).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.25 percent		
101.	Primer fails to withstand disassembly torque	Torque-test	05001
102.	Exposed liner adhesive tacky	Manual	05002
Minor:	AQL 0.40 percent		
201.	Foreign matter in interior of case	Visual	05003

4.2.2.6 Cartridge case, prior to inserting projectile (see dwg. 8886611).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.25 percent		
101.	Liner flaps not folded	Visual	06001
Minor:	None defined		

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:00Z
Check the source to verify that this is the current version before use.

4.2.2.7 Cartridge (see dwg. 8886611).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer above flush	Gage	07001*
Major:	AQL 0.25 percent		
101.	Total length, max	Gage	07002
102.	Diameter of bourrelet after retouching, max	Gage	07003
Minor:	AQL 1.5 percent		
201.	Exterior coating with an aggregate of bare spots in excess of 1/4 square inch	Visual	07004
202.	Marking misleading or unidentifiable including incorrect color code	Visual	07005
203.	Evidence or poor workmanship (see 3.5)	Visual	07006

4.2.2.8 Unsealed fiber container (see dwg. 7548613)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.25 percent		
101.	Packing components missing	Visual	08001
Minor:	AQL 1.5 percent		
201.	Cartridge not removable by hand	Manual	08002
202.	Container cap not removable by hand	Manual	08003
203.	Glue or asphalt on cartridge	Visual	08004
204.	Evidence of poor workmanship (see 3.5)	Visual	08005

4.2.2.9 Sealed fiber container (see dwg. 7548613)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Sealing strip incomplete or badly wrinkled	Visual	09001
102.	Container cut or damaged through all impregnated layers	Visual-Manual	09002
103.	Metal end loose or distorted	Visual-Manual	09003

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:00Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Minor:	AQL 2.5 percent		
201.	Sealing strip tab length, min	Gage	09004
202.	Marking misleading or unidentifiable	Visual	09005
203.	Cuts, scuffs or gouges in outer layer	Visual	09006
204.	Connector loose	Manual	09007
205.	Color of tape incorrect	Visual	09008

4.2.2.10 Sealed wood packing box (see dwg. 7548614)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Box damaged exposing contents	Visual-Manual	10001
102.	Strapping missing, broken or loose	Visual-Manual	10002
103.	Hardware missing, broken or loose	Visual-Manual	10003
104.	Boards loose, broken or nails protruding	Visual-Manual	10004
105.	DOD symbol missing or incorrect	Visual	10005
Minor:	AQL 2.5 percent		
201.	Car seal missing, unsealed or improperly positioned	Visual	10006
202.	Marking misleading or unidentifiable	Visual	10007
203.	Hardware improperly engaged	Visual-Manual	10008
204.	Strapping improperly assembled	Visual-Manual	10009
205.	Handle missing or insecure	Visual-Manual	10010

4.2.3 Testing

4.2.3.1 Check test for deterioration of primers (see applicable specification) - Major defect. - (Code No. 01003).- If the total time between original acceptance of any primer lot and the assembly of that lot into the complete round exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to, and must satisfactorily pass the check test specified in the applicable loading specification immediately before the primer lot is assembled into the cartridges. The test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the cartridges (see 6.4).

4.2.3.2 Propellant weight (see 3.3) - Critical defect) - (Code No. 07007).- The propellant for each charge shall be weighed and check-weighed 100 percent. The check weighing shall be accomplished independently of the original weighing, using a different balance from that used to conduct the original weighing and, if performed manually, shall be performed by another operator. Any charge which fails to comply with the applicable requirement shall be classed defective and shall be returned to the original weighing station for correction. Equipment shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:00Z
Check the source to verify that this is the current version before use.

4.2.3.3 Bullet pull (see dwg. 8886611) - Major defect - (Code No. 07008).- The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Part II, Table B-3, Code letter F and AQL of 1.5 percent. The test shall be performed as specified in 4.3.1 with equipment in accordance with 4.2.4.

4.2.3.4 Profile and alignment (see dwg. 8886611) - Major defect - (Code No. 07009).- The cartridges shall be gaged 100 percent for profile and alignment. Any cartridge which fails to meet the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.5 Proving ground.- The following tests shall be performed as specified in 4.3.2.

4.2.3.5.1 Muzzle velocity (see 3.4.1) - Major defect - (Code No. 07010).

4.2.3.5.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan for this test shall be in accordance with Standard MIL-STD-414. Section B, part II, Table B3, Code letter I and an AQL of 1.0 percent shall be used. In addition, if the velocity standard deviation of the sample cartridges multiplied by the factor 0.75 exceeds the lot requirement, the lot shall be rejected.

4.2.3.5.1.2 After three consecutive lots have complied with the criteria of 4.2.3.5.1.1, the sampling plan for this test shall be in accordance with Standard MIL-STD-414. Section B, Part II, Table B3, Code letter F and an AQL of 1.0 percent shall be used. In addition, if the velocity standard deviation of the sample cartridges multiplied by the factor 0.65 exceeds the applicable lot requirement the lot shall be rejected.

4.2.3.5.2 Tracer functioning (see 3.4.2) - Major defect - (Code No. 07011).

4.2.3.5.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sample cartridges fired in the test for muzzle velocity (see 4.2.3.5.1.1) shall be observed for tracer functioning. If three or more of the samples fired fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.2.2 After three consecutive lots have complied with the criteria of 4.2.3.5.1.1, the sample cartridges fired in the test for muzzle velocity in 4.2.3.5.1.2 shall be observed for tracer functioning. If two or more sample cartridges fail to comply with the applicable requirement, the lot shall be rejected

4.2.3.5.3 Security of parts (see 3.4.3) - Major defect - (Code No. 07012).- The cartridges fired in the test for muzzle velocity shall be observed for compliance with the applicable requirement. Failure of any sample cartridge shall be cause for rejection of the lot.

4.2.3.5.4 Accuracy test (for information only) (see 4.3.2.1). The sample cartridges fired in the test for muzzle velocity and tracer functioning shall be observed for accuracy.

4.2.3.5.5 Refiring.- If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and performs a new test on additional rounds as required.

4.2.4 Inspection Equipment.- Index of Inspection Equipment Lists Number IEL-8886611 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:00Z
Check the source to verify that this is the current version before use.

4.2.4.1 Government rights to documentation.- Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement of parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and wherever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.- Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection and test equipment.- The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of it's accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures.

4.3.1 Bullet pull.- The security of the cartridge case to projectile crimp shall be determined by applying a load in the axial direction at the rate of 0.125 inch per minute using test equipment in accordance with 4.2.4.

4.3.2 Proving ground tests.- These tests shall be conducted at a Government proving ground in accordance with the applicable Ordnance Proof Manual and Acceptance Test Procedure. The sample cartridges shall be fired in a gun for which the cartridge is standard and observation made for conformance to all applicable requirements (see 6.5 and 6.6).

4.3.2.1 Accuracy test.- The cartridges shall be fired at a target placed 1000 meters from the muzzle of the gun. The hit pattern results shall be reported on the firing record for information purposes.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A.- The cartridge shall be preserved and packaged in accordance with dwg. 7548613 with marking and sealing in accordance with dwg. 8796521.

5.2 Packing

5.2.1 Level A.- The container shall be packed in accordance with dwg. 7548614 with marking and sealing in accordance with dwg. 8796522.

5.3 Data cards.- Data cards shall be prepared for each lot in accordance with the information specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data.- Procurement documents shall specify the following:
a. Title, number and date of this specification.

6.2 Inspection code number.- The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:00Z
Check the source to verify that this is the current version before use.

6.3 Inspection equipment.- The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of 6.3.1 through 6.3.7.

6.3.1 Inspection Equipment Lists.- Inspection Equipment Lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (00 Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "contractor design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 Inspection Equipment List codes.- The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5, and 6.3.6 will be designated in the Inspection Equipment List by the following codes:

CDOF	-	Contractor's design responsibility on Ordnance format; ORDM-608-12.
CDCF	-	Contractor's design responsibility on contractor format.
OD	-	Ordnance design.
ODMU	-	Ordnance design, mandatory for use.
CE	-	Commercial equipment.
SCD	-	Specification Control Drawing.

6.3.3 Ordnance designs.- Ordnance designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Ordnance design is listed for an item of inspection equipment. Ordnance designs fall into two basic classifications; mandatory and non-mandatory. When an Inspection Equipment List references mandatory Ordnance designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawings.- Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment.- Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and government. Contractors are not required to furnish drawings of commercial inspection equipment but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs.- Contractor designs are designs of inspection equipment for which

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:00Z
Check the source to verify that this is the currentversion before use.

the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDOF shall comply with the format and requirements of ORDM 608-12, and, in addition, contain the detail and information specified above.

6.3.7 Submission of contractor designs.- Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Cost of check test.- The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Combining of proving ground tests.- When the contractor for the cartridge is also the contractor for one or more of the components thereof, the proving ground tests of the components may be combined with the proving ground tests of the cartridge to save expense, upon agreement between the procuring activity and the contractor. In cases where the cartridge specification does not cover all of the proving ground tests specified for the component, the additional tests specified in the component specification shall be conducted.

6.6 Submission of firing and test data.- In addition to the normal distribution of records for each lot of cartridges, when the item is procured by the Department of the Army, copies should be sent to:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-ND2 (1 copy)
Dover, New Jersey SMUPA-DC8 (1 copy)

6.7 Submission of critical defect reports.- For U.S. Army Munitions Command procurements, one copy of each critical defect report will be furnished the cognizant Government inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN: SMUAP-RO; Picatinny Arsenal, ATTN: SMUPA-ND.

6.7.1 Reporting to other services.- For other than U.S. Army Munitions Command procurements, critical defect reporting shall be as prescribed by the Contracting Officer.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1315-A393

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:00Z
Check the source to verify that this is the current version before use.