MIL-F-45421D(AR)
AMENDMENT 5
3 April 1987
SUPERSEDING
AMENDMENT 4
15 September 1976

MILITARY SPECIFICATION

FIRING DEVICE, ELECTRICAL, M57
PARTS FOR, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-F-45421D(AR), dated 9 July 1973, and is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

* 4.3.2.1: Under Major defects 105 and 106 change:

"Concentricity" to "True position".

PAGE 8

* 4.3.2.2: Under Major defects 105 and 106 change:

"Concentricity" to "True position".

PAGE 20

4.3.3.5: Delete in its entirety and substitute as follows:

"4.3.3.5 Load Test of Top Plate and Housing Assembly (see Dwg 8837124) - Major Defect, Code No. 13006. - After the assemblies have passed the requirements of paragraph 4.3.2.13, twenty-five (25) assemblies shall be selected from each lot for test. The lot shall be rejected if any housing separates from the plate or if three (3) or more assemblies fail the height requirement of paragraph 4.3.2.13, Major Defect 101 after the load test. The test shall be performed as specified in 4.4.5 using test equipment in accordance with 4.3.4. (Non-Destructive Test)"

4.3.5: First sentence after "Classifiction of Defects", add "and with the approval of the Contracting Officer"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:57Z
Check the source to verify that this is the current version before use.

PAGE 22

4.3.5.2: Add major defect 107:

"107. Height from handle stop to pivot pin hole Gage 26009"

4.3.5.3: Add major defect 106:

"106. Height from handle stop to pivot pin hole Gage 27007"

PAGE 24

4.4.2: Delete 4th sentence and substitute as follows:

"Any item in which the boot is not in the expanded condition while under vacuum or is still collapsed after 5 minutes has elapsed from time of vacuum release, does not comply with 3.4 and shall be rejected".

4.4.5: Add paragraph 4.4.5 as follows:

"4.4.5 Load Test of Top Plate and Housing Assembly. With the assembly held securely, a dead load of not less than twenty-five (25) pounds shall be applied coaxially to the housing. Observation shall be made for compliance with the applicable requirements".

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A454)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:57Z
Check the source to verify that this is the current version before use.