INCH-POUND

MIL-F-45421D(AR)
AMENDMENT 6
29 JUNE 1990
SUPERSEDING
AMENDMENT 5
3 APRIL 1987

MILITARY SPECIFICATION

FIRING DEVICE, ELECTRICAL, M57
PARTS FOR, ASSEMBLING AND PACKING

This Amendment form a part of Military Specification MIL-F-45421D(PA), dated 9 July 1973, and is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 3.5.1a: Delete in its entirety and substitute with the following

"a. Mechanism does not actuate or generate energy exceeding 1 milliwatt-second (mWs) when handle is depressed with bail in safety (vertical slot) position.

PAGE 7

4.3.2.1: Under Major defects 105 and 106 change:

"Concentricity" to "True position".

PAGE 8

4.3.2.2: Under Major defects 105 and 106 change:

"Concentricity" to "True position".

PAGE 19

* 4.3.3.1.1, Table I: Change first "DEFECT" to read:

"Mechanism actuates or generates energy with bail in safe position (see 3.5.1a and 3.5.2)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:57Z
Check the source to verify that this is the current version before use.

4.3.3.5: Delete in its entirety and subsitute as follows:

"4.3.3.5 Load Test of Top Plate and Housing Assembly (see Dwg 8837124) - Major Defect, Code No. 13006. - After the assemblies have passed the requirements of paragraph 4.3.2.13, twenty-five(25) assemblies shall be selected from each lot for test. The lot shall be rejected if any housing separates from the plate or if three (3) or more assemblies fail the height requirement of paragraph 4.3.2.13, Major Defect 101 after the load test. The test shall be performed as specified in 4.4.5 using test equipment in accordance with 4.3.4 (Non-Destructive Test)"

4.3.5: First sentence after "Classifiction of Defects", add "and with the approval of the Contracting Officer".

PAGE 22

4.3.5.2: Add major defect 107:

"107. Height from handle stop to pivot pin hole Gage 26009"

4.3.5.3: Add major defect 106:

"106. Height from handle stop to pivot pin hole Gage 27007.

PAGE 24

4.4.2: Delete 4th sentence and substitute as follows:

"Any item in which the boot is not in the expanded condition while under vacuum or is still collapsed after 5 minutes has elapsed from time of vacuum release, does not comply with 3.4 and shall be rejected".

* 4.4.3: Delete the following:

"Observe that bail prevents handle from being fully depressed and mechanism does not actuate (3.5.1a)."

And replace with:

"Observe that bail prevents handle from being fully depressed, mechanism does not actuate and generated energy is in compliance with 3.5.1a."

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:57Z
Check the source to verify that this is the current version before use.

4.4.5: Add paragraph 4.4.5 as follows:

"4.4.5 Load Test of Top Plate and Housing Assembly. With the assembly held securely, a dead load of not less than twenty-five(25) pounds shall be applied coaxially to the housing. Observation shall be made for compliance with the applicable requirements".

PAGE 26

* 5.3: Change second sentence to read:

"In addition, each unit and exterior box shall have special caution labels applied in accordance with applicable paragraphs of MIL-STD-129, latest revision, referencing magnetic materials."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A584)

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:57Z
Check the source to verify that this is the currentversion before use.