MILITARY SPECIFICATION

FUZE, MINE, AT, M607, LOADING, ASSEMBLING AND PACKING

This Specification is approved for use within the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the loading and assembling of Fuze, Mine, AT; M607.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-2550 - General Specification for Ammunition Except Small Arms Ammunition.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Research, Development and Engineering Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

MIL-A-48078- Ammunition, Standard Quality Assurance Provisions, General Specification for

MIL-D-70603- Detonator, Stab, PA523, Loading, Assembling and Packing

STANDARDS

MILITARY

MIL-STD-105- Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109- Quality Assurance Terms and Definitions.

MIL-STD-331- Fuze and Fuze Components, Environmental and Performance Tests For

MIL-STD-1235- Continuous Sampling Procedures and Table for Inspection by Attributes.

(Copies of specifications, standards, drawings, publications, and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

8833783 - Fuze, Mine, Anti-Tank, M607, Loaded Assembly.

8836108 - Carton, Packing, Ammunition, Loaded Assembly, for Fuze, Mine, AT, M607.

8836107 - Box, Packing, Ammunition, Loaded Assembly for Fuze, Mine, AT, M607.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Fuzes. The fuzes shall comply with all requirements specified on Drawing (dwg.) 8833783, and with all requirements specified in applicable specifications.

3.3 Jolt and jumble. The loaded fuzes shall withstand the jolt test specified in Standard MIL-STD-331. After completion of the jolt test, the same fuzes shall withstand the jumble test specified in Standard MIL-STD-331, when tested as specified in 4.5.2.

3.4 Static functioning. The fuzes shall function satisfactorily as evidenced by the shattering of the cap thread when tested as specified in 4.5.3.

3.5 Torque on closure assembly. The closure assembly shall show no evidence of looseness when a torque of 30 to 35 inch pounds is applied as specified in 4.5.1.

3.6 Xray of loaded fuze assembly. All loaded fuze assemblies without tilt rod extension shall be xrayed in accordance with 4.5.4.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of cracks, gouges, burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly, nor shall they be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing shall be dry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of specification MIL-A-2550 shall apply.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantities
Assembly prior to staking detonator	8833784	50
Assembly prior to staking retainer	8833783	50
Assembly prior to assembly of closure assembly	8833783	50
Loading assembly	8833783	50

The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3. Unless otherwise directed by the Contracting Officer, loaded components shall not be submitted to a Proving Ground for any test until the above assemblies submitted in accordance with this paragraph have been accepted.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-45429C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Fuze, Mine, AT, M607				See below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Assembly prior to staking detonator (Dwg. 8833783)				
	Examination for defects	50		3.2	4.4.2.1
	Assembly prior to staking retainer (Dwg. 8833783)				
	Examination for defects	50		3.2	4.4.2.2
	Assembly prior to assembly of closure assembly (Dwg. 8833783)				
	Examination for defects	50		3.2	4.4.2.3
	Loading assembly (Dwg. 8833783)				
	Examination for defects	50		3.2	4.4.2.4
	Jolt and jumble	50-0-1		3.3	4.5.2
	Static functioning	50-1-2		3.4	4.5.3
	Xray	50-0-1		3.6	4.5.4

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.3.3 Rejection. See MIL-A-48078. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.1.1 Cavity identification (plastic and cast parts). The contractor shall maintain an approved cavity identification system. Components shall be grouped and identified until all inspections have been completed.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45429C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Fuze, Mine, AT, M607 Loading assembly, prior to staking detonator				8833784 NEXT HIGHER ASSEMBLY 8833783
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Firing pin in detonator cavity		100%	3.2	Visual
2	Height to firing pin		100%	3.2	Gage
Major					
101	Firing pin not visible through detonator well opening		100%	3.2	Visual
Minor					
201	Workmanship		.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45429C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Fuze, Mine, AT, M607 Loading assembly prior to staking retainer	1 OF 1	8833783
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Detonator damaged exposing explosive		100%	3.2	Visual
Major					
101	Detonator inverted		100%	3.2	Visual
Minor					
201	Workmanship		0.65%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45429C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Fuze, Mine, AT, M607 Loading assembly prior to assembly of closure assembly				8833783 NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Retainer stake missing		100%	3.2	Visual
2	Detonator secure after staking		100%	3.2	Manual
Major	None defined				
Minor					
201	Gasket damaged		0.65%	3.2	Visual
202	Workmanship		0.65%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45429C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.4	Fuze, Mine, AT, M607 Loading assembly	1	1	8833783
				NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Boxed end pin missing		100%	3.2	Visual
2	Xray		100%	3.6	4.5.4
3	Jolt and jumble	12-0-1	(1)	3.3	4.5.2
Major					
101	Closure assembly turns when min. torque is applied in tightening direction		.40%	3.5	4.5.1
102	Assembly damaged (dented, deformed, cracked, or punctured		.40%	3.2	Visual
103	Jolt and jumble	12-0-1	(1)	3.3	4.5.2
104	Static functioning		.40%	3.4	4.5.3
Minor					
201	Protective coating damaged (other than light scratches)		0.65%	3.2	Visual
202	Marking misleading or unidentifable		0.65%	3.2	Visual
203	Poor workmanship		0.65%	3.8	Visual

NOTES: (1) Samples which have detonator firing during tests shall be classed as critical defects. Samples which fail for cause other than detonator firing shall be classed as major defects.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45429C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Carton, packing, sealed				8836108
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Carton damaged so that contents are exposed or liable to become exposed		0.40%	3.2	Visual
102	Flaps not secured with adhesive		0.40%	3.2	Visual
103	Sealing strip incomplete, badly wrinkled, or not in contact with surface for at least 1/2 inch around entire carton		0.40%	3.2	Visual
Minor					
201	Contents loose upon shaking		0.65%	3.2	Manual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45429C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Box, packing, sealed wooden				8836107
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Hardware missing, broken or loose		0.40%	3.2	Visual/Manual
102	Strapping missing, broken or loose		0.40%	3.2	Visual/manual
103	Box damaged so that contents are, exposed or liable to become exposed		0.40%	3.2	Visual
104	DOD symbol misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Hardware improperly engaged		0.65%	3.2	Visual/Manual
202	Car seal missing, unsealed or improperly positioned		0.65%	3.2	Visual/Manual
203	Contents loose when box is tilted		0.65%	3.2	Visual/Manual
204	Strapping improperly assembled.		0.65%	3.2	Visual/Manual
205	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Check test for deterioration of detonators (see Specification MIL-D-70603. If the total time between original acceptance of any detonator lot and assembly of that lot into the mine fuze exceeds two years, or if the detonators have been subjected tc adverse conditions, however brief, at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in Specification MIL-D-70603 immediately before the lot is assembled into the fuzes. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling the detonators into the fuzes. The test shall be conducted at Government expense, without cost to the contractor who loaded the detonator, or to the contractor assembling the detonators into the fuzes, and shall not constitute a basis of rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the lot was under jurisdiction of either contractor.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in Classified of Defects and Tests forms beginning with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Torque on closure assembly. The specified torque shall be applied to the closure assembly, in a tightening direction, using a torque wrench that is capable of exerting the min. force specified on the applicable drawing. Observation shall be made for any evidence of loosening of the closure assembly.

4.5.2 Jolt and jumble. The fuze shall be assembled to a specified fixture and subjected to the jolt test as specified in Standard MIL-STD-331. The same fuzes shall then be removed from the jolt fixture and assembled into a specified protective adapter and then subjected to the jumble test as specified in Standard MIL-STD-331. Upon completion of the jolt and jumble tests, the fuzes shall then be examined for detonator firing, unseating of the detonator or other listed defects by removing the pull ring assembly, band and stop.

4.5.3 Static functioning. The closure assembly, the boxed end pin and the band and stop shall be removed from the fuzes. A vertical load shall be applied to the pressure ring of the fuze until functioning occurs. Observation shall be made for satisfactory functioning as specified in 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.5.4 X-ray of loaded fuze assembly. The entire production of loaded fuze assemblies less tilt rod extension shall be xrayed to confirm proper clearance between tilt rod and firing pin spring assembly, presence of tilt rod groove pin and firing pin spring assembly groove pin, and to assure firing pin spring assembly is in the correct position for firing.

5. PACKAGING

5.1 Preservation - packaging.

5.1.1 Level C. Fuze, Mine, M607, (dwg. 8833783), shall be packaged as specified in 5.2.1.

5.2 Packing.

5.2.1 Level C. One hundred (100) Fuze, Mine, M607 (dwg. 8833783), shall be packed in accordance with dwgs. 8836107 and 8836108.

5.3 Marking. Marking shall be in accordance with dwg. 8836107.

5.4 Data cards. Data card information shall be as specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U S ARDEC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.3 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M, Dover, New Jersey 07801-5001.

6.4 Drawings. Drawings listed in section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.6 Subject term (key word) listing.

Fuze, Mine, AT
Loaded Assembly
Static Functioning
Closure Assembly

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A163)

U.S. GOVERNMENT PRINTING OFFICE: 1986 - 605-036/45227

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
U S ARMY ARMAMENT RSCH DEV & ENGR CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-45429C (AR)	FUZE, MINE, AT, M607, LOADING ASSEMBLING AND PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.