MIL-F-45430C(AR)
6 June 1986
SUPERSEDING
MIL-F-45430B(MU)
30 April 1965

MILITARY SPECIFICATION

FUZE, MINE, AT: M607, PARTS FOR

This Specification is approved for use within the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the parts for Fuze, Mine, AT: M607.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-L-201- Lead Sheet.

MILITARY

MIL-A-2550 - General Specification for Ammunition Except Small Arms Ammunition.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Research, Development and Engineering Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

MIL-I-45607 - Inspection Equipment, Supply and Maintenance of.
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes. (ABC-STD-105)
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For
MIL-STD-1169- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1235- Continuous Sampling Procedures and Table for Inspection by Attributes.

(Copies of specifications, standards, drawings, publications, and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

8833784 - Fuze, Mine, AT, M607, Body Assembly.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:58Z
Check the source to verify that this is the current version before use.

3.2 Parts. All parts shall comply with drawings, specifications and standards.

3.3 Metal parts assembly. The metal parts assembly shall comply with all requirements specified on Drawing (Dwg.) 8833783, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Air pressure. The fuze assembly shall withstand in air pressure of 5 pounds per square inch gage (p.s.i.g.), min. for a period of 10 seconds (secs), min, when tested as specified in 4.5.1.

3.5 Horizontal load. The fuze assemblies shall not function when subjected to horizontal load of 3.74 pounds or less, and shall function when subjected to a horizontal load greater than 3.74 pounds and not more than 6.75 pounds when tested as specified in 4.5.4.

3.6 Penetration of firing pin point. The firing pin point shall penetrate a lead cylinder to a depth of 0.40 inch minimum (min.). The eccentricity as measured between the center of penetration and the center of the lead cylinder shall not exceed .030 inch when tested as specified in 4.5.5.

3.7 Jolt test. The fuze metal parts assemblies shall withstand the jolt test specified in MIL-STD-331 when tested as specified in 4.5.6.

3.8 Reversed height test. The Belleville springs shall have a reversed height of 0.145 + 0.015 inch and will require a load of 20 to 27 pounds to snap it back to a height of 0.155 inch min., with length travel during snap back 0.085 + 0.025 inches as specified in 4.5.2.

3.9 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.10 Workmanship. All parts and assemblies shall be fabricated and assembled in thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

sharply defined. External threads shall be full, complete and undamaged for their entire length. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantities
Retainer	8835001	50
PA523, Detonator, Stab	9358084	50
Pin, Boxed End	12561279	50
Band	8833786	50
Body	8833787	50
Cap	8833788	50
Gasket	8834998	50
Closure	8833790	50
Fork	8834997	50
Closure Assembly	8833791	50
Ring, Pressure	8835002	50

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

Seal	8835007	50
Stop	8835008	50
Rod, Tilt	8835006	50
Rod, Extension	8835005	50
Collar	8833792	50
Cap, Bearing	8833789	50
Pin, Firing	8834999	50
Firing Pin Assembly	8833794	50
Firing Pin Spring Assembly	8833795	50
Spring, Belleville	8796159	50
Body Assembly	8833784	50

NOTES: (1) Those components produced from plastic molds or casting cavities shall have fifty (50) components from each mold or cavity submitted for this inspection. The contractor shall submit six sets each of bodies, caps, and pressure rings from each die which have been produced consecutively by the production process which the contractor will use in fulfilling the contract, to a Government-approved facility designated by the contracting officer. A set shall consist of all similar parts made in one complete operating cycle of the die casting machine. The sets shall consist of 3 sets of parts intact, attached to gates and runners (sprue), and 3 sets of parts after machining, and shall be identified by the number of the die that produced them. Individual parts in the set shall be identified by the cavity number in the die.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. See MIL-A-48078. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.4 Die requalification. At the conclusion of every 20 working days, or completion of every 200,000 cycles of the die casting machine, whichever comes first, the contract shall submit to a Government-approved facility designated by the contracting officer, three sets each of bodies, caps, and pressure rings from each die being used in production process in fulfilling the contract, and whenever a change occurs in the manufacturing process. A set shall consist of all similar parts made in one complete operating cycle of the die casting machine. These parts shall be submitted after machining, and shall be identified by the number of the die that produced them. Individual parts in the set shall be identified by the cavity number in the die. If the parts submitted are rejected, thus disqualifying the dies, the contractor may correct his dies and submit a new quantity of parts for acceptance. Only those parts produced by qualified dies shall be acceptable for production. Die requalification is considered a special test and parts expended shall not be considered as deliveries.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-45430C(AR)

PARAGRAPH	TITLE: Fuze, Mine, AT: M607		SHEET 1 OF 4		DRAWING NUMBER: See below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Retainer (Dwg. 8835001) Examination for Defects	50		3.2	4.4.2.1
	PA 523, Detonator, Stab (Dwg. 9358084) Examination for Defects	50		3.2	4.4.2.2
	Band (Dwg. 8833786) Examination for Defects	50		3.2	4.4.2.4
	Pin, Boxed End (Dwg. 12561279) Examination for Defects	50		3.2	4.4.2.3
	Body (Dwg. 8833787) Examination for Defects	50		3.2	4.4.2.5
	Cap (Dwg. 8833788) Examination for Defects	50		3.2	4.4.2.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
	Fuze, Mine, AT: M607				See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Gasket (Dwg. 8834998) Examination for defects	50		3.2	4.4.2.7
	Closure (Dwg. 8833790) Examination for Defects	50		3.2	4.4.2.8
	Fork (Dwg. 8834997) Examination for Defects	50		3.2	4.4.2.9
	Closure Assembly (Dwg. 8833791) Examination for Defects	50		3.2	4.4.2.10
	Ring, Pressure (Dwg. 8835002) Examination for Defects	50		3.2	4.4.2.11
	Seal (Dwg. 8835007) Examination for Defects	50		3.2	4.4.2.12

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-45430C(AR)

PARAGRAPH	TITLE: Fuze, Mine, AT: M607		SHEET 3 OF 4		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Stop (Dwg. 8835008) Examination for Defects	50		3.2	4.4.2.13
	Rod, Tilt (Dwg. 8835006) Examination for Defects	50		3.2	4.4.2.14
	Rod, Extension (Dwg. 8835005) Examination for Defects	50		3.2	4.4.2.15
	Collar (Dwg. 8833792) Examination for Defects	50		3.2	4.4.2.16
	Cap, Bearing (Dwg. 8833789) Examination for Defects	50		3.2	4.4.2.17
	Pin, Firing (Dwg. 8834999) Examination for Defects	50		3.2	4.4.2.18
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-45430C(AR)

PARAGRAPH	TITLE: Fuze, Mine, AT: M607		SHEET 4 OF 4		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Firing Pin Assembly (Dwg. 8833794)				
	Examination for Defects	50		3.2	4.4.2.19
	Firing Pin Spring Assembly (Dwg. 8833795)				
	Examination for Defects	50		3.2	4.4.2.20
	Spring, Belleville (Dwg. 8796159)				
	Examination for Defects	50		3.2	4.4.2.21
	Reversed height, load and travel to snap back, and free overall height test.	50		3.8	4.5.2
	Body Assembly (Dwg. 8833784)				
	Examination for Defects	50		3.2	4.4.2.24
	Air pressure test	50		3.4	4.5.1
	Axial load of collars test	50		3.3	4.5.3
	Horizontal load test	50		3.5	4.5.4
	Penetration of firing pin point test	50		3.6	4.5.5
	Jolt test	50		3.7	4.5.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:58Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.1.1 Cavity identification (Plastic and cast parts). The contractor shall maintain an approved cavity identification system. Components shall be grouped and identified until all inspections have been completed.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Retainer				8835001
					NEXT HIGHER ASSEMBLY 8833783
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
Minor 202	Workmanship		.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	PA523, Detonator, Stab				9358084
					NEXT HIGHER ASSEMBLY
					8833783
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Establishment of "H" prior to crimping		0.40%	3.2	Gage
103	Overall height after crimping and lacquering		0.40%	3.2	Gage
Minor					
201	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Pin, Boxed End		12561279
			NEXT HIGHER ASSEMBLY 8833784

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Presence of a gap between straight and bend ends of pin		100%	3.2	Visual
Major					
101	Inside length of rectangle formed by bending one leg of pin		0.40%	3.2	Gage
Minor					
201	Overall outside length		0.65%	3.2	Gage
202	Distance from center of loop to inside length of bent leg		0.65%	3.2	Gage
203	Proper form of pin		0.65%	3.2	Gage
204	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8833786
4.4.2.4	Band				NEXT HIGHER ASSEMBLY 8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Height of band		0.40%	3.2	Gage
102	Radius of band		0.40%	3.2	Gage
103	Diameter of pin hole		0.40%	3.2	Gage
Minor					
201	Location of pin hole		0.65%	3.2	Gage
202	Workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil-- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Body				8833787
					NEXT HIGHER ASSEMBLY 8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of bearing cap cavity, max.		0.40%	3.2	Gage
102	Distance from base to tilt rod seating shoulder		0.40%	3.2	Gage
103	Distance from base to bottom end of bearing cap cavity		0.40%	3.2	Gage
104	Distance from tilt rod seating shoulder to top face		0.40%	3.2	Gage
105	Angle of belleville spring mating face (See View A)		0.40%	3.2	Gage
106	Outside diameter of belleville spring mating face (See View A)		0.40%	3.2	Gage
107	Outside diameter of flange, max.		0.40%	3.2	Gage
108	Malformed or incomplete casting		0.40%	3.2	Visual
109	Cuts or scratches in bearing cap cavity		0.40%	3.2	Visual
Minor					
201	Finish improper		0.65%	3.2	Visual
202	Protective finish inadequate, damaged or improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 8833788
4.4.2.6	Cap				NEXT HIGHER ASSEMBLY 8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Diameter of detonator retaining lip (See View B)		100%	3.2	Gage
Major					
101	Distance from body seating, surface to lower corner of beveled side of retaining ring groove (See View C).		0.40%	3.2	Gage
102	Diameter of retaining ring groove		0.40%	3.2	Gage
103	Width of retaining ring groove, Max.		0.40%	3.2	Gage
104	Pitch diameter of thread		0.40%	3.2	Gage
105	Major diameter of thread		0.40%	3.2	Gage
106	Length of thread undercut, Max. (See View D)		0.40%	3.2	Gage
107	Distance from body seating surface to gasket seating surface, Max.		0.40%	3.2	Gage
108	Distance from body seating surface cavity to threaded end, Min.		0.40%	3.2	Gage
109	Distance from body seating surface to surface of internal boss		0.40%	3.2	Gage
110	Distance from body seating to far side of detonator retaining lip		0.40%	3.2	Gage
111	Inside diameter below retaining ring groove, Max.		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.6	Cap (Cont'd)				8833788
					NEXT HIGHER ASSEMBLY
					8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major cont'd					
112	Depth of belleville spring seat (See View C)		0.40%	3.2	Gage
113	Diameter of belleville spring seat (See View C)		0.40%	3.2	Gage
114	Angle of belleville spring mating face seat (See View E)		0.40%	3.2	Gage
115	Diameter of belleville spring mating face		0.40%	3.2	Gage
116	Concentricity of detonator cavity with pitch diameter of thread		0.40%	3.2	Gage
117	Concentricity of detonator hole with belleville spring seat		0.40%	3.2	Gage
118	Malformed or imcomplete casting		0.40%	3.2	Visual
119	Burrs on body mating face		0.40%	3.2	Visual
120	Burrs or ejector pin marks on outside diameter, inside diameter or seat of belleville spring cavity		0.40%	3.2	Visual
Minor					
201	Protective finish improper or inadequate		0.65%	3.2	Visual
202	Finish improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Gasket				8834998
					NEXT HIGHER ASSEMBLY
					8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8833790
4.4.2.8	Closure				NEXT HIGHER ASSEMBLY 8833791
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of thread, Max.		0.40%	3.2	Gage
102	Minor diameter of thread, Max.		0.40%	3.2	Gage
103	Depth to bottom of cavity		0.40%	3.2	Gage
104	Crack or deep cut		0.40%	3.2	Visual
Minor					
201	Workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Fork				8834997
					NEXT HIGHER ASSEMBLY
					8833791
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of drive screw hole		0.40%	3.2	Gage
102	Distance between prongs at base		0.40%	3.2	Gage
103	Overall height of fork		0.40%	3.2	Gage
104	Deep cut or groove		0.40%	3.2	Visual
Minor					
201	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Closure Assembly				8833791
					NEXT HIGHER ASSEMBLY 8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Distane from top of drive screw head to bottom inside closure		0.40%	3.3	Gage
Minor					
201	Workmanship		0.40%	3.10	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Ring, pressure				8835002
					NEXT HIGHER ASSEMBLY 8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Length of effective threads, min.		0.40%	3.2	Gage
102	Pitch diameter of thread		0.40%	3.2	Gage
103	Minor diameter of thread, max.		0.40%	3.2	Gage
104	Location of pin hole		0.40%	3.2	Gage
105	Diameter of pin hole		0.40%	3.2	Gage
106	Malformed or incomplete casting		0.40%	3.2	Visual
Minor					
201	Paint on surfaces of contact		0.65%	3.2	Visual
202	Protective finish inadequate, damaged, or improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Seal				8835007
					NEXT HIGHER ASSEMBLY
					8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Diameter of thru hole for tilt rod		0.40%	3.2	Gage
103	Overall height of seal		0.40%	3.2	Gage
Minor					
201	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Stop		8835008
			NEXT HIGHER ASSEMBLY
			8833784

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Height of stop		0.40%	3.2	Gage
102	Width of stop		0.40%	3.2	Gage
Minor					
201	Location of pin holes		0.65%	3.2	Gage
202	Radius of large curved surface		0.65%	3.2	Gage
203	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Rod, tilt		8835006
			NEXT HIGHER ASSEMBLY
			8833784

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of head, min.		0.40%	3.2	Gage
102	Height of head, min.		0.40%	3.2	Gage
103	Profile of head improper		0.40%	3.2	Gage
104	Location of pin hole, max.		0.40%	3.2	Gage
105	Diameter of pin hole		0.40%	3.2	Gage
106	Length from head at neck to rod end, min.		0.40%	3.2	Gage
107	Diameter of stem for required distance, min.		0.40%	3.2	Gage
Minor					
201	Finish improper		0.65%	3.2	Visual
202	Protective finish inadequate, damaged, or improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Rod, Extension				8835005
					NEXT HIGHER ASSEMBLY 8833784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread		0.40%	3.2	Gage
103	Diameter of thread pilot, max.		0.40%	3.2	Gage
104	Length of thread pilot, max.		0.40%	3.2	Gage
105	Distance from base to top of thread min.		0.40%	3.2	Gage
106	Threads not rolled		0.40%	3.2	Visual
107	Deep cuts or grooves		0.40%	3.2	Visual
Minor					
201	Length, total		0.65%	3.2	Gage
202	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8833792
4.4.2.16	Collar				NEXT HIGHER ASSEMBLY 8832784
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Crack or split		100%	3.2	Visual
Major					
101	Height total		0.40%	3.2	Gage
102	Diameter of tilt rod cavity		0.40%	3.2	Gage
103	O.D. of flange		0.40%	3.2	Gage
104	Axial load test	80-0-1		3.2	4.5.3
Minor					
201	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Cap, bearing	1 OF 1	8833789
			NEXT HIGHER ASSEMBLY: 8833795

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Total height		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
104	Concentricity of outside diameter to inside diameter		0.40%	3.2	Gage
105	Depth of cavity		0.40%	3.2	Gage
106	Angle of chamfer		0.40%	3.2	Gage
107	Presence of vent hole		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Pin, firing		8834999
			NEXT HIGHER ASSEMBLY 8833794

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Length of point, min.		0.40%	3.2	Gage
102	Profile of point		0.40%	3.2	Gage
103	Concentricity of pin with body		0.40%	3.2	Gage
104	Groove missing		0.40%	3.2	Visual
Minor					
201	Total height, min.		0.65%	3.2	Gage
202	Outside diameter, min.		0.65%	3.2	Gage
203	Protective finish, improper or inadequate		0.65%	3.2	Visual
204	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Firing pin assembly				8833794
					NEXT HIGHER ASSEMBLY 8833795
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Total height, min,		0.40%	3.3	Gage
102	Height of body above flange		0.40%	3.3	Gage
103	Concentricity of outside diameter with firing pin		0.40%	3.3	Gage
Minor					
201	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.20	Firing pin spring assembly		8833795
			NEXT HIGHER ASSEMBLY 8833784

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Presence and location of groove pin		100%	3.3	Visual
2	Bearing cap cracked or deformed		100%	3.2	Visual
3	Firing pin loose in mold body		100%	3.3	Manual
Major					
101	Belleville spring not in cocked position		0.40%	3.3	Visual
102	Firing pin assembly not fully seated at mating surface of bearing cap at tilt rod end		0.40%	3.3	Visual
104	Groove pin protudes beyond outside diameter of bearing cap		0.40%	3.3	Visual
105	Firing pin damaged (mushroomed, scratched, etc.)		0.40%	3.2	visual
Minor					
201	Location of groove pin		0.65%	3.3	Gage
202	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.21	Spring, belleville		8796159
			NEXT HIGHER ASSEMBLY 8833795

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
104	Spring angle		0.40%	3.2	Gage
105	Cracks about outside or inside diameter		0.40%	3.2	Gage
106	Reversed height load and travel to snap back, and free overall height test	125-0-1	1/	3.8	4.5.2
Minor					
201	Marking improper or illegible		0.65%	3.2	Visual
202	Workmanship		0.65%	3.10	Visual

NOTES:

1/ 125-0-1 below 20 lbs; 125-5-6 above 27 lbs.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.22	Body Assembly, prior to assembly of cap and retainer				8833784
					NEXT HIGHER ASSEMBLY 8833783
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Seal loose or fits improperly		0.40%	3.3	Visual
102	O-Ring torn, cut or punctured		0.40%	3.2	Visual
103	Grease missing from body, seal, or tilt rod		0.40%	3.2	Visual
104	Seal torn, cut or punctured		0.40%	3.3	Visual
Minor					
201	Workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23	Body Assembly, prior to assembly of band, stop and closure assembly	1 OF 1	8833784
			NEXT HIGHER ASSEMBLY 8833783

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Collar split or cracked		100%	3.2	Visual
2	Groove pin loose		100%	3.3	Manual
Special					
1	Height to firing pin		100%	3.2	Gage
Major					
101	Firing pin spring assembly missing		100%	3.3	Visual
102	Closure gasket missing		0.40%	3.3	Visual
103	Retainer ring not fully seated in groove		0.40%	3.3	Visual
104	Fork missing		0.40%	3.3	Visual
105	Paint on threads		0.40%	3.3	Visual
Minor					
201	Protective finish improper or inadequate		0.65%	3.2	Visual
202	Workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.24	Body Assembly		8833784
			NEXT HIGHER ASSEMBLY 8833783

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Pin, boxed end missing		100%	3.3	Visual
2	Band and stop loose or not fully seated		100%	3.3	Visual
Major					
101	Closure assembly loose or cracked		0.40%	3.3	Visual
102	Air pressure		100%	3.4	4.5.1
103	Horizontal load	80-0-1		3.5	4.5.4
104	Penetration of firing pin point	80-0-1	1/	3.6	4.5.5
105	Jolt test	12-0-1		3.7	4.5.6
Minor					
201	Protective finish improper or adequate		0.65%	3.2	Visual
202	Workmanship		0.65%	3.10	Visual

NOTES:

1. Use the same assemblies as used in the horizontal load test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.4.3 Inspections to be performed. Each part shall be inspected for all dimensions, except those dimensions that have been machined, and characteristics specified on the applicable detail drawing.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in Classified of Defects and Tests forms beginning with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Air pressure. The metal parts assemblies shall be assembled into a fixture specified in 4.4.4 and subjected to an air pressure of not less than 5 p.s.i.g. for not less than 10 seconds. Observation shall be made for leakage of air into the fuze as evidenced by drop in air pressure.

4.5.2 Reversed height, load and travel to snap back, and free overall height of Belleville spring. The Belleville springs shall be subjected to an axial load at the rate of 1/2 to 1 inch per minute to cause it to snap through and then to snap back. Observation shall be made that the reversed height is 0.145 plus .015 inch, a load of 20 to 27 pounds is required to snap back, the travel during snap back is 0.085 plus .025 inch, and the height after snap back is 0.155 inch min. to determine compliance with the requirements. Springs so tested shall be scrapped.

4.5.3 Axial load of collars. The pull ring assembly, band and top shall be removed from the assembly. A uniform load shall be applied to the pressure ring along the vertical centerline of the fuze and at a rate of 1/2 to 1 inch per minute. The load at the time of breakage of the collar shall be recorded. Fuzes used in this test shall be discarded.

4.5.4 Horizontal load. This test shall be performed as specified in 4.5.3, except that the load shall be applied at the end of the extension rod. The load at the time of functioning shall be recorded. Functioning shall be evidenced by the breakage of the collar and sudden reversal of the belleville spring. Fuzes used in this test shall be discarded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.5.5 Penetration of firing pin point. This test shall be performed simultaneously with the horizontal load test (see 4.5.5). A lead slug, 0.370 inch - .005 long by 0.241 inch - .004 diameter shall be assembled to the fuze in place of the M46 detonator prior to the horizontal load test. After the horizontal load test, the lead slug shall be removed and the depth of penetration into the load slug shall be measured to the nearest .001 inch. The eccentricity of penetration shall be measured from the center of the lead cylinder to the center of the hole made by the firing pin point. Observation shall be made for compliance with 3.6.

4.5.6 Jolt test. The fuze metal parts assembly shall be assembled to the specified fixture and subjected to the jolt test as specified in Standard MIL-STD-331. Upon completion of the test, the fuze shall be examined to determine compliance with 3.7.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level C. The parts and assemblies for Fuze, Mine, AT, M607 shall be packed in accordance with Specification MIL-STD-1169 in such a manner that no damage will occur during shipment.

5.2 Packing.

5.2.1 Level C. The parts and assemblies for Fuze, Mine, AT, M607 shall be packed in accordance with Specification MIL-P-10025. Separately designated items shall not be packed together.

5.3 Data cards. Data card information shall be as specified in Specification MIL-A-2550.

5.4 Shipping. When component parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated.

5.5 Marking and labeling. Marking of the cartons shall be in accordance with Standard MIL-STD-129 and Specification MIL-P-10025.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U S ARDEC, ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:58Z
Check the source to verify that this is the currentversion before use.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U S ARDEC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.4 Drawings. Drawings listed in section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.6 Subject term (key word) listing.

Fuze, Mine, AT
Firing Pin
Belleville Spring
Reversed Height
Horizontal Load
Axial Load of Collars
Closure Assembly
Extension Rod

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A166)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
U S ARMY ARMAMENT RSCH DEV & ENGR CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-45430C (AR)	FUZE, MINE, AT: M607, PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:58Z
Check the source to verify that this is the current version before use.