MILITARY SPECIFICATION

FUZE, MINE, AT: M607,
PARTS FOR

This Amendment forms a part of Military Specification MIL-F-45430C(AR), dated 6 June 1986, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3, line 2: Change drawing number to "8833784".

PAGE 4

4.3.1: Delete in its entirety and substitute with the following:

"4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantities
Retainer	8835001	10
PA523, Detonator, Stab	9358084	10
Pin, Boxed End	12561279	10
Band	8833786	10
Body	8833787	10
Cap	8833788	10
Gasket	8834998	10
Closure	8833790	10
Fork	8834997	10
Closure Assembly	8833791	10
Ring, Pressure	8835002	10
Seal	8835007	10
Stop	8835008	10
Rod, Tilt	8835006	10
Rod, Extension	8835005	10
Collar	8833792	10

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

Cap, Bearing	8833789	10
Pin, Firing	8834999	10
Firing Pin Assembly	8833794	10
Firing Pin Spring Assembly	8833795	10
Spring, Belleville	8796159	10
Body Assembly	8833784	50

NOTES: (1) Those components produced from plastic molds or casting cavities shall have three (3) components from each mold or cavity submitted for this inspection. The contractor shall submit six sets each of bodies, caps, and pressure rings from each die which have been produced consecutively by the production process which the contractor will use in fulfilling the contract, to a Government-approved facility designated by the contracting officer. A set shall consist of all similar parts made in one complete operating cycle of the die casting machine. The sets shall consist of 3 sets of parts intact, attached to gates and runners (sprue), and 3 sets of parts after machining, and shall be identified by the number of the die that produced them. Individual parts in the set shall be identified by the cavity number in the die."

PAGE 5

4.3.4: Delete in its entirety and substitute with the following:

"4.3.4 Die requalification. At the conclusion of every 10,000 parts produced, the contractor shall submit to a Government-approved facility designated by the contracting officer, three sets each of bodies, caps, and pressure rings from each die being used in production process in fulfilling the contract, and whenever a change occurs in the manufacturing process. A set shall consist of all similar parts made in one complete operating cycle of the die casting machine. These parts shall be submitted after machining, and shall be identified by the number of the die that produced them. Individual parts in the set shall be identified by the cavity number in the die. If the parts submitted are rejected, thus disqualifying the dies, the contractor may correct his dies and submit a new quantity of parts for acceptance. Only those parts produced by qualified dies shall be acceptable for production. Die requalification is considered a special test and parts expended shall not be considered as deliveries."

PAGE 6

TABLE I: Delete in its entirety and substitute with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Fuze, Mine, AT: M607		SHEET 1 OF 4		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Retainer (Dwg. 8835001) Examination for Defects	10		3.2	4.4.2.1
	PA 523, Detonator, Stab (Dwg. 9358084) Examination for Defects	10		3.2	4.4.2.2
	Band (Dwg. 8833786) Examination for Defects	10		3.2	4.4.2.4
	Pin, Boxed End (Dwg. 12561279) Examination for Defects	10		3.2	4.4.2.3
	Body (Dwg. 8833787) Examination for Defects	10		3.2	4.4.2.5
	Cap (Dwg. 8833788) Examination for Defects	10		3.2	4.4.2.6
	Gasket (Dwg. 8834998) Examination for defects	10		3.2	4.4.2.7
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Fuze, Mine, AT: M607		SHEET 2 OF 4		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Closure (Dwg. 8833790) Examination for Defects	10		3.2	4.4.2.8
	Fork (Dwg. 8834997) Examination for Defects	10		3.2	4.4.2.9
	Closure Assembly (Dwg. 8833791) Examination for Defects	10		3.2	4.4.2.10
	Ring, Pressure (Dwg. 8835002) Examination for Defects	10		3.2	4.4.2.11
	Seal (Dwg. 8835007) Examination for Defects	10		3.2	4.4.2.12
	Stop (Dwg. 8835008) Examination for Defects	10		3.2	4.4.2.13
	Rod, Tilt (Dwg. 8835006) Examination for Defects	10		3.2	4.4.2.14

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22102:582
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-45430C(AR)
AMENDMENT 1

PARAGRAPH	TITLE: Fuze, Mine, AT: M607		SHEET 3 OF 4		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rod, Extension (Dwg. 8835005) Examination for Defects	10		3.2	4.4.2.15
	Collar (Dwg. 8833792) Examination for Defects	10		3.2	4.4.2.16
	Cap, Bearing (Dwg. 8833789) Examination for Defects	10		3.2	4.4.2.17
	Pin, Firing (Dwg. 8834999) Examination for Defects	10		3.2	4.4.2.18
	Firing Pin Assembly (Dwg. 8833794) Examination for Defects	10		3.2	4.4.2.19
	Firing Pin Spring Assembly (Dwg. 8833795) Examination for Defects	10		3.2	4.4.2.20

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Fuze, Mine, AT: M607		SHEET 4 OF 4		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Belleville				
	(Dwg. 8796159)				
	Examination for Defects	10		3.2	4.4.2.21
	Reversed height, load and travel to snap back, and free overall height test.	10		3.8	4.5.2
	Body Assembly, prior to assembly of cap and retainer				
	(Dwg. 8833784)				
	Examination for Defects	10		3.2	4.4.2.22
	Body Assembly, prior to assembly of band, stop and closure assembly				
	(Dwg. 8833784)				
	Examination for Defects	10		3.2	4.4.2.23
	Body Assembly				
	(Dwg. 8833784)				
	Examination for Defects	50		3.2	4.4.2.24
	Air pressure test	50		3.4	4.5.1
	Axial load of collars test	20		3.3	4.5.3
	Horizontal load test	20		3.5	4.5.4
	Penetration of firing pin point test	20		3.6	4.5.5
	Jolt test	10		3.7	4.5.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

PAGE 22

4.4.2.11, Minor 203: Change AQL to "1.0%".

PAGE 23

4.4.2.12, Minor 201: Change AQL to "1.0%".

PAGE 24

4.4.2.13, Minor 203: Change AQL to "1.0%".

PAGE 25

4.4.2.14, Minor 203: Change AQL to "1.0%".

PAGE 26

4.4.2.15, Minor 203: Change AQL to "1.0%".

PAGE 27

4.4.2.16:

Major 104: Delete in its entirety.

Minor 201: Change AQL to "1.0%".

PAGE 28

4.4.2.17, Minor 201: Change AQL to "1.0%".

PAGE 29

4.4.2.18, Minor 204: Change AQL to "1.0%".

PAGE 30

4.4.2.19, Minor 201: Change AQL to "1.0%".

PAGE 31

4.4.2.20, Minor 202: Change AQL to "1.0%".

PAGE 32

4.4.2.21, Minor 202: Change AQL to "1.0%".

PAGE 33

4.4.2.22, Minor 201: Change AQL to "1.0%".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

PAGE 11

4.4.2.1: Under Minor defects, change to read:

"201 Workmanship 1.0% 3.10 Visual".

PAGE 12

4.4.2.2, Minor 201: Change AQL to "1.0%".

PAGE 13

4.4.2.3, Minor 204: Change AQL to "1.0%".

PAGE 14

4.4.2.4, Minor 202: Change AQL to "1.0%".

PAGE 15

4.4.2.5, Minor 203: Change AQL to "1.0%".

PAGE 16

4.4.2.6, Major 106: Change "of" to "to".

PAGE 17

4.4.2.6, Minor 203: Change AQL to "1.0%".

PAGE 18

4.4.2.7, Minor 204: Change AQL to "1.0%".

PAGE 19

4.4.2.8, Minor 201: Change AQL to "1.0%".

PAGE 20

4.4.2.9, Minor 201: Change AQL to "1.0%".

PAGE 21

4.4.2.10:

Major 101: Change "Distane" to "Distance".

Minor 201: Change AQL to "1.0%".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

PAGE 34

4.4.2.23, Minor 202: Change AQL to "1.0%".

PAGE 35

4.4.2.24:

Under Major defects, add:

"106 Axial load of collars 80-0-1 3.3 4.5.3".

Minor 202: Change AQL to "1.0%".

PAGE 36

4.5.3:

Line 1: Change "pull ring assembly" to "boxed end pin".

Line 2: Change "top" to "stop".

PAGE 37

4.5.5, line 4: Change "M46" to "PA523".

PAGE 38

6.5: Renumber "6.5" to "6.6" and add new paragraph 6.5:

"6.5 Intended use. When the M607 is manufactured specifically to be used in the M624 Adapter and Fuze Assembly, the following parts will not be manufactured and therefore all references to said parts contained within this specification are not applicable.

Closure (P/N 8833790)
Fork (P/N 8834997)
Closure Assembly (P/N 8833791)
Rod, Extension (P/N 8835005)"

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A380)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.