MILITARY SPECIFICATION

FUZES, HAND GRENADE, M213 AND M215 PARTS FOR, LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-F-45437D(PA) dated 23 April 1976.

PAGE 4

Add paragraph 3.7.4:

"3.7.4 Moisture Content. - The moisture content of the delay composition shall not exceed 0.04% maximum throughout assembly of the fuze."

PAGE 20

Paragraph 4.4.2.10 - Add Major Defect 106:

"106 Moisture Content 0.40% 3.7.4 4.4.3.11.4"

PAGE 32

Add paragraph 4.4.3.11.4:

"4.4.3.11.4 Moisture Content. - The contractor shall provide adequate controls to maintain the moisture content of the delay column during all operations of the Fuze assembly. The contractor shall develop and submit a plan to insure that the moisture content is maintained within the specified limits, including records to be kept and made available to the government upon request. Changes to the approved process will require approval of the design Agency in order to insure that the change will not degrade the fuze function."

FSC: 1330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:59Z
Check the source to verify that this is the current version before use.

PAGE 34

Paragraph 4.5.5 - Add the following sentence after "retest." in Line 14:

"Fuze assemblies subject to retest shall be maintained in a humidity controlled area in order to insure that the requirements of 3.7.4 are maintained."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1330-A128

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:59Z
Check the source to verify that this is the current version before use.