MIL-M-45424D(MU)
17 August 1970
SUPERSEDING
MIL-M-45424C(MU)
15 AUGUST 1966

MILITARY SPECIFICATION

MINE, ANTIPERSONNEL, M18A1
PARTS FOR

1. SCOPE

1.1 This specification covers the parts for one type of mine designated as Mine, Antipersonnel, M18A1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-T-45 - Tape, Gummed, Paper Reinforced and Plain, for Sealing and Securing
PPP-B-636 - Box, Fiberboard

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

8885262 - Mine, APERS, M18A1, Assembly

PUBLICATIONS

U.S. ARMY MUNITIONS COMMAND

ET-8885262 - Equipment Tabulation Number

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Mine parts.-The mine parts shall comply with all requirements specified on Drawing (dwg.) 8885262, and with all requirements specified in applicable specifications.

3.3 Susceptibility to cracking

3.3.1 Case assembly.-The case assembly, dwg. 8800918, shall not crack when subjected to a load of 175 pounds, plus or minus 5 pounds when tested as specified in 4.4.3.1

3.3.2 Cover.-The cover, dwg. 8800916, shall not crack when subjected to a load of 60 pounds, plus or minus 5 pounds when tested as specified in 4.4.3.2.

3.3.3 Low temperature.-The cover and mine case assembly shall not crack when subjected to temperature conditioning at minus 65 degrees Fahrenheit plus or minus 5 degrees, for a period of 24 hours plus or minus 1/2 hour when tested as specified in 4.4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

3.4 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, crazes, porosity, warpage, burn marks, checks, blisters, excess flash, unblended radii, chipped edges, scratches, dirt, grease, rust, corrosion products and other defects and foreign matter which would affect appearance or serviceability. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

3.5 First article inspection.-This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Refernce shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall bupply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 15 complete sets of parts (i.e., 15 each of every individual component and every subassembly, including at least three itemss from each cavity used to produce plastic parts and so identified as to permit tracing each item to the cavity in which it was molded) which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit an additional sample or portion thereof of items for first article inspection. Until a first article sample is accepted, the contractor is, in no way, authorized by the Government to initiate regular production unless otherwise directed by the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.2.2 Inspections to be performed.-Subassemblies and components shall be subjected by the Government to any or all of the examinations specified in 4.3 of this specification and any or all requirements of the applicable drawings. After classification of defects and other inspections have been performed as specified, the following components and sub-assemblies shall be subjected to test as indicated below:

a. Susceptibility to cracks under loading (see 3.3.1 and 3.3.2) - 5 case assemblies, 5 covers

b. Susceptibility to cracks at low temperature (see 3.3.3) - 5 case assemblies, 5 covers

c. Hardness and carburization of ball (see dwg. 8800922) - 15 balls

4.2.3 Rejection.-If any subassembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected, The Government reserves the right to terminate its inspection upon any failure of a subassembly or component to comply with any of the stated requirements.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represnt any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspectionlot has been produced by one manufacturer, in one unchaged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions, and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot munbering, as reuqired, shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.3.1.1 Process specification.-A process specification specifiying the time, temperature and pressure ranges which shall be maintained during production of the molded parts shall be kept on file and available for review.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL’s to individual defects using an AQL of 0.40 percent for each major defect and AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraphs of this section, except where 100 percent inspection is specified, and be documented as part of the contractor’s inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Case (see dwg. 8800915 covering a detail of dwg. 8885264).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Case split	Visual	01001
102.	Fillet to face of snap tabs improper	Visual	01002
103.	Start of perfect trread incorrectly located	Gage	01003
104.	Depth of thread cavity	Gage	01005
105.	Depth oto botto of undercut below threads, maximum (max.). .	Gage	01006
106.	Location of well recesses . .	Gage	01007

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.0 percent		
201.	Knife-edges of sight have flash or nicks	Visual	01008
202.	Evidence of poor workmanship (see 3.4)	Visual	01009

4.3.2.2 Cover (see dwg. 8800916 covering a detail of dwg. 8885262).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Cover split	Visual	02001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	02002

4.3.2.3 Case assembly (see dwg. 8800918 covering a detail of dwg. 8885262).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Height front to rear knife-edge	Gage	03001
102.	Length across snap tabs	Gage	03002
103.	Width across snap tabs	Gage	03003
104.	Pitch diameter of threads	Gage	01004
105.	Outside length of mating lip section	Gage	01019
106.	Outside width of mating lip section	Gage	01020
107.	Potting compound on threads or wall of thread cavity	Visual	03014
108.	Part missing or improperly assembled (except balls)	Visual	03008
Minor:	AQL 4.0 percent		
201.	Excess potting compound on inner walls	Visual	03004
202.	Height between compound and top of balls	Visual	03005
203.	Void larger than 1 ball	Visual	03006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

204.	Balls not flush	Visual	03007
205.	Torque to move legs (see dwg. 8837129)	Test	03009
206.	Torque to move brackets	Test	03010
207.	Evidence of poor workmanship (see 3.4)	Visual	03011

4.3.2.4 Ball (see dwg. 8800922 covering a detail of dwg. 8885262).

Categorles		Defects	Method of Inspection	Code No.
Critical:	None defined			
Major:		AQL 0.40 percent		
	101.	Crack or split	Visual	04001
Minor:		AQL 1.0 percent		
	201.	Diameter	Gage	04002
	202.	Evidence of poor workmanship (see 3.4)	Visual	04003

4.3.2.5 Cup, well (see dwg. 8837133 covering a dstail of dwg. 8885262).

Categories		Defects	Method of Inspection	Code No.
Critical:	None defined			
Major:		AQL 0.40 percent		
	101.	Flange diameter	Gage	05001
Minor:		AQL 0.65 percent		
	201.	Evidence of poor workmanship (see 3.4)	Visual	05002

4.3.2,6 Shipping plug (see dwg. 8857210 covering a detail of dwg. 8885262).

Categories		Defects	Method of Inspection	Code No.
Critical:	None defined			

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:58Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.65 percent		
101.	Start of perfect thread, plug end	Gage	06001
102.	Start of perfect thread, slit end	Gage	06002
103.	Slot width, minimum (min.)	Gage	06003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	06004

4.3.2.7 Carton sealed (see section 5).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Contents move when carton is shaken (insufficient filler material)	Manual	07001
102.	Carton damaged so that contents are exposed or liable to become exposed	Visual	07002
103.	Sealing strip incomplete, badly wrinkled, or not fully attached to surface around entire carton	Visual	07003
Minor:	AQL 0.65 percent		
201.	Marking misleading or unidentifiable	Visual	07004

4.3.3 Testing

4.3.3.1 Hardness and carburization of ball (see dwg. 8800922) - Major defects - Code No. 04004 for hardness and Code No. 04005 for carburizatiorL.-Fifteen (15) balls from each heat treatment batch shall be selected for these tests. If a total of two or more balls fall to comply with either requirement or both requirements combined, the heat treatment batch shall be rejected. The tests shall be performed as specified in 4.4.1 and 4.4.2 using equipment i.n accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T02:58Z
Check the source to verify that this is the current version before use.

4.3.3.2 Susceptibility to cracking

4.3.3.2.1 Case assembly (see 3.3.1) - Major defect - Code No. 03012.-A sample of thirty-five case assemblies shall be selected from each lot for this test. If one or more case assemblies fail to comply with the requirements specifed, the lot shall be rejected. The test shall be performed as specified in 4.4.3.1, using equipment in accordance with 4.3.4.

4.3.3.2.2 Covers (see 3.3.2) - Major defect - Code No. 02003. -A sample of thirty-five covers shall be selected from each lot for this test. If one or more covers fail to comply with the requirements specified, the lot shall be rejected. The test shall be performed as specified in 4.4.3.2, using equipment in accordance with 4.3.4.

4.3.3.2.3 Low temperature (see 3.3.3) - Major defect - Code No. 03013 for case assemblies and Code No. 02016 for covers. -A sample of fifteen case assemblies and fifteen covers shall be selected from each lot for this test. If one or more case assemblies or covers fail to comply with the requirement specified the corresponding lot shall be rejected. The test shall be performed as specified in 4.4.3.3 using equipment in accordance with 4.3.4.

4.3.4 Inspection Equipment.-Equipment Tabulation Number ET-8885262 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspectionof items at overhaul general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.3.5 Dimensional control of cast or molded parts.- To qualify a new or reworked cavity for use in production, a sample of at least three (3) parts from each cavity shall be fully inspected dimensionally. Individual cavity identification must be provided for each mold. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed In paragraphs 4.3.5.1 through 4.3.5.3 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All molds removed from production because of some fault, may after reworking, be returned to production provided they pass the qualification test above. The contractor may request a change of inspection frequency provided he presents objective evidence to the contracting officer to substantiate the request. The following subparagraphs identify those items and the minimum inspections subject to the requirements of this paragraph. A defect classification of Minor is assigned to all defects listed herein.

The following subparagraphs Identify those items and the minimum inspections subject to the requirements of this paragraph.

4.3.5.1 Case (see dwg. 8800915)

Defects	Method of Inspection	Code No.
1. Marking minleading or unidentifiable	Visual	01010
2. Radius of mating lip edge incorrect . . .	Visual	01011
3. Radii and fillets incorrect	Visual	01012
4. Height of mating liup above peripheral band	Gage	01013
5. Outside corner radius (4) of lip	Gage	01014
6. Thickness of front face in area of four (4) corners	Gage	01015
7. Thickness of walls, 4 sides	Gage	01016
8. Thickness of 4 eyepiece stiffener webs	Gage	01017
9. Theickness of 2 knife-edge sections	Gage	01018

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T02:58Z
Check the source to verify that this is the current version before use.

10. Outside diameter of well bodies	Gage	01021
11. Width of (4) snap tabs	Gage	01022
12. Bracket hole locations front to rear	Gage	01023
13. Bracket hole diameters	Gage	01024
14. Diameter of undercut below threads. . .	Gage	01025
15. Width of peripheral band, 4 sides. . . .	Gage	01026
16. Width of clearance slots behind wells	.Gage	01027
17. Height of clearance slots behind wells	.Gage	01028

4.3.5.2 Cover (see dwg. 8800916)

Defect	Method of Inspection	Code No.
1. Marking misleading or unidentifiable	Visual	02004
2. Radii and fillets incorrect	Visual	02005
3. Lip thickness, 8 places	Gage	02006
4. Face thickness, 4 sides	Gage	02007
5. Width of cutouts	Gage	02008
6. Height of lip above cutouts, 3 places.	.Gage	02009
7. Height of top cutout tab	Gage	02010
8. Location of cutouts	.Gage	02011
9. Inside lip height, 2 sides	Gage	02012
10. Inside width	Gage	02013
11. Inside length	Gage	02014
12. Lip contour out	.Gage	02015

4.3.5.3 shipping plug (see dwg. 8857210)

Defect	Method of Inspection	Code No.
1. Overall height of plug end	Gage	06005
2. Overall height of slit end	Gage	06006
3. Height of plug boss.....	Gage	06007
4. Height of plug end threaded section	Gage	06008
5. Height of slit end threaded section	Gage	06009
6. Depth of counterbore	Gage	06010
7. Height to major diameter, 2 places	Gage	06011
8. Height to pitch diameter, 2 places	Gage	06012
9. Thread major diameter, 2 places	Gage	06013

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

10.	Thread pitch diameter, 2 places	Gage	06014
11.	Boss diameter incorrect, 2 places. . .	Gage	06015
12.	Counterbore diameter	Gage	06016
13.	Optional hole diameter oversize . . .	Gage	06017
14.	Optional hole depth oversize	Gage	06018
15.	Small adapter hole diameter	Gage	06019
16.	Countersink missing or inadequate. . .	Visual	06020

4.3.6 Dimensional control of stamped parts.-To qualify a new or reworked tool to be used in the stamping process for use in production, a sample of at least ten (10) parts shall be fully inspected dimensionally. As a control of each tool during production, the above quantity of parts from each tool shall be inspected for at least the defects specified in 4.3.6.1 through 4.3.6.3 after each hours production. If any defective parts are found during qualification of the tool it shall not be used in production. If any defective parts are found when inspection is performed for the control of the tool, the tool producing the defect shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All tools removed from production because of some fault, may after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request. The following subparagraphs identify those Items and minimum inspections subject to the requirements of this paragraph. A defect classification of Minor is assigned to all defects listed herein.

4.3.6.1 Bracket, angle (see dwg. 8800907 covering a detail of dwg. 8885262).

Defects	Method of Inspection	Code No.
1. Bend angle	Gage	08001
2. Hole location, 2 places	Gage	08002

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

3. Hole diameter, 2 places	Gage	08003
4. End radius, 2 places	Gage	08004
5. Evidence of poor workmanship (see 3.4)	Visual	08005

4.3.6.2 leg (see dwg. 8800908 covering a detail of dwg. 8885262).

Defect	Method of Inspection	Code No.
1. Offset depth	Gage	09001
2. Hub diameter	Gage	09002
3. Hole diameter	Gage	09003
4. Length hole to tip	Gage	09004
5. Evidence of poor workmanship (see 3.4)	Visual	09005

4.3.6.3 Cup, well (see dwg. 8837133 covering a detail of dwg. 8885262).

Defect	Metnod of Inspection	Code No.
1. Length, min	Gage	05003
2. Inside diameter	Gage	05004
3. Wall thickness	Gage	05005
4. Bottom thickness	Gage	05006

4.4 Test methods and procedures

4.4.1 Surface hardness of ball. -The surface hardness of the bail shall be determined as follows: Mount specimen in bakelite. The finished. surface shall be through the centerline of the specimen within 0.003 inches and must be highly polished and free from scratches and surface imperfections. (Surface preparation should be Performed by using emery papers of increasing fineness up to No. 000, followed by final polishing on green and blue billiard cloths to provide the specimen with a scratch-free surface where minimum disturbed metal is present.) Using a Tukon microhardness tester with a roo gram load 0.20, 0.25, and 0.30 millimeters from the edge or the speciment. The average shall be taken of the three readings and shall be between 438 and 576 on the Knoop hardness scale. Failure to obtain an average reading~ within the established limits shall cause the specimen to be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

4.4.2 Carburization of ball.-Utilizing samples prepared as specified in 4.4.1, take three (3) hardness readings 0.05 millimeters apart between 1.14 and 1.65 millimeters from the edge of the speciment. The average of the three readings must be at least 75 Knoop points lower than the surface hardness obtained for the same piece as specified in 4.4.1 to indicate presence of a core. Failure to meet this requirement shall cause the specimen to be classed defective.

4.4.3 Susceptibility to cracks under loading

4.4.3.1 Case assembly.-The case assembly shall be placed on a flat dry steel surface of 60 micro-inch finish with the convex curved face facing upward. The sight area shall be allowed to overhang the side of the steel surface so that the sides of the case assembly lie flat on the testing surface. A load of 175 pounds plus or minus 5 pounds shall be applied with a flat plate, five inches square minimum, centered over the convex curved face. The load shall be applied and held for a period of 5 seconds minimum and care shall be taken to avoid a sudden application of the load with consequent risk of exceeding the requirement. Observation shall be made for evidence of cracks, including hairline cracks, as evidence of noncompliance with 3.3.1.

4.4.3.2 Cover.-The cover shall be placed on a flat dry steel surface of 60 microinch finish with the concave curved face facing downward. A load of 60 pounds plus or minus 5 pounds shall be applied with a flat plate, 3-3/4 inches square centered over the convex curved face. The load shall be applied and held for a period of 5 seconds minimum and care shall be taken to avoid a sudden application of the load with consequent risk of exceeding the requirement. Observation shall be made to evidence of cracks, including hairline cracks, as evidence of noncompliance with 3.3.2.

4.4.3.3 Low temperature.-The case assembly and the cover shall be placed in a cold temperature chamber in such a manner that no external mechanical stresses are applied. The case shall be maintained at a temperature of minus sixty-five degrees Fahrenheit plus or minus 5 degrees for a period of 24 hours, plus or minus 1/2 hour. Observation shall be made for evidence of cracks, including hairline cracks, as evidence of noncompliance with 3.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C.-The parts for Mine, Anti-personnel, M18A1 shall be packaged in accordance with Specification MIL-STD-1169. Separately designated items shall not be packaged together as a single assembly.

5.2 Packing

5.2.1 Level C.-The parts for Mine, Anti-Personnel, M18A1 shall be packaged in accordance with Specification MIL-STD-1169. The following additional packing requirements shall apply for the items specified.

5.2.1.1 Case assembly (dwg. 8800918).-Thirty (30) case assemblies shall be packed leg-end down in a fiberboard box with interior half-slotted partitions assembled to form 30 individual cells in 3 by 5 arrangement. A filler pad shall be inserted in the bottom of the box, between layers, and on the top layer of cells. The inside dimension of each cell shall be 8-1/2 by 2-1/16 by 5-1/2 inches deep. The inside dimensions of the box shall be 25-13/16 by 10-7/8 by 11-3/8 inches deep. The filler pads shall be 25-3/4 by 10-3/4 inches. The box shall be Style RSC, conforming: to Specification PPP-B-636, Type CF, Class Domestic, Variety SW, Grade 200. The partitions and filler pads shall be constructed of the same fiberboard as the box. Minor changes in dimension to provide a tight pack are permissible.

Top and bottom flaps of the box shall be sealed by applying 2-inch wide gummed kraft tape conforming to Specification PPF-T-45, Type III, Grade B over the intire length of all seams, with an extension of a minimum of 2 inches onto the end panels, and around all corners of the box.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

c. Provisions for submission of first article samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspection herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. In addition, they should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraph 6.3,1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment design by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraph 6.3.3 anti 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as- "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commerical equipment
MU - Army design, mandatory for use

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classification; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number).

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:58Z
Check the source to verify that this is the current version before use.

When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all Information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted In accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND15. All other designs of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1345-A-299

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:58Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:58Z
Check the source to verify that this is the current version before use.