PP-P-002211(Army-GL)
September 27, 1984
SUPERSEDING
(See 6.4)

INTERIM FEDERAL SPECIFICATION

PORK SLICES, WITH GRAVY, THERMOSTABILIZED, TRAY PACK

This interim Federal specification was developed by the U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers Pork Slices With Gravy, thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, and other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

FSC 8940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items
MIL-L-35078	-	Loads, Unit; Preparation of Nonperishable Subsistence Items; General Specification for

Military Standards:

MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-900	-	Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Canned Foods for the Armed Forces

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Law and Regulations:

U.S. Department of Health and Human Services

Federal Food, Drug, and Cosmetic Act and Regulation Promulgated Thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Department of Agriculture (USDA)

Meat and Poultry Inspection Regulations

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Standards for Condition of Food Containers

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Environmental Protection Agency (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Dehydrated Onion and Garlic Association (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association (ADOGA), 251 Kearny Street No. 410, San Francisco, CA 94108.)

American Spice and Trade Association

Official Analytical Methods of the American Spice and Trade Association

(Application for copies should be addressed to the American Spice and Trade Association, Inc., 580 Sylvan Avenue, Englewood Cliffs, NJ 07632.)

Association of Official Analytical Chemists

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

National Academy of Sciences

Food Chemicals Codex

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Pork. Pork shall be derived from any one or any combination of the following recognizable wholesale bone in cuts: shoulders, shoulder picnics, Boston butts, hams and loins. Recognizable cuts are those which, when compared to IMPS cuts, have no more than a minor amount of lean fat or bone removed or included from an adjacent cut. All pork destined for use in the product shall be in excellent condition, i.e., exposed lean and fat surfaces shall be of a color and bloom normally associated with the class and cut of meat and typical of meat which has been properly stored and handled. Cut surfaces and naturally exposed lean surfaces shall show no more than slight darkening or discoloration due to dehydration, aging or microbial activity. The fat shall show no more than a slight discoloration due to oxidation or microbial activity. No odors foreign to fresh meat shall be present. Changes in color and odor characteristically associated with vacuum packaged meat in excellent condition shall be acceptable. Also, the pork shall show no evidence of freezing, defrosting or mishandling. Coarse textured, dark pork and pale, soft and exudative (PSE) pork is not accpetable. Cuts which have had a slight amount of bruised lean fully removed will be acceptable. Cuts which have had more than a slight amount of lean removed for any reason are not eligible to be included. All suitable lean meat shall be used in proportions as existing in the involved cut, except that the tenderloins may be excluded at the option of the contractor.

3.2.1.1 Boning and trimming. The pork shall be boned and trimmed to remove objectionable material such as bone, cartilage, heavy connective tissue, etc. The boneless trimmed pork shall meet the limitations specified in tables I and II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

3.2.1.2 Handling and storage. Handling and storage of the boned and trimmed pork prior to processing into the finished product shall be in accordance with the following requirements:

a. Pork processed on the same day as boning and trimming shall be held in the temperature range of 28° to 50°F (inclusive) at all times prior to processing.

b. Holding in the fresh chilled state for not more than 4 days is permitted provided that the pork is maintained in the temperature range of 28° to 40°F (inclusive) at all times prior to processing.

c. Holding raw pork in the frozen state is permitted provided that the pork is:
- placed in the freezer within 4 hours after certification and frozen to 0°F within 72 hours
- stored at 0°F or lower at all times
- held for not more than 60 days
- protected from freezer deterioration and damage
- stored in containers that are adequate to maintain product excellence
- maintained without defrosting until time of processing into the finished product.

3.2.2 Water. Water used for ice making, formulation, and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.2.3 Starch, modified, high opacity. The high opacity starch shall be white, odorless, finely pulverized, modified maize food starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. The starch shall resist breakdown at low pH, under shear stress, and conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.4 Onions, dehydrated, chopped. Dehydrated chopped onions shall be fancy grade complying with the Official Standards and Methods of the American Dehydrated Onion and Garlic Association (ADOGA) for Dehydrated Onion and Garlic products.

3.2.5 Salt. Salt shall be non-iodized, white, refined sodium chloride, with or without anti-caking agents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

3.2.6 Worcestershire sauce. Worcestershire sauce shall be a brown to dark brown colored liquid having a pleasant, tart, peppery fruit-spice flavor and shall possess the body and character typical of this sauce. Titratable acidity, as acetic acid, shall not be less than 2.5 nor more than 3.5 percent.

3.2.7 Monosodium glutamate. Monosodium glutamate (MSG) shall comply with the Food Chemicals Codex.

3.2.8 Garlic powder. Garlic powder shall be Standard grade or better of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association (ADOGA) for Dehydrated Onion and Garlic products.

3.2.9 Paprika. Paprika shall be Spanish paprika and shall possess a bright orange to red color with a color value in the range of 90 to 120 American Spice and Trade Association (ASATA) units.

3.2.10 White pepper, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer an inner coverings have been removed. The ground white pepper shall have a characteristic penetrating odor, a hot biting pungent flavor and a light color. Volatile oil content shall be not less than 1.0 mL/100g and the white pepper shall be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.11 Color, caramel. Caramel color shall meet the requirements of Food Chemicals Codex.

3.2.12 Brown sugar. Brown sugar shall be partially refined cane sugar. It shall be light brown in color and shall have a sweet, molasses-like flavor.

3.2.13 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this specification. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formula.

3.3 Preparation and processing.

3.3.1 Pork preparation. The boned and trimmed pork shall be mechanically ground once through a kidney-shaped plate having openings measuring 2-1/2 inches or more in the least dimension using a two-bladed knife that yields

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

pieces weighing at least 2 ounces. Grinding shall be a continuous process and the meat shall be ground within 4 days following the boning and trimming operation.

3.3.1.1 Mixing. The ground meat shall be mechanically vacuum mixed in accordance with the following formulation:

Ingredient	Percent
Pork	96.25
Salt	0.75
Water (Ice Slush)	3.00

Mixing shall continue until the product becomes moderately tacky. Time from grinding to mixing shall not exceed 4 hours.

3.3.1.2 Stuffing and forming. The mixed meat shall immediately be mechanically stuffed into number 6-1/2 regenerated cellulose prestuck casings. The open ends shall be left temporarily unclipped. The resultant meat logs (rolls) shall be pressed between spring-loaded screens separated by 1 3/4 inch spacers, such that rectangular shaped logs are formed measuring 1 3/4 inch $\pm$ 1/8 inch in height. The open ends shall then be sealed, exerting minimum pressure on the meat. The stuffed meat logs shall be cooked within 4 hours after being stuffed.

3.3.1.3 Cooking. The pressed meat logs in the screens shall be cooked in a cook house (smoke house without smoke) or other commercially acceptable cooking method to provide a product meeting the finished product requirements.

3.3.1.4 Cooling and freezing. Immediately after completion of the cooking, the meat logs shall be refrigerated and cooled to 40°F (maximum). The cooled, cooked meat logs shall be held not longer than 48 hours at a temperature not to exceed 40°F prior to slicing. Alternatively, the cooked meat logs may be held in the frozen state after cooking, provided the logs are placed in a freezer within 4 hours after cooking and frozen to 0°F or lower within 10 hours after being placed in the freezer and the meat is mechanically vacuum stuffed into heat sealable casings made from FDA and USDA food approved laminate consisting of 0.0005 inch thick polyester and 0.0015 inch thick medium density polyethylene. If the pork logs are to be frozen the meat shall not have been previously frozen. The frozen cooked logs shall be held at 0°F for a period of not more than 14 days prior to slicing. The frozen meat logs shall be tempered to a range of 28° to 40°F prior to slicing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

REASON FOR RECOMMENDATION

3.3.1.5 Slicing. The cooked pork logs shall be sliced into slices having uniform size, shape and thickness. Slicing to filling shall be a continuous operation.

3.3.2 Gravy preparation. The gravy shall be formulated as follows:

Ingredient	Percent
Water	91.69
Starch	5.50
Onions, chopped, dehydrated	0.93
Salt	0.65
Worcestershire sauce	0.44
Brown sugar	0.40
Monosodium glutamae	0.30
Garlic powder	0.04
White pepper, ground	0.02
Paprika	0.02
Caramel color	0.01

a. A slurry shall be made with the starch and part of the water. The remaining ingredients shall be mixed together and heated to not less than 180°F. The starch slurry shall be added and the final mixture heated to 165° to 170°F and held for approximately 5 minutes at this temperature.

b. The volume of the final mixture shall be adjusted to compensate for evaporation loss during heating.

c. The gravy shall be used within 4 hours after cooking. The temperature of the prepared gravy shall not be allowed to fall below 150°F any time prior to fillling of the tray pack cans.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with pork slices and gravy such as to conform to the finished product requirements and to the following requirements:

a. Not less than 60 pork slices shall be shingled in two rows within each tray pack can and then covered with gravy.

b. The gravy temperature at time of filling shall be not less than 150°F.

c. The pork temperature at time of filling shall be within the range of 28° to 40°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

d. Each can shall be hermetically sealed with a minimum of 10 inches (Hg) vacuum immediately after filling.

e. The filled and sealed tray pack cans shall be in the retort process within 1 hour after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting at 240°F or below until a sterilization value (F_o) of not less than 6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material, such as, but not limited to dirt, insect, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor, such as, but not limited to burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. Pork slices shall not be dry, tough, rubbery or mushy.

e. Gravy shall have a smooth (not lumpy) consistency without being excessively thick or thin.

f. No individual can shall contain less than 62 ounces drained weight of pork slices.

g. Total weight of fat chunks, opaque connective tissue, ligaments, tendons, blood vessel, cartilage or glandular material shall be not greater than 3 ounces.

h. The average net weight shall be not less than 106 ounces.

i. No individual can shall contain less than 104 ounces of product.

j. The average fat content shall not be greater than 12.0 percent.

k. The fat content of any individual can shall not be greater than 14.0 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

l. The salt content of any individual can shall be not less than 0.5 percent nor greater than 1.25 percent.

m. No individual can shall contain less than 60 approximately 1 3/4 by 4 1/2 inch intact pork slices.

n. There shall be no pockets of fat greater than 1/2 inch in any dimension extending through the pork slice.

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The pork component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting it to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this specification. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatabilty failure shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

4.4 Component and material inspection. Compenents and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1 Pork examination for condition and cut. All pork shall be examined in either the bone-in or boneless state for conformance to the condition and cut requirements in 3.2.1. Cuts initially examined in the boneless state shall be in the form of whole boneless recognizable cuts. Any nonconforming pork shall be rejected.

4.4.2 Boned and trimmed pork examination. After boning and trimming and prior to any further processing or to any freezing, the pork shall be examined for the defects listed in table II. The lot size expressed in terms of pounds shall be declared to the Agricultural Marketing Service (AMS) agent by the contractor. However, the AMS agent reserves the right to declare as a lot a portion of a declared lot, if, in his or her opinion, that portion may be out of compliance with any requirement. The sample unit shall be a minimum of 12 pounds of adjacent boneless pork. The sample size shall be as specified in table I. If all or a portion of the sample unit falls within a larger cut, the entire cut shall be examined. Failure of the pork to meet the acceptance criteria as indicated in table I shall be cause for rejection of the lot. Except for pork rejected because of freezing, defrosting, or presence of any off-condition, the pork may be reworked by the contractor and reoffered for examination. For reexamination, the sampling plan used shall be the one in table I designed for the next larger lot size than the one under which the lot was initially rejected. Pork shall not be reexamined more than one time.

TABLE I. Sampling plan for boned and trimmed pork

Lot size (pounds)	Sample size (number of sample units)	Defect Categories			
		Major		Minor	
		AC	RE	AC	RE
500 or less	13	1	2	3	4
501-1200	20	2	3	5	6
1201-3200	32	3	4	7	8
3201-10,000	50	5	6	10	11
10,001-35,000	80	7	8	14	15
Reinspection lots of 10,001-35,000	125	10	11	21	22

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

TABLE II. Boned and trimmed pork defects

Category		Defect 1/ 2/
Major	Minor	
151		Presence of blood clot measuring 0.5 inch or more in any dimension.
	201	Presence of blood clot measuring 0.3 inch or more but less than 0.5 inch in any dimension.
152		Presence of bruise measuring 1.0 inch or more in any dimension.
	202	Presence of bruise measuring 0.3 inch or more but less than 1.0 inch in any dimension.
153		Presence of bone measuring 0.3 inch or more in any dimension.
154		Presence of cartilage measuring 0.5 inch or more in any dimension.
	203	Presence of cartilage measuring 0.3 inch or more but less than 0.5 inch in any dimension.
155		Presence of major lymph gland measuring 1.0 inch or more in any dimension.
	204	Presence of exposed lymph gland measuring 0.5 inch or more but less than 1.0 inch in any dimension.
156		Presence of skin measuring 0.3 inch or more in any dimension.
157		Exposed (protruding) ligaments and tendons measuring more than 0.3 inch.
158		Presence of kidney measuring more than 1.0 inch in any dimension.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

TABLE II. Boned and trimmed pork defects (cont'd)

Category		Defect 1/ 2/
Major	Minor	
159		Presence of ham facing.
	205	Presence of shank with tendinous end showing less than 75 percent lean tissue on a cross-sectional cut surface.
	206	Presence of exposed major blood vessel measuring 1.0 inch or more in any dimension.
	207	Presence of skirt (diaphragm) or abdominal tissue.
	208	Presence of leaf, lumbar, or pelvic fat.
	209	Presence of mediastinal tissue in the first rib or sternal region.
	210	Presence of dehydrated surface measuring 1.0 square inch or more.

1/ Acceptability of product with respect to the presence of foreign material (for example: glass, dirt, insects, insect parts, hair, wood, metal) shall be determined by a Meat and Poultry Inspection Operations employee.

2/ Evidence of freezing or defrosting or presence of any off-condition (including but not restricted to being off-odor, slightly sticky, gassy, rancid, sour, or showing discoloration) shall cause rejection of the involved lot.

4.4.3 Ingredient and component examination. Conformance of ingredients and components to identify condition and other requirements shall be determined by examination of pertinent labels, markings, U.S. Grade certificates, invoices, certificates of analysis, or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.6 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.6.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty of the tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.6.2 Product inspection. Eight tray packs shall be selected at random from the lot. The eight tray packs shall be heated for 15 minutes in 140° to 150°F water, opened and inspected in accordance with table III.

a. If no defects are found, the lot shall be accepted.

b. If two or more defects are found, the lot shall be rejected.

c. If only one defect is found, a second sample of eight tray packs shall be selected at random from the lot heated as above, opened, and inspected for the defects indicated in table III. If any defect is found in the second sample, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

TABLE III. Product inspection 1/ 2/

Category	Defect
Major	
151	Drained weight of pork slices in a can is less than 62 ounces. 3/
152	Total weight of fat chunks, opaque connective tissue, ligaments, tendon, blood vessel, cartilage or glandular material in a can is greater than 3 ounces.
153	Color not characteristic of the product. (Materially darked, scorched, or oxidized)
154	Pok slices dry, rubbery, tough, or mushy.
155	Gravy consistency lumpy or excessively thick or thin.
156	Slices not shingled within a can.
157	Less than 60 approximately 1 3/4 by 4 1/2 inch intact pork slices per can.
158	Slices not uniform in thickness.
159	Presence of fat pocket greater than 1/2 inch which extends through the pork slice.

1/ The presence of any foreign material (e.g. glass, dirt incesct parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale, etc.), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

Thread for all seaming and sleeving shall be 3.3.3 Thread. The

3/ To determine drained weight, the free liquid in the can shall be poured off and the remaining contens shall be poured into a flat bottom container. A minimum of three times the tray pack can's volume of 190° to 212°F water shall be added to the container so as to cover the contents. The contents and water shall be agitated so as to liquify rendered fat and remove the gravy without breaking the pork slices. The contents shall then be poured into a U.S.Standard 1/4 inch sieve in a manner than will distribute the product over the sieve without breaking the pork slices. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at approximately a 45° angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

4.6.3 Fat and salt content testing. Nine tray pack cans shall be selected from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by an AMS agent as a reserve sample.

The three tray packs for laboratory analyses shall be individually tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Meats and Meat Products, Section: meat, except that preparation of the samples shall be as follows. The three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The lot shall be rejected if:

a. The average fat content of the three tray packs is greater than 12.0 percent.
b. The fat content of any individual tray pack is greater than 14.0 percent.
c. The salt content of any individual tray pack is less than 0.5 percent or greater than 1.25 percent.

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat or salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

4.7 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable), in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows: Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible. Minor: (1) Other required markings missing, incorrect, or illegible; (2) Interior packing with fiberboard liner or pads not as specified; (3) Reinforcement with nonmetallic strapping or tape is not used; (4) Height of box liner less than inside depth dimension of box by more than 1/8 inch or extends above the top edge of box; (5) Length or width of pads less than box dimensions by more than 1/8 inch; (6) Arrangement or number of cans not as specified.

4.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 106 ounces of the food product, sealed, and thermoprocessed as specified in 3.4, 3.5 and 3.6. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.2 Level C. The product shall be packaged as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed, in accordance with style RSC-L, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box (+0 inch, -1/8 inch). The pads shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of V3c fiberboard. The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping container shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to non-metallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pads shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.7 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

TO HEAT

a. To heat in water: Submerge unopened can in boiling water. Simmer gently 35 minutes. Avoid overheating to the point where internal pressure is evident (can shows evidence of bulging). Remove from water and open lid for serving. CAUTION: Use care when opening as pressure may have been generated within the can.

b. To heat in oven: Eith punch several holes in lid of tray can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 35 to 40 minutes until contents reach an internal temperature of 165°F.

WARNING: Do not place closed can in oven, as heating will increase internal pressure which may cause the can to burst.

YIELD

Approximately 20 servings of 3 slices each.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of packaging and packing required (see 5.1 and 5.2).
e. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article inspection. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should include specific instructions in all procurement documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Supersession data. This document includes the requirements of PD 400 -Pork Slices with Gravy, Thermostabilized, Tray Pack, dated 31 December 1980.

Preparing activity:

Army - GL

Project No. 8940-A458

☆U.S. GOVERNMENT PRINTING OFFICE: 1984—505-038/A4808

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
PP-P-002211(Army-GL)	Pork Slices, with Gravy, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK/OR, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760-5014

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:03Z
Check the source to verify that this is the current version before use.