RR-K-195J
AMENDMENT-1
February 1, 1988

FEDERAL SPECIFICATION

KETTLE, STEAM-JACKETED, (STAINLESS STEEL, STEAMHEATED)

This amendment which forms a part of Federal Specification RR-K-195J, dated January 29, 1986 is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration for the use of all Federal agencies.

PAGE 3

2.1, under Military Standards: Add the following:

"MIL-STD-167/1 - Mechanical Vibration of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited).

MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities."

PAGE 5

Add the following new paragraph:

"3.13 Human factors criteria (for Navy use only). Human factors engineering criteria, principles, and practices, as defined in MIL-STD-1472, shall be incorporated into the design of the steam-jacketed kettles. The equipment shall be designed such that all maintenance and operational tasks shall permit safe and efficient performance by the 5th percentile female through the 95th percentile male as defined in MIL-STD-1472. Particular attention shall be given to providing suitable sized access panels or openings in enclosures for servicing components or operating controls. All controls, valves, handwheels and gages shall be selected and integrated into the design of the kettles so as to meet the applicable requirements of MIL-STD-1472 and they shall be clearly and appropriately labeled to identify function. The clearance or free area required around an item shall permit an individual with applicable 5th and 95th percentile body dimensions and physical capabilities, as defined in MIL-STD-1472, to safely operate, maintain, remove or replace that item. When establishing accessibility requirements, both physical and visual access must be provided along with access for any tools, test equipment needed and parts replacement. While inspecting for defects and performing tests, the equipment shall adhere to the human factors engineering consideration listed herein."

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

PAGE 7

3.4.2, at end of the paragraph: Add "The kettle shall be insulated so as to ensure that the exterior surface temperature does not exceed 140°F."

PAGE 8

3.4.4: Delete second sentence and substitute: "A heat-resisting hand grip shall be provided to insulate any handles, such that surface temperature of the grip does not exceed 120°F."

PAGE 9

3.4.5.2: Delete in entirety and substitute:

"3.4.5.2 Tube and valve for drawoff assemblies. Drawoff assemblies shall be located tangent to the lowest point inside of the body of the kettle. The assembly shall consist of the tube specified in 3.4.5.2.1 and the valve specified in 3.4.5.2.2. Unless otherwise specified, all kettles shall be supplied with a 1-1/2 inch nominal outside diameter tube and a 1-1/2 inch nominal outside diameter valve. When specified (see 6.2), 40 gallon kettles shall be supplied with a 2 inch nominal outside diameter tube and valve. When specified (see 6.2), 60 and 80 gallon kettles shall be supplied with a 3 inch nominal outside diameter tube and valve."

Table III, delete in entirety.

3.4.5.2.1, in paragraph title: Delete "Tube" and substitute "Drawoff tube construction".

3.4.5.2.2, in paragraph title: Delete "Valve" and substitute "Drawoff valve construction".

PAGE 15

Add the following new paragraph:

"3.9 Environmental suitability. When specified for shipboard use (see 6.29), steam-jacketed kettles shall be capable of withstanding ship vibration when tested as specified in 4.4.3."

PAGE 20

4.2.3.3, line 2: Delete "4.4.1 and 4.4.2" and substitute "4.4.1, 4.4.2 and 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

PAGE 21

Add the following new paragraph:

"4.4.3 Shipboard environmental test. The following test is required for steam-jacketed kettles for shipboard use. Failure to operate satisfactorily at the conclusion of the test or evidence of breakage or excessive looseness of parts shall constitute failure of this test.

(a) Vibration test. The kettle shall be secured to a test machine and run through the vibration endurance test as specified in MIL-STD-167/1, Type I equipment. Directly after endurance test remove safety relief valve from kettle and hydrostatically test kettle at a pressure of 90 psi for 30 minutes. Kettle should show no signs of leakage, cracks or bulges. Replace safety relief valve and hydrostatically test kettle to verify that safety valve releases at a pressure not less than 45 psi but not greater than 55 psi. Leakage, cracking or bulging of the kettle or failure of safety relief valve to operate properly shall constitute failure of the test."

PAGE 25

6.2, note c: Delete (see 3.4 and 3.6.2.1) and substitute (see 3.4, 3.6.2.1 and 3.9).

6.2, note g: Delete in entirety and substitute:

"g. When drawoff tube and valve other than 1-1/2 inch nominal outside diameter is required (see 3.4.5.2)."

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD
Navy - SA, SH
DLA - GS

User Activities

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
NIH
VA - OSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0748

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.