RR-P-375B
April 1, 1971
SUPERSEDING
Fed. Spec. RR-P-375A
September 20, 1966

FEDERAL SPECIFICATION

PITCHERS, VACUUM OR INSULATED; FILLER, GLASS (REPLACEABLE)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers vacuum and insulated pitchers and replaceable glass fillers.

1.2 Classification. Pitchers and replaceable glass fillers shall be of the following types, grades, sizes, and styles as specified (see 6.2).

Type I - Pitchers, vacuum insulated, with replaceable glass filler.
  Grade A - Brass outer shell.
    Size - 10 ounce.
    Size - 20 ounce.
    Size - 1 quart.
  Grade B - Plastic outer shell.
    Size - 10 ounce.
    Size - 20 ounce.
    Size - 1 quart.
Type II - Pitchers, insulated, corrosion-resisting steel outer and inner shells.
  Size - 10 ounce.
    Style A - 4-7/8 inches high.
    Style B - 3-3/4 inches high.
  Size - 20 ounce.
  Size - 1 quart.
Type III - Filler, glass, replaceable (applicable to type I only).
  Size - 10 ounce.
  Size - 20 ounce.
  Size - 1 quart.

FSC 7350

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-380	-	Plastic Molding Material, Methacrylate.
L-P-390	-	Plastic Molding Material, Polyethylene, Low and Medium Density.
L-P-398	-	Plastic Molding Material, Styrene-Butadiene.
L-P-399	-	Plastic Molding Material, Styrene-Acrylonitrile.
QQ-A-591	-	Aluminum Alloy Die Castings.
QQ-B-613	-	Brass, Leaded and Non-Leaded; Flat Products (Plate, Bar, Sheet, and Strip).
QQ-S-763	-	Steel Bars, Shapes, and Forgings, Corrosion-Resisting.
QQ-S-766	-	Steel Plates, Sheets, and Strip - Corrosion-Resisting.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-636	-	Box, Fiberboard.
PPP-C-843	-	Cushioning Material, Cellulosic.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock, (Container Grade), and Cut Shapes.

Federal Standard:

FED-STD-123	-	Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-P-116	-	Preservation, Methods Of.
MIL-P-3065	-	Rubber, Fabricated Parts.
MIL-M-22544	-	Molding Plastic, Acrylonitrile - Butadiene - Styrene, Rigid.
MIL-P-22748	-	Plastic, Polyethylene and Copolymers, High Density, Molded and Extrusion Material.

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized and Containerized Unit Loads, 40" X 48" Pallets, Skids, Runners, or Pallet-Type Base.
MIL-STD-417	-	Rubber Compositions, Vulcanized, General Purpose, Solid (Symbols and Tests).

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Department of Health, Education and Welfare, Food and Drug Adminstration

Federal Food and Drug Cosmetics Act, Food Additive Amendment for Contact with Food

(Application for copies should be addressed to the Department of Health, Education and Welfare, Food and Drug Administration, 330 Independence Avenue, S. W., Washington, DC 20204.)

American Society for Testing and Materials (ASTM) Specification

D 2146 - Polypropylene Moulding and Extrusion Material (Tentative)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

National Motor Freight Traffic Association, Incorporated, Agent

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Attn: Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The pitchers and the replaceable glass fillers delivered under this specification shall be the manufacturers' current commercial standard product except for any changes necessary to comply with specification requirements.

3.2 Standards compliance. The materials used in the pitchers shall conform to the applicable requirements of the Federal Food, Drug and Cosmetics Act, Food Additive Amendment for Contact with Food.

3.2.1 Certification. Prior to approval of the first shipment the supplier shall furnish the contracting officer or his authorized representative a certified statement that the materials used in the pitchers he proposes to supply under this specification comply with the requirements of 3.2.

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for his pitchers and replaceable glass fillers provided the completed items comply with all provisions of this specification.

3.3.1 Brass. Sheet brass shall conform to composition 2 and brass for machined parts shall conform to composition 24 of QQ-B-613.

3.3.2 Steel, corrosion-resisting. Corrosion-resisting steel shall conform to class 302, 303, 304, or 305, condition A of QQ-S-766 or QQ-S-763, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.3.3 Plastics.

3.3.3.1 Polystyrene, modified. Modified styrene shall conform to L-P-399 or type I, class 2 of L-P-398, except that for styrene conforming to L-P-398 the minimum Izod impact strength shall be 1.8 foot pounds per inch of notch.

3.3.3.2 Acrylonitrile - butadiene - styrene. Acrylonitrile - butadiene - styrene shall conform to type IV of MIL-M-22544.

3.3.3.3 Polyethylene, virgin. Virgin polyethylene shall be high-density linear type conforming to type I, grade 1 of MIL-P-22748.

3.3.3.4 Acrylic, clear. Clear acrylic plastic shall conform to type I of L-P-380.

3.3.3.5 Polyethylene, low and medium density. The low and medium density polyethylene shall conform to type I, class 1, any grade of L-P-390.

3.3.3.6 Polypropylene, virgin. Virgin polypropylene shall conform to type I-00400 of ASTM D 2146.

3.3.4 Aluminum alloy, die casting. Aluminum alloy used for die casting shall conform to alloy No. 218 of QQ-A-591.

3.3.5 Rubber, synthetic. Synthetic rubber shall be a rubber composition meeting the requirements of type, class, grade, and suffix letters RS $310A_1B$ or RS $410A_1B$ as required of MIL-STD-417 and MIL-R-3065.

3.4 Construction.

3.4.1 Type I, pitchers, vacuum. The type I vacuum pitchers shall consist of an outer shell, an inner shell consisting of a vacuum-type replaceable glass filler, a lid, removable stopper or float closure, and a handle. The vacuum insulated glass inner shell shall be securely held within the body by means of a rubber retainer at the neck and a shock absorber at the bottom. The shock absorber at the bottom may be rubber or plastic, alone, or supported on a corrosion-resisting spring-steel retainer. Water at a temperature of 212° F. in the one quart vacuum pitcher shall not drop below 120° F. after 24 hours at room temperature when tested as specified in 4.4.1.1. Water at a temperture of 190° F. in the 10- and 20-ounce vacuum pitchers shall not drop more than 25 degrees after one hour at room temperature when tested in accordance with 4.4.1.2. When tested as specified in 4.4.2 the capacity of the type I, 1-quart pitcher shall not vary more than plus or minus 2 ounces: the capacity of the 10-ounce pitcher when filled to the brim, shall be not less than 9.75 ounces; and the capacity of the 20-ounce pitcher when filled to the brim, shall be not less than 19.5 ounces.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:09Z
Check the source to verify that this is the currentversion before use.

3.4.2 Type II, pitchers, insulated. The type II insulated pitchers shall consist of an inner and outer shell joined by welding or brazing. The spaces between the shells shall be insulated with a commercial grade of non-hygroscopic-type material. Water in the pitcher at a temperature of 190° F. shall not drop more than 50 degrees after one hour at room temperature between 68° F. and 72° F., when tested in accordance with 4.4.1.3. The size 10 ounce, style A pitcher shall have an overall height of not more than 4-7/8 inches and the diameter of the top rim shall be not more than 4 inches. The size 10 ounce style B pitcher shall have an overall height of not more than 3-3/4 inches and the diameter of the top rim shall be 3-3/8 ± 1/8 inch. The capacity of the type II 10-ounce pitchers shall not vary more than plus or minus 1/2 ounce from specified capacities when tested as specified in 4.4.2. Capacity of the 1-quart and 20-ounce pitchers shall not vary more than plus or minus 2 ounces when tested as specified in 4.4.2.

3.4.3 Type III, fillers, glass, replaceable. Type III items shall be replaceable glass fillers for the type I pitchers. The glass fillers shall be 10 ounce, 20 ounce, or 1 quart as stated in 1.2 and shall conform to the requirements specified in 3.4.4.1.5. Heat retention and capacities shall be as specified in 3.4.1 (see 4.4.1.1, 4.4.1.2, and 4.4.2).

3.4.4 Details of components.

3.4.4.1 Type I.

3.4.4.1.1 Outer shell, grade A. The outer shell of the type I, grade A pitcher shall be made of brass specified in 3.3.1. The outer shell may be made of either a lower and an upper section or a one-piece shell and a bottom. When made with upper and lower sections, the sections shall be joined by a threaded joint. When the outer shell is of one-piece construction, the outer shell shall be joined to the bottom by a threaded ring spun into the inside or outside of the outer shell base with a minimum of 6-1/2 threads per inch over a length sufficient for a screw fit of the bottom into the shell and to allow for inner shell length variations. The pouring lip flange shall be formed independently and be joined to the upper section of the outer shell.

3.4.4.1.2 Outer shell, grade B. The outer shell of the type I, grade B, 1-quart pitcher shall be formed of plastic specified in 3.3.3.1. Plastic for the outer shell of the 10- and 20-ounce pitcher shall conform to the requirements of 3.3.3.1, 3.3.3.2, or 3.3.3.3.

3.4.4.1.2.1 Lip and handle, grade B. The lip and handles of the type I grade B pitcher when not an integral part of the outer shell shall be formed of material specified in 3.3.4, 3.3.3.2, or 3.3.3.4.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the currentversion before use.

3.4.4.1.3 Handle, grade A. Handles for the type I, grade A pitcher shall be molded or formed of material specified in 3.3.3.1, 3.3.3.3, 3.3.3.4, or of general purpose phenolic.

3.4.4.1.4 Lid or float closure, grades A and B. The lid or float closure for type I, grades A and B pitchers shall be formed of the following materials at the option of the supplier:

(a) Brass specified in 3.3.1, double walled, airtight.
(b) Plastic specified in 3.3.3.1.
(c) Polyethylene specified in 3.3.3.5.
(d) Polypropylene specified in 3.3.3.6.
(e) A combination of brass and plastic or rubber.

The lid or float closure shall be double wall (airspace) watertight construction and shall fit closely over the neck to form a neat closure. The lid, if hinged, shall be operable by thumb pressure on a lid extension and be securely attached to the outer shell and lid. The hinge pin shall be made of corrosion-resisting steel or brass. When equipped with a float closure, there shall also be a removable outer lid to control the opening of the float closure.

3.4.4.1.5 Inner shell. The replaceable glass filler shall be formed of clear lime or borosilicate glass, fully annealed and free from any significant quantities of seeds, pits, stones, or striae. The filler shall be so formed as to fit snugly within the outer shell specified in 3.4.1. Its chambered surface shall be silvered and the chamber evacuated of air.

3.4.4.2 Pitchers, insulated, type II.

3.4.4.2.1 Outer and inner shells. The outer and inner shells shall be formed of corrosion-resisting steel conforming to 3.3.2.

3.4.4.2.2 Handle. The handle shall be made of corrosion-resisting steel conforming to 3.3.2 and shall be located on the side of the pitcher in accordance with the manufacturer's standard practice.

3.4.4.2.3 Lid. The lid shall be made as specified in 3.4.4.1.4, except that the material shall be the same as the outer shell. The lid of the 10- and 20-ounce pitchers shall be hinged.

3.4.5 Support bracket. When specified (see 6.2), type I and II pitchers shall be provided with a close fitting support bracket made of either one of the following materials:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

(a) Brass. The brass bracket shall consist of a brass strip band with an attached bottom strap. The circular band with attached bottom strap shall be attached to a 2-1/2 inch square brass plate with not less than four brass rivets. The brass plate shall have four holes for No. 8-32 mounting screws. Sheet brass used for the bracket shall be as specified in 3.3.1. All surfaces of the support bracket which contact the pitcher shall be lined with felt, leather, or other suitable material in accordance with the manufacturer's standard practice.

(b) Plastic. The plastic bracket shall be molded in one piece from clear acrylic plastic conforming to 3.3.3.4. The wall mounting portion of the bracket shall be not less than 2-3/4 inches square and shall have four holes for No. 8-32 mounting screws.

3.5 Finish.

3.5.1 Type I, grade A. The brass outer shell and the lid of the type I, grade A pitchers shall be nickel-chromium plated in accordance with the manufacturer's standard practice.

3.5.2 Type I, grade B. The outer shell and exterior plastic parts of the type I, grade B pitchers shall have a uniform high luster and color produced by the molding process. Color shall be in accordance with the manufacturer's standard practice.

3.5.3 Type II. The inner surface of the inner shell of the type II pitchers shall have a smooth pickled finish in accordance with the manufacturer's standard practice. The exterior metal surfaces of the pitcher shall have a 2B polish or better.

3.5.4 Support brackets. Support brackets when made of brass shall be nickel-chromium plated and polished in accordance with the manufacturer's standard practice. When made of plastic the finish shall conform to 3.5.2, with color to match outer shell.

3.5.5 Type III, replaceable glass fillers. The type III replaceable glass fillers shall be finished in accordance with the manufacturer's standard practice.

3.6 Marking.

3.6.1 Type I. Each type I pitcher shall be marked with adequate information to insure positive identification of the replaceable glass filler for reordering purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.6.2 Type II. Type II pitchers shall be marked in accordance with the manufacturer's standard practice.

3.6.3 Type III. Type III replaceable glass fillers shall be marked in accordance with the manufacturer's standard practice. Marking shall include a part or identification number.

3.7 Workmanship. The finished pitchers shall be complete, clean, and free of slivers, die marks, sharp edges, dents, scratches, and deformities.

3.7.1 Welding and brazing. Welding and brazing shall be uniform, sound, and free of burn holes, cracks, undercutting, excessive metal build-up and splatter. All scale and flux shall be removed and the welds and brazes shall be finished to blend with the joined metal surfaces.

3.7.2 Rivets. Rivets, when used, shall be tight and the heads and peened ends shall be round and in full contact with the surfaces of the joined materials. There shall be no empty rivet holes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Components and materials inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 In process inspection.

4.2.2.1 Process examination. Examination shall be made of the annealing of the glass fillers as specified in 3.4.4.1.5 to establish that no deviation is made from specified requirements. Whenever nonconformance is noted, correction shall be made to the affected items and process.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

4.2.3 End item inspection. The lot shall consist of all pitchers or glass fillers of one type, grade, size, and style offered for inspection at one time. The sample unit shall be one complete pitcher or one replaceable glass filler as applicable.

4.2.3.1 Visual examination. Examination shall be made of the pitchers, or the replaceable glass fillers, as applicable, for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 4.0 for major defects and 10.0 for total defects expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Dirty		X
Type I, grade A	Not nickel-chromium plated in accordance with manufacturer's standard practice	X	
Type I, grade B	Plastic shell and outer parts not a uniform high luster and color produced by the molding process	X	
Type II	Inner surfaces of inner shell not a smooth pickled finish in accordance with manufacurers standard practice	X	
	Not a 2B polish or better	X	
Type III	Not finished in accordance with manufacturers standard practice	X	
	Visible evidence of seeds, pits, stones, or striae		X
	Chambered surface not silvered	X	
Support bracket	Brass brackets not nickel-chromium plated	X	
Construction			
Type I	Location of rubber retainer and shock absorber not as specified	X	
	Glass inner shell (filler) missing or not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction (cont'd)			
Type I (cont'd)	Inner shell chambered surface not silvered	X	
	Lid, float closure, or stopper missing	X	
	Lid not as specified	X	
Type I, grade A	Outer shell not one or two-piece as specified		X
	Lip not as specified	X	
	Handle not as specified	X	
Type II	Lid not same material as outer shell	X	
	Lid for 10- and 20-ounce pitchers not hinged	X	
Support bracket (when furnished)	Brass support bracket not constructed with components as specified	X	
	Liner for brass bracket missing		X
	Plastic bracket not one piece		X
Identification marking	Missing, incomplete, illegible, not as specified		X

4.3.3.2 Dimensional examination. An examination shall be made to determine compliance with dimensions specified. Any nonconformance shall be considered a defect. The inspection level shall be S-3 with an AQL of 4.0 defects expressed in terms of defects per hundred units.

4.3.4 Testing of the end item. The end item shall be tested as specified in table II. The inspection level shall be S-3 with an AQL of 4.0 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE II. End item testing

Classification	Test	Test paragraph	Requirement paragraph
Type I, 1 quart	Heat retention	4.4.1.1	3.4.1
	Capacity	4.4.2	3.4.1
Type I, 10 and 20 ounce	Heat retention	4.4.1.2	3.4.1
	Capacity	4.4.2	3.4.1
Type II	Heat retention	4.4.1.3	3.4.2
	Capacity	4.4.2	3.4.2
Type III, 1 quart	Heat retention	4.4.1.1	3.4.1 and 3.4.3
	Capacity	4.4.2	3.4.1 and 3.4.3
Type III, 10 and 20 ounce	Heat retention	4.4.1.2	3.4.1 and 3.4.3
	Capacity	4.4.2	3.4.1 and 3.4.3

4.3.5 Standards compliance. Proof of compliance with the requirements of 3.2 shall be submitted to the Government representative.

4.3.6 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be as specified in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

TABLE III. Examination of preparation for delivery

Examine	Defect
Markings	Omitted: incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Components missing, damaged, or otherwise defective.
Weight	Net weight is more than specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

4.3.6.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and strapping shall be in accordance with PPP-B-636.

4.3.6.2 Examination of palletization. An examination shall be made to determine that palletization is in compliance with section 5 of this specification. Defects shall be as specified in table IV. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

TABLE IV. Examination of palletization

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.4 Tests.

4.4.1 Heat retention tests. The heat retention tests specified for the type I pitchers and the type III replaceable glass filler shall be conducted not sooner than 72 hours after drawing of the vacuum and sealing the chamber. When the type III replaceable glass fillers are being tested for heat retention they may be tested as a complete type I pitcher.

4.4.1.1 Type I and III, 1 quart. The type I, 1 quart pitcher or the type III, 1 quart replaceable glass fillers as applicable shall be filled with water at a temperature of 212 F. and stoppered with a tight fitting cork and allowed to remain in an ambient temperature of 70 $\pm$ 2 F. for not less than 24 hours. The temperature of the water shall then be measured to determine compliance with the heat retention requirements of 3.4.1 or 3.4.3 as applicable. Any nonconformance with specified heat retention requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T12:09Z
Check the source to verify that this is the currentversion before use.

4.4.1.2 Type I and III, 10 and 20 ounce. The type I, 10 and 20 ounce pitchers or the type III, 10 and 20 ounce replaceable glass fillers, as applicable shall be preheated with water between 203 F. and 207 F. for a period of three minutes. The pitcher or glass filler shall then be emptied and refilled with water at a temperature of not less than 190 F. and closed with a tight fitting cork stopper. The pitcher or replaceable glass filler shall then remain in an ambient temperature of 70 ± 2 F. for not less than 1 hour. The water temperature shall then be measured to determine compliance with the heat retention requirements of 3.4.1 or 3.4.3 as applicable. Any noncompliance with specified heat retention requirements shall consititute failure of this test.

4.4.1.3 Type II. The type II insulated pitcher shall be tested as specified in 4.4.1.2 for the type I insulated pitcher. The water temperature shall then be measured to determine compliance with the temperature retention requirements of 3.4.2. Any noncompliance with specified heat retention requirements shall constitute failure of this test.

4.4.2 Capacity. The pitcher shall be filled to capacity with water. The water shall then be poured into a graduated measuring beaker to determine compliance with the capacity requirements of 3.4.1, 3.4.2, or 3.4.3 as applicable. Any nonconformance with specified capacity requirements shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Pitchers. Each pitcher shall be individually wrapped and cushioned in cellulose cushioning material conforming to type II, class B of PPP-C-843, and packaged in a snug-fitting fiberboard box conforming to style RSC end opening, type CF, variety optional, class domestic of PPP-B-636. Box closure shall be in accordance with the appendix of PPP-B-636.

5.1.1.2 Fillers. Each filler shall be packaged in accordance with method III of MIL-P-116 in a snug-fitting paperboard box conforming to PPP-B-566. Box closure shall be in accordance with the appendix of PPP-B-566.

5.1.2 Level C. Pitchers or fillers shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Pitchers. Six pitchers of one type, size, and style only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to V2s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636. The weight of contents of each shipping container shall not exceed 65 pounds.

5.2.1.2 Fillers. Six fillers of one size only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style FOL-L, V2s of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-F-320. Each shipping container shall be closed as specified in 5.2.1.1.

5.2.2 Level B.

5.2.2.1 Pitchers. Six pitchers of one type, style, and size only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to type CF, variety optional, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636. The weight of contents of each shipping container shall not exceed 65 pounds.

5.2.2.2 Fillers. Six fillers of one size only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style FOL, type CF, variety DW, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

5.2.2.3 When specified (see 6.2), the shipping containers specified in 5.2.2.1 and 5.2.2.2 shall be V3c, V3s, or V4s, fabricated in accordance with PPP-B-636 and closed in accordance with the appendix thereto.

5.2.3 Level C. Pitchers or fillers, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

5.3 Palletization (military requirements). Unless otherwise specified (see 6.2) pitchers or fillers, packed as specified, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. Marking shall be in accordance with 5.4.1 or 5.4.2 as specified (see 6.2).

5.4.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123. Precautionary and handling markings shall apply.

5.4.2 Military agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129. Precautionary and handling markings shall apply.

6. NOTES

6.1 Intended use. The pitchers covered by this specification are intended for use in hospitals, mess halls, officers' quarters, on ships, and in similar locations.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents, as applicable:

(a) Title, number, and date of this specification.
(b) Type, grade, size, and style required (see 1.2).
(c) When support brackets are required for type I and II pitchers (see 3.4.5).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.3).
(f) When palletization is not required (see 5.3).
(g) Agency marking required (see 5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

6.3 Classification comparison. Classification comparison between superseded RR-P-375a and this revision is as follows:

RR-P-375a	RR-P-375B	Comparison notes
Type I pitcher, vacuum	Type I pitchers, vacuum insulated, replaceable glass filler	All type I pitchers are vacuum insulated and have replaceable glass fillers
Grade A - Brass outer shell and replaceable glass filler	Grade A - Brass outer shell	Indented to show grade under type I
	Size - 10 ounce Size - 20 ounce Size - 1 quart	Added to indicate sizes of type I, grade A pitchers covered
Grade B - Plastic outer shell and replaceable glass filler	Grade B - Plastic outer shell	Indented to show grade under type I
	Size - 10 ounce Size - 20 ounce Size - 1 quart	Added to show sizes of type I, grade B pitchers covered
Type II, pitchers, insulated, corrosion-resisting steel outer and inner shells	Type II, pitchers, insulated, corrosion-resisting steel outer and inner shells	No change
Size - 10 ounce	Size - 10 ounce Style A Style B	Indented to show sizes of type II pitchers coverd. Added style A and B to size 10 ounce
Size - 20 ounce Size - 1 quart	Size - 20 ounce Size - 1 quart	
Finish 1 - No. 4 luster, corrosion-resisting steel	Finish 1 - Polished corrosion-resisting steel	Indented to show finish applies to type II pitchers only. No. 4 luster requirement deleted
Finish 2 - Black enamel Finish 3 - Orange enamel Finish 4 - Olive drab enamel		Deleted

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

RR-P-375a	RR-P-375B	Comparison notes
Type II, pitchers, insulated, corrosion-resisting steel outer and inner shells (cont'd)		
Finish 5 - No. 4 luster (nickel chromium plated)	None	Deleted. Nickel-chromium plated finish applies to type I, grade A pitchers only

MILITARY CUSTODIANS:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Army - MD
Navy - MS

Preparing activity:

Army - GL

Project No. 7350-0093

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 20 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

Pitchers, Vacuum or Insulated; Filler, Glass (Replaceable) RR-P-375B

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 68 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-EQ3
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.