RR-P-375B
INT. AMENDMENT-1(Army-GL)

December 16, 1971

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

PITCHERS, VACUUM OR INSULATED: FILLER, GLASS (REPLACEABLE)

This interim amendment was developed by the U. S. Army Natick Laboratories(GL), Natick, Massachusetts 01760 based on currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations to the preparing activity at the address shown above.

The General Services Administration has authorized use of this interim amendment as a valid exception to Federal Specification RR-P-375B dated 1 April 1971.

PAGE 2

Paragraph 2.1.- Under Federal Specification: Add in proper sequence:

"L-P-393 - Plastic Molding Material, Polycarbonate, Injection and Extrusion."

"L-P-394 - Plastic Molding Material (Propylene Plastics, Injection and Extrusion)."

"L-P-1183 - Plastic Molding Material, Acrylonitrile-Butadiene-Styrene (ABS) Rigid."

PAGE 3

Paragraph 2.1.- Under Military Specifications:

Delete "MIL-M-22544-Molding Plastic, Acrylonitrile-Butadiene-Styrene,Rigid."

Add "MIL-P-46120 - Plastic Molding and Extrusion Material, Polysulfone."

Paragraph 2.2.- Delete "American Society for Testing and Materials(ASTM) Specification.

D-2146 - Polypropylene Moulding and Extrusion Material(Tentative)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street Philadelphia, PA 19103.)".

PAGE 5

Paragraph 3.3.3.2.- Delete "MIL-M-22544" and substitute "L-P-1183".

Paragraph 3.3.3.6.- Delete "-00400 of ASTM D2146" and substitute "of L-P-394".

Add new paragraphs 3.3.3.7 and 3.3.3.8 as follows:

"3.3.3.7 Polysulfone. Polysulfone shall conform to Type I, Class 1 of MIL-P-46120.".

"3.3.3.8 Polycarbonate. Polycarbonate molding material shall conform to Form 1, of L-P-393.".

Paragraph 3.4.1.- Second sentence. Delete and substitute: "At the option of the manufacturer, the type I, grade B pitcher may also have a plastic filler shield conforming to 3.4.4.1.6. The vacuum insulated glass inner shell shall be securely held in the body by a rubber retainer at the neck and a shock absorber at the bottom, except that in pitchers having a plastic filler shield, the inner shell shall be held in place by the filler shields and a shock absorber at the bottom.

PAGE 6

Paragraph 3.4.4.1.2.1.- Last line. Delete "or 3.3.3.4" and substitute "3.3.3.4, or 3.3.3.8".

PAGE 7

Paragraph 3.4.4.1.4.- Add the following:

"(f) Polycarbonate specified in 3.3.3.8."

Add new paragraph 3.4.4.1.6 as follows:

"3.4.4.1.6 Plastic filler shield, type I, grade B. Plastic filler shields, when used in type I, grade B pitchers shall be fabricated of the polysulfone specified in 3.3.3.7. The shield shall fit down inside the replaceable glass filler and conform to the capacity requirements specified in 3.4.1. The plastic filler shield shall be removable to permit replacement of the glass filler.".

Preparing activity

Army - GL



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

Project No. 7350-A146