RR-S-345C
March 28, 1975
SUPERSEDING
Fed. Spec. RR-S-345B
June 24, 1967

FEDERAL SPECIFICATION

SIFTER, FLOUR, HAND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers one type of 1-1/2 quart capacity hand operated flour sifter with crank.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-378	-	Plastic Sheet and Strip Thin Gauge (Polyolefin)
QQ-T-425	-	Tinplate (Hot Dip and Electrolytic)
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-F-320	-	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U. S. Military Property
MIL-STD-147	-	Palletized Unit Loads for 40" x 48" Pallets

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

U. S. Postal Service Regulation

(Copies of the manual may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Standard product. The flour sifters delivered under this specification shall be the manufacturer's commercially current standard product, except for any changes necessary to comply with specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.2 Materials. The materials shall conform to the requirements specified herein. Materials not definitely specified, shall be of the quality normally used for the purpose by the manufacturer in his standard commercial hand flour sifter.

3.2.1 Tinplate. Tinplate shall conform to type I, grade 1, class A2 of QQ-T-425, with a minimum of 155 pounds per base box or type II, grade 3, class A of QQ-T-425 with a minimum of 175 pounds per base box.

3.3 Construction. The flour sifter shall be constructed as specified herein. The flour sifter shall consist of a hemispherical screen mounted in a cylindrical hopper, with a handle joined to the body and a crank-operated agitator also having a handle. When tested as specified in 4.3.1, the sifter shall operate as intended and the capacity shall not be less than 1-1/2 quarts of flour.

3.3.1 Agitator. The agitator shall consist of two circles formed from smoothly tinned steel wire not less than 0.090 inch diameter centered at right angles to each other. The wire circles shall be 1/4 inch less than the inside diameter of the hopper. There shall be a crankshaft with a wood or plastic swivel handle attached to rotate the wire circles across the surfaces of the hemispherical screen.

3.3.2 Handle. The handle shall be made of tinplate specified in 3.2.1, and joined to the body of the hopper by rivets or solder and the handle shall have a smooth handgrip. The handle shall be strengthened by concaving or beading.

3.3.3 Hopper. The hopper shall be constructed of tinplate specified in 3.2.1, and shall be crimped to form a cylinder, not less than 5 inches in diameter. The hopper shall range in height from 5 to 6 inches. The top and bottom edges of the hopper shall have a half round beaded edge or a bead sealed with solder over wire, or the top edges of the hopper shall have a flat edge.

3.3.4 Screen. The screen shall be made of brass wire cloth, 0.011-inch nominal-wire diameter, 15 meshes per inch, or tinned steel screen, 0.016 inch nominal wire diameter 16 meshes per inch symmetrically and evenly formed into hemispherical shape and attached by crimping or soldering the edges to a flange on the interior of the hopper so that convexity is outward and near the bottom end of the hopper. When the hopper is placed upright on tabletop the lowest point of the screen shall be not less than 1/4 inch above tabletop.

3.4 Finish. All sharp edges, burrs, and slivers shall be removed from the finished item. All edges of tinplate where required after fabrication shall be coated with hot tin or solder.

3.5 Marking for identification. The flour sifter shall have the manufacturer's name, trademark, or trade name. All marking shall be applied in accordance with MIL-STD-130.

3.6 Workmanship. The flour sifter shall conform to the quality of product specified herein. There shall be no rust, scratches, or pitted areas on the finished product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be made in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End product inspection. The lot shall consist of all sifters offered for inspection at one time. The sample unit shall be one completely fabricated sifter.

4.2.2.1 Visual examination. Examination of the sifter shall be in accordance with table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification	
		Major	Minor
Finish	Not tinplated as specified	X	
	Not smooth continuous plating	X	
	All edges after fabrication not coated with tin or solder	X	
	Not adherent (flaking or peeling)	X	
	Porous, pitted, or corroded	X	
	Scratches, nicks, or abrasions		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship	Agitator not crank operated with handle	X	
	Handle missing	X	
	Handle does not provide a smooth handgrip		X
	Agitator does not consist of 2 circles	X	
	Crankshaft does not have wooden or plastic swivel handle	X	
	Handle not strengthened by concaving or beading	X	
	Handle not joined to the body by riveting or solder	X	
	Inadequately peened or loose rivets	X	
	Edges of hopper not as specified	X	
	Screen not attached by crimping or soldering to the hopper	X	
	Screen not made of brass cloth or tinned steel	X	
	Fractured, split, punctured, dented, bowed	X	
	Sharp burr, edge or sliver	X	
Identification marking	Missing, illegible, incomplete, or incorrect		X

4.2.2.2 Dimensional examination. Examination shall be made of the end item to determine conformance with dimensional requirements of the specification. Any nonconformance with specified requirements shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0 defects expressed in terms of defects per hundred units.

4.2.2.3 Testing of the end item. The end item shall be tested as specified in 4.3.1. Any failure shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.2.3 Examination of preparation for delivery. An examination for defects listed in table II shall be made to determine that packaging, packing, and marking as required by section 5 are complied with. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for delivery at one time. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of preparation for delivery

Examine	Defect
Marking, exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing or damaged.
Contents	Number per container is more or less than required.

4.2.3.1 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

TABLE III. Examination for palletization

Examine	Defect
Finished dimension	Length, width or height exceeds specified maximum requirements
Palletization	Not as specified Pallet pattern not as specified Interlocking of load not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application

4.3 Tests.

4.3.1 Capacity. Fill the cylindrical hopper over the wire screen with flour. Sift the flour into a container of known capacity to determine compliance with the operation and capacity requirements of 3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Each sifter shall be packaged in a loose-fitting bag made of polyethylene film nominal 0.003-inch thick conforming to type II, grade A, B, or C, finish 1 or 2 of L-P-378. All seams shall be heat sealed. The open end of the bag shall extend a minimum of 5 inches beyond the packaged item. The bag shall be closed by double folding the plastic material at the mouth and stapling or taping it to the body with pressure-sensitive tape. Alternatively, the closure of the bag may be accomplished by means of a mechanical tie (paper or plastic covered soft steel wire).

5.1.2 Level C (commercial packaging). Each sifter shall be packaged to afford adequate protection against physical damage during shipment from the supplier to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Twenty-four sifters, packaged as specified in 5.1, shall be packed upright, four in length, three in width, and two in depth in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be furnished with slotted partitions forming individual cells for each sifter. The slotted partitions shall be approximately 1/8 inch less than the inside length and width of the container and equal in height to the sifter. The two layers shall be separated with a pad cut approximately 1/8 inch less than the inside length and width of the container. The slotted partitions and layer pad shall be made from corrugated fiberboard conforming to grade W5c of PPP-F-320. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B. Unless otherwise specified (see 5.2.2.1), sifters packaged as specified in 5.1, shall be packed upright, four in length, three in width, and two in depth in a snug-fitting fiberboard shipping container conforming to style RSC type CF, variety optional or type SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be furnished with slotted partitions forming individual cells for each sifter. The slotted partitions shall be approximately 1/8 inch less than the inside length and width of the container and equal in height to the sifter. The two layers shall be separated with a pad cut approximately 1/8 inch less than the inside length and width of the container. The slotted partitions and layer pads shall be made of the same material as the container. Closure shall be in accordance with method II of the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

5.2.2.1 When specified (see 6.2), the fiberboard shipping container shall be grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Level C (commercial packing). Sifters, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with the US Postal Service Manual, Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Polyethylene-bagged packages. Polyethylene-bagged packages shall have the required information legibly printed or stamped in black directly on the bag or on a white paper label inserted within the bag so as to permit ready identification.

5.3.2 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.3.3 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.4 Palletization. When specified (see 6.2), sifters packed as specified in 5.2 shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet used shall first be approved by the contracting officer.

6. NOTES

6.1 Intended use. The flour sifter covered by this specification is intended for use in the sieving by hand, of such dry staples as flour, sugar, and salt.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Whether weather-resistant grade fiberboard shipping containers are required for level B shipment (see 5.2.2.1).
(c) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When palletization is required (see 5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Air Force - 84

Review activities:

Army - MD
Navy - MC, YD
Air Force -- 45

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS

Project No. 7330-0384

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.