RR-S-410B
August 21, 1974
SUPERSEDING
Fed. Spec. RR-S-410A
June 9, 1965

FEDERAL SPECIFICATION

SKIMMER, KITCHEN

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a stainless steel kitchen skimmer.

1.2 Classification.

1.2.1 Type and size. This specification covers one type and size of stainless steel kitchen skimmer.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

QQ-S-766 - Steel Plates, Sheets and Strip, Corrosion Resisting.
PPP-B-636 - Box, Shipping, Fiberboard.
PPP-B-665 - Boxes; Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Sanitation Foundation (NSF) Standard:

No. 2 - Food Service Equipment Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, Michigan 48105.)

3. REQUIREMENTS

3.1 NSF compliance. The skimmers shall conform to the applicable requirements of NSF Standard No. 2.

3.2 Material. Corrosion-resisting steel shall conform to either class 301, 302, 304 or 430 of QQ-S-776.

3.3 Construction. Skimmers covered by this specification shall be constructed of the materials specified in 3.2 and shall conform to the dimensions of 3.3.1 and 3.3.2. The skimmers shall be of two-piece construction, lap welded with a minimum of two spot welds or stainless steel continuous welding of handle to the body. The body shall rest over the handle. The overall projected length of the skimmer shall be 18 inches (± 1-1/2 inches). The angle between the vertical axis of the body and the handle shall be 40° (± 2°).

3.3.1 Body. The body shall have a diameter of 6 1/8 inches (± 1/4 inch) and a minimum thickness of 0.0359 inch, and a minimum of 72 holes having diameters of 1/8 inch (+ 1/16 - 1/32 inch). The body shall have a dished shape with a 5/8 inch (± 3/16 inch) height at the center.

3.3.2 Handle. The dimensions of the unformed handle shall be: developed length 15 1/8 inches minimum and width 5/8 inch, and a minimum thickness of 0.1046 inch. The main straight length of the formed handle shall be 13 1/8 inches (± 1 3/8 inches) with an open end hook 1-1/16 inches long forming a 76° ± 2° angle with the main length of handle. The remaining length of handle shall be formed to meet the overall projected length and angle requirements of 3.3.

3.4 Weld strength. When tested as specified in 4.4.2 the skimmer body and handle shall not separate.

3.5 Finish. After fabrication, skimmers shall have all rough and sharp edges removed and given a No. 4 standard stain finish. The final appearance shall be uniform with surfaces free from discolorations stains, or pits.

3.6 Marking for identification. The manufacturer's name, trade name or trademark of such known character easily identifiable with said manufacturer shall be indented on each skimmer.

3.7 Workmanship. The finished skimmers shall be clean, well made, and free from any defect which may affect appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. The sample size levels of inspection shall be in accordance with MIL-STD-105.

4.2.1 Lot. Unless otherwise specified (see 6.2) a lot shall consist of all skimmers submitted for inspection at the same time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects, end item

Examine	Defect	Classification Major	Minor
Finish	Burr or sharp edges	X	
	Pit, scratch or tool mark deep enough to hold food particles	X	
	Not No. 4 standard finish or better		X
	Pit or tool mark, slight scratches, not deep enough to hold food particles		X
	Not clean, stained or discolored		X
	Dents, buckled or wrinkled, or grind marks	X	
Construction	Malformed or damaged	X	
	Cracked or fractured metal	X	
	Any forming operation missing	X	
Welding	Spot weld not as specified	X	
	Crevice of any spot-weld joint not completely sealed all around	X	
Marking	Incomplete, incorrect, omitted or illegible		X

4.2.2 Sampling for dimensional and visual examination of the end item. Sampling of skimmers for these characteristics shall be in accordance with level S-3.

4.2.3 Sampling for tests. Samples for tests shall be in accordance with level S-2.

4.3 Inspection of preparation for delivery. An inspection shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the [illegible] rations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.

4.4 Tests.

4.4.1 Acceptable quality level. The AQL for tests shall be 6.5 percent defective.

4.4.2 Weld shear strength test. Place handle in one hand and body in other hand. Apply hand force to produce maximum force at welds parallel to handle and body in weld area.

5. PREPARATION FOR DELIVERY

5.1 Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Six skimmers shall be packaged together in accordance with method IC-2 of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Six skimmers shall be packaged together in close-fitting boxes conforming to PPP-B-665, PPP-B-676 or PPP-B-636, class domestic. The fiberboard box shall be closed in accordance with the appendix to the box specification.

5.1.3 Level C. The skimmers shall be packaged in accordance with suppliers commercial practice.

5.2 Packing. Packing shall be level A, B or C, as specified.

5.2.1 Level A. The skimmers shall be packed in a close-fitting box conforming PPP-B-636, grade A. The box shall be closed and strapped in accordance with the applicable specification or appendix thereto. The gross weight of the PPP-B-636 fiberboard shall not exceed the weight limitations of the box specification.

5.2.2 Level B. Eight unit packages of skimmers shall be packed in a close-fitting box conforming to PPP-B-636. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The skimmers shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The skimmers are intended for kitchen use to remove scum, floating substance or film from a boiling liquid.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size of lot, if different than 4.2.1.
(c) Level of packaging and packing required (see 5.1 and 5.2).

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 84

Review activity:

Army - MD

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.