[METRIC]

A-A-188B
December 31, 1996
Superseding
A-A-188A
January 9, 1990

COMMERCIAL ITEM DESCRIPTION

EYELET REINFORCEMENT, GUMMED CLOTH

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification DDD-E-940 which is canceled.

1. **SCOPE:** This Commercial Item Description covers white gummed eyelets for use as reinforcement around punched holes of loose-leaf sheets.

2 **SALIENT CHARACTERISTICS:**

2.1 The eyelet reinforcements shall be of the types, sizes, punches and tolerances indicated in table 1. The eyelets shall be circular in diameter with a center hole.

2.2 The reinforcements shall be made of bleached cloth with a non-animal adhesive on the other side. The adhesive shall be non-toxic, free of offensive odor and devoid of ingredients that may discolor the eyelet reinforcements, or the surface to which it the eyelet is applied. The adhesive shall be capable of being quickly activated with water.

2.3 Performance: The gummed surface of the eyelet shall be moistened and applied to plain bond paper. After two hours drying time, it shall not be possible to remove the eyelets without paper separation.

2.4 Bleaching: To obtain an acceptable brightness a chemical bleaching process may be used. When specified in the ordering data (See Ordering Data), the bleaching process shall not include the use of chlorine, chlorine dioxide, or other chlorine compounds. The Government reserves the right to require proof of such conformance.

ÉÍÍ»
°Beneficial comments, recommendations, additions, deletions, °
°clarification's, etc. and any data which may improve this document °
°should be sent to General Services Administration, Federal Supply °
°Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278 °
ÈÍÍ¼

FSC 7510

Workmanship: Eyelet reinforcements shall be free from tears, cuts, creases, wrinkles and any defects which may affect the appearance or serviceability of the item.

Table I

Type	Size	Punching
1	14.288 mm diameter (9/16 inch diameter)	6.350 mm diameter hole (1/4 inch diameter hole)
2	23.813 mm diameter (15/16 inch diameter)	9.525 mm diameter hole (3/8 inch diameter hole)

Tolerances allowed are +/- .794 mm (=/- 1/32 inch)

3. REGULATORY REQUIREMENTS:

3.1 The offeror/contractor is encouraged to utilize recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulations (FAR).

4. QUALITY ASSURANCE:

4.1 Product Conformance: The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PREPARATION FOR DELIVERY:

Packaging, packing and marking shall be as specified in the contract or purchase order.

6. **REFERENCED DOCUMENTS:** The issue of each document in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Federal Acquisition Regulations (FAR) are available from:

The Superintendent of Documents
Government Printing Office
Washington DC 20402

7. **NOTES:**

A. Ordering Data: Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(1) Type of eyelet.
(2) Whether chlorine or chlorine compound bleaching is acceptable.
(3) Specific packaging, packing, palletization and, marking requirements.

B. List of NSNs: 7510-00-171-1123
7510-00-171-1124
7510-00-285-5422
7510-00-285-5424

No official DOD interest	Preparing Activity GSA - FSS