[INCH-POUND]

A-A-2707
November 30, 1990

COMMERCIAL ITEM DESCRIPTION

STAPLES, HEAVY DUTY, PAPER FASTENING

The General Services Administration has authorized the use of this Commercial Item Description (CID) in lieu of Federal Specification GG-S-745 (Staples, Class A, Size 2).

This description covers preformed, heavy duty staples which are used for clinching paper.

Classification: The staples covered by this Commercial Item Description shall have the following leg lengths, as specified. The leg length tolerance shall be plus (+) 0.0156, minus (-) 0. (See Section 6, Ordering Data):

	Leg Length
Size A -	0.2500 Inch (1/4")
Size B -	0.3750 Inch (3/8")
Size C -	0.5000 Inch (1/2")

1. SALIENT CHARACTERISTICS:

A. Staples shall have 0.5000 to 0.5070 inch crowns.

B. The top face of the staple shall be 0.029 ± .002 inches wide.

C. The wire thickness shall be 0.0215 ± 0.0025

D. Each staple leg shall be perpendicular to the staple crown to within one degree.

E. Staples shall be cemented together to form a strip. Unless otherwise specified, strips shall contain no less than 98 and no more than 140 staples, and shall be supplied 5,000 (+ Unlimited, - 0) to a box.

Distribution Statement A:
Approved for public release;
distribution is unlimited.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

F. When staple strips are placed vertically (on end) on a flat, horizontal surface, they shall stand perpendicular to that surface to within one degree, in each plane.

G. The temper of the wire (carbon content) shall be such as to permit penetration and firm seated clinching without buckling or fracturing of the crown or legs. (See Section 4, Quality Assurance, Performance Test).

H. The staple legs shall have blunt or chisel-point ends.

I. Tensile strength of the staple wire shall not be less than 135,000 p.s.i. Contractor shall provide a manufacturer's certification of compliance, upon request by the government.

J. The staples shall be made of either a corrosion resistant metal or have a finish that resists corrosion. Contractor shall provide a manufacturer's certification of corrosion resistance upon request by the Government.

K. The staple shall be capable of forming either a standard clinch or a pin clinch.

L. Workmanship: Except for the leg ends, the staple strips shall be free of sharp edges. The staple strips shall also be free of any defects which impair serviceability, including, but not limited to, superfluous cement coating or burrs, or anything which might constitute a personal hazard to the user. The staples shall not exhibit evidence of deformity or cracking after testing as prescribed in Section 4, Quality Assurance, Tests.

2. APPLICABLE DOCUMENTS AND DOCUMENT SOURCES: The following documents form a part of this Commercial Item Description to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply:

Federal Standard:

Fed. Std. No. 123, Marking for Domestic Shipment (Civil Agencies)

Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, Handbooks, and Commercial Item Descriptions (CIDs), as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

Single copies of this Commercial Item Description, or other Commercial Item Descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston; New York; Philadelphia; Washington, D.C.; Atlanta; Chicago; Kansas City, MO; Fort Worth; Houston: Denver; Los Angeles; San Francisco; and Auburn, WA.

Military Standards:

MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129, Marking for Shipment and Storage

Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, or as directed by the contracting officer.

Public Law:

Public Law 94-580, Resource Conservation and Recovery Act, is part of U. S. Code, Title 42. Copies of the U. S. Code may be obtained through the Congressional Sales Office, U. S. Government Printing Office, Washington, D. C. 20402.

3. REGULATORY REQUIREMENT: The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. QUALITY ASSURANCE:

A. Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the Commercial Item Description, where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements (See Section 6, Ordering Data).

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:25Z
Check the source to verify that this is the current version before use.

B. Sampling. All sampling shall be performed in accordance with MIL-STD-105.

(1) Sampling for Visual Inspection. A random sample of staple strips shall be taken from each lot. Inspection level shall be II with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one staple strip.

(2) Sampling for Dimensional Inspection. A random sample of staple strips shall be taken from each lot. The inspection level shall be S-3 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one staple strip.

(3) Sampling for Tests. A random sample of staple strips shall be taken from each lot. The inspection level shall be S-1 with an AQL of 4.0 percent defective. The sample unit shall be one staple strip.

(4) Sampling for Preparation for Delivery. For examination of interior packaging. The sample unit shall be one shipping container fully prepared for delivery, selected at random. The inspection level shall be S-2 with an AQL of 4.0 percent defective.

C. Inspections.

(1) Visual Examination. Samples taken in accordance with paragraph 4.B.1 shall be examined to verify that the superficial product characteristics are in compliance with Section 1.

(2) Dimensional Examination. Samples taken in accordance with paragraph 4.B.2 shall be examined to verify that all dimensionally measurable product requirements are in compliance with Section 1.

(3) Tests. Samples taken in accordance with paragraph 4.B.3 shall be subjected to the following tests to demonstrate consistency in product functionality, durability, and performance:

(a) Performance Test: Bond Paper, Chemical Wood Pulp - Basis Weight 20-lb (17x22-500): Using the required bond paper, this test shall demonstrate the capability of the staples to consistently clinch 20 sheets when using Size 1 staples, 60 sheets when using Size 2 staples and 100 sheets when using Size 3 staples. Should a jam occur for which the test must be interrupted, it shall count as one malfunction. For each paper amount and corresponding staple size, the stapling operation shall be done 100 times. In order to be considered an acceptable specimen, at least 90 operations shall provide a standard clinch with no evidence of staple fracture or malformation, or malfunction due to jamming.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

(4) Examination for Preparation for Delivery. Samples taken in accordance with paragraph 4.B.4 shall be examined to determine compliance with Section 5.

5. PREPARATION FOR DELIVERY.

A. Packaging and Packing Provisions. Staple Strips totalling 5,000 staples shall be packaged to prevent damage during multiple shipments, handling, and storage. Packaged strips shall be packed in accordance with normal commercial practice. The packing container shall be closed to prevent accidental opening and shall be such to insure carrier acceptance and safe delivery to destination, complying with the rules and regulations applicable to the mode of transportation to be used.

B. Marking.

(1) Civil Agencies. In addition to any special marking required by contract or order, marking shall be in accordance with Fed. Std. No. 123. Bar Code marking is required, unless otherwise specified (See Section 6).

(2) Military Activities. In addition to any special marking required by contact or order, marking shall be in accordance with MIL-STD-129. Bar code marking is required, unless otherwise specified (See Section 6).

6. NOTES:

A. Item Identifiers/Reference Part Numbering System (For cataloging use only): (Types, Sizes, Classes, Colors, etc.)

Part Numbering System: The below example describes heavy duty staples with 1/4" legs:

AA2707 - A

Sizes (Leg Length):
A - 0.250 Inch (1/4")
B - 0.375 Inch (3/8")
C - 0.500 Inch (1/2")

B. Ordering Data: Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(1) Title, number, and date of this Commercial Item Description.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:25Z
Check the source to verify that this is the currentversion before use.

(2) Purchaser should specify desired size.

(3) Purchasers should specify arrangement for inspections and inspection facilities, if different than provisions under Quality Assurance.

(4) Purchasers should specify special packaging and packing, if different than provisions in Packaging and Packing.

(5) Purchasers should specify special marking, if different than provisions in Marking.

(6) Specify, only if Bar Code marking is not required.

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.