MILITARY SPECIFICATION

SHAPER PULSE: 10548806

This amendment forms a part of MIL-S-50673A (AR), dated 12 December 1990, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete in its entirety and substitute the following:

"*3.3.1* Vibration. The pulse shaper shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier.[a]

3.3.3, *3.3.3.1* and 3.3.3.2: Delete in their entirety and substitute the following:

"3.3.3 Altitude operating. The pulse shaper shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:33Z
Check the source to verify that this is the current version before use.

PAGE 4

Table I, Requirement No. 4, Output signal:

Delete "Pulse width: Not less than 0.5 us" and "Pulse amplitude: Not less than +15.0 V." and substitute:

"Pulse width: 1.0 ± 0.4 ps[a] and "Pulse amplitude: +20 *5 v."

PAGE 5

3.7: Delete in its entirety and substitute the following:

"3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 10

4.7.1.1: Delete first sentence and substitute the following:

"4.7.1.1 Vibration. This test shall be perfomed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein. "

PAGE 12

4.7.1.3: Delete in its entirety and substitute the following:

"4.7.1.3 Altitude operating. This test shall be perfomed as specified in Procedure II, Method 500 of MIL-STD-810 operational checkout shall be as specified in 4.7.2 and"4.7.3 for compliance with 3.3.3."

PAGE 13

4.8: Delete in its entirety and substitute the following:

"**4.8** Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph **3.7.**"

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A838)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:33Z
Check the source to verify that this is the current version before use.