MILITARY SPECIFICATION

CASE, CARTRIDGE, 105MM, M14B4

This Amendment forms a part of Military Specification MIL-C-48423A (AR) dated 29 May 1979 and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Under Specifications, Military add the following specification:

"MIL-A-2550 - Ammunition, General Specifications For"

Under Standards, Military, add the following:

"MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes"

Boxed in area at bottom of page, delete:

"Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QA, Dover, New Jersey 07801" and substitute:

"Commander, U.S. Army Armament Research and Development Center, ATTN: DRSMC-QA, Dover, New Jersey 07801-5001".

PAGE 2

2.1 Under Drawings

Delete: "U.S. Army Armament Research and Development Command (ARRADCOM)" and substitute the following:

"US Army Armament Research and Development Center (ARDC)"

FSC 1315

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

Delete: "8647259 - Chamber Gage" and substitute the following two drawings:

"8647258 - Chamber Gage
8647259 - Acceptance Check Gage"

Add new paragraph 2.3

"2.3 Order of precedence. In the event of a conflict between the text of this specification and the reference cited herein, the text of this specification shall take precedence."

PAGE 5

4.3.2 Add "(see MIL-A-48078)" to the end of the paragraph.

PAGE 8

4.4.3 Delete in its entirety and substitute the following:

4.4.3 Tool control dimensions.

a. Dimensions marked tool control shall be gaged at the beginning or end of each working day (24 hrs.), during First Article Inspection and for the first component after each tooling change, adjustment or repair. Where destruction of the component is necessary to gage such dimensions, measurements of the tool may be substituted providing the contractor has established correlation between the tool dimensions and the component dimensions prior to the start of production.

b. When the contractor has satisfied (a) above, visual inspection of the tool control dimensions(s) will be permitted. Visual inspection shall be performed every two (2) hours for each machine in operation. If any tool control dimension(s) is in doubt during visual inspection, the dimension(s) shall be immediately gaged to determine acceptability. Corrective action will immediately be instituted by the contractor whenever a defective tool control dimension is found.

PAGE 16

4.4.4.3 Add Major defect category: "Major 112", EXAMINATION OR TEST "salt spray" No. of Sample Units "(b)", REQUIREMENT PARAGRAPH "3.1", PARAGRAPH REFERENCE/INSPECTION METHOD "4.5.3.1".
Under Notes: Add "(b) sample selection and acceptance criteria for salt spray shall be in accordance with MIL-C-46487."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

PAGE 21

4.5.2 Line 3, delete "drawing 8647259" and substitute "drawing 8647258".

4.5.3.1 Line 2, delete "20 percent" and substitute "5 percent".

PAGE 24

6.6 Delete: "US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801" and substitute the following:

"US Army Armament Munitions and Chemical Command, ATTN: DRSMC-QAR-I(D), Dover, New Jersey 07801-5001".

6.7 Delete in its entirety and substitute the following:

"6.7 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, or US Army Research and Development Command (ARRADCOM) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC."

6.8 Delete in its entirety and substitute the following:

"6.8 Submission of test data and ammunition data cards. In addition to the normal distrubition of records when the cartridge case is procured by the Army Armament Munitions and Chemical Command, one copy of all ballistic test data and ammunition data cards shall be forwarded to each of the following: Commander, ARDC, ATTN: DRSMC-LCU-M and DRSMC-QAR-Q, Dover, NJ 07801-5001 and Commander, ARRCOM, ATTN: DRSMC-QAD, Rock Island, IL 61299."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1315-A619

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.