MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY: 11732350 RETICLE PROJECTOR AND ELEVATION SERVO DRIVE

This Amendment forms a part of Military Specification MIL-C-48470B(AR), dated 30 June 1981, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3.1, last line, delete:

"...shall be described by the following transfer function: $(V1-V2) = 19.35 * V_{2B} - 1.33$".

and substitute: "$|(V1-V2)| = 33.3 * |V_{2B}| - 1.33$".

PAGE 4

3.3.1 continued, second line, delete:

"...shall not be greater than the value of the following equation: $\Delta(V1-V2) = 0.05 * (V1-V2) + 0.10$"

and substitute:

"...shall not be greater than the value of the following equation: $\Delta(V1-V2) = 0.06 * |(V1-V2)| + 0.40$".

Last line, delete:

"with the following limit: $|(V1-V2)| < 27$ VRMS"

and substitute:

"with the following limit: $4\text{VRMS} < |(V1-V2)| < 27$ VRMS".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

MIL-C-48470B (AR)
AMENDMENT 1

PAGE 5

TABLE 1, Item 3.1, under characteristics delete "0.0 to -10.0 VRMS" and substitute "0.100 to 0.650 VRMS".

PAGE 7

Note 3/, delete "Measured at P1-2A with respect to P1-23A" and substitute "Measured at P1-23A with respect to P1-2A".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-A364)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.